

# Transfer and degradation of polyacrylamide based flocculants in hydrosystems: a review

Anne-Gwenaelle Guezennec, Caroline Michel, Kathy Bru, Solène Touzé, Nicolas Desroche, Inès Mnif, Mikael Motelica-Heino

### ▶ To cite this version:

Anne-Gwenaelle Guezennec, Caroline Michel, Kathy Bru, Solène Touzé, Nicolas Desroche, et al.. Transfer and degradation of polyacrylamide based flocculants in hydrosystems: a review. Environmental Science and Pollution Research, 2015, 22 (9), pp.6390-6406. 10.1007/s11356-014-3556-6. hal-01071342

# HAL Id: hal-01071342 https://brgm.hal.science/hal-01071342v1

Submitted on 6 Oct 2014

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

- 1 Title: Transfer and degradation of polyacrylamide based flocculants in hydrosystems: a review
- 2
- 3 Authors: A. G. Guezennec<sup>1</sup>, C. Michel<sup>1</sup>, K.Bru<sup>1</sup>, S. Touze<sup>1</sup>, N. Desroche<sup>2</sup>, I. Mnif<sup>3</sup>, M. Motelica-Heino<sup>4</sup>
- 4 <sup>1</sup>BRGM
- 5 <sup>2</sup> Nexidia SAS, 15 Rue de Mayence 21000 DIJON France
- 6 <sup>3</sup> Université de Nice
- 7 <sup>4</sup> ISTO, UMR 7327 CNRS-Université d'Orléans, 1A rue de la Férollerie, 45071 Orléans cedex 2
- 8
- 9 Corresponding author:
- 10 Anne-Gwénaëlle Guezennec a.guezennec@brgm.fr
- 11

- Abstract
- 13 The aim of this review was to summarize information and scientific data from the literature dedicated
- 14 to the fate of PAM-based flocculants in hydrosystems. Flocculants, usually composed of
- polyacrylamides (PAMs), are widely used in several industrial fields, particularly in minerals extraction,
- to enhance solid/liquid separation in water containing suspended matter. These polymers can contain
- 17 residual monomer of acrylamide (AMD) which is known to be a toxic compound. This review focuses
- 18 on the mechanisms of transfer and degradation, which can affect both PAM and residual AMD, with a
- 19 special attention given to the potential release of AMD during PAM degradation. Due to PAM ability to
- adsorb onto mineral particles, its transport in surface water, groundwater and soils is rather limited and
- 21 restricted to specific conditions. PAM can be also subject of biodegradation, photodegradation and
- 22 mechanical degradation but most of the studies report slow degradation rates without AMD release. In
- 23 the contrary, the adsorption of acrylamide onto particles is very low, which could favor its transfer in
- 24 surface waters and ground water. However AMD transfer is likely to be limited by quick microbial
- 25 degradation.
- 26
- 27 **Key words**: flocculation, polyacrylamide, acrylamide, environmental hazards, transfer, adsorption,
- 28 photodegradation, biodegradation, amidase
- 29

#### 1. Introduction

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

Flocculants are widely used in several industrial fields (mineral extraction, chemical industry, food processing industry, treatment of drinking water, etc.) to enhance solid/liquid separation in water containing suspended matter (Heath et al., 2006, Harford et al., 2011). In most cases, flocculants are polymers composed of polyacrylamide (PAM) (Taylor et al., 2002). PAM is a polymer with high molecular weight, synthetized from acrylamide (AMD) and acrylic acid/acrylate (AA) (Scott et al., 1996; Caulfield et al., 2002). The use of flocculants enables to increase the recycling rate of process water and to decrease sludge volumes and thus the surface of settling ponds. Those ponds are open systems with possible exchanges into the near aquatic environment (water percolation towards soils and aquifers, water seepages in natural streams or rivers...), which can lead to the dissemination of flocculants into surface and groundwaters (de Rosemond & Liber, 2004; Liber et al., 2005). The question of flocculants safety is now arising as a new key-environmental issue. The potential environmental hazard does not concern the polyacrylamide itself, which is generally considered as not toxic (Andersen, 2005), but the products of PAM degradation and the residual acrylamide contained in the flocculants due to incomplete polymerization process (Labahn et al., 2010; Young et al., 2007; Caulfield et al., 2002). AMD is reported to be a neurotoxin to humans (McCollister et al., 1964). AMD is also classified as a carcinogenic (level 2), mutagenic (level 2) and reprotoxic (level 3) compound (World Health Organization 1985; Molak, 1991). This review focuses on the fate of PAM-based flocculants in hydrosystems, with a major emphasis on the mechanisms of transfer and degradation which can affect both PAM and associated AMD. The section dedicated to transfer phenomenon will especially examine transport and reactivity with solid matrices. In the section devoted to degradation, abiotic and biotic factors will be discussed with a specific emphasis on potential hazardous AMD release during PAM degradation.

52 53

54

55

56

57

58

59

# 2. Polyacrylamide and acrylamide in flocculation processes and potential environmental hazards

The word polyacrylamide and the acronym "PAM" (for polyacrylamide) refer to a group of water soluble molecules formed by polymerization of acrylamide monomers. PAMs have been used for decades in a variety of industries and have proven particularly effective in facilitating the solid-liquid separation for waste and drinking water treatment as well as for the clarification of various types of

effluents. High molecular weight PAMs (10<sup>6</sup> to 10<sup>7</sup> g.mol<sup>-1</sup>) work as flocculants by causing suspended particles to bind together to form larger aggregates which can settle out quickly from solution leaving a clear supernatant (Heath et al., 2006). By increasing solid-liquid separation, PAMs improve water clarification processes and water quality prior to discharge, re-use or disposal. In France, for instance, the consumption of PAM-based flocculants is about 15 kt per year. In particular, the aggregate production uses about 900 t/y of PAM-based flocculants (i.e. 6% of the total consumption) as clarification aid (UNPG 2013). High molecular weight PAMs can be modified to develop non-ionic, anionic, or cationic properties for specific uses (Scott et al., 1996). However for environmental applications which are described in this article, anionic PAMs are preferred because of their extremely low aquatic toxicity compared to cationic forms (Hamilton et al., 1994; de Rosemond & Liber, 2004; Liber et al., 2005). Common anionic PAMs are usually produced by copolymerization of acrylamide and acrylic acid or one of its salts (see Fig.1). Their molecular weights vary between 3.10<sup>6</sup> and 2.10<sup>7</sup> Da. The most polyvalent anionic PAM contains around 30% of acrylate (in mol). Anionic PAMs used in flocculation applications are water-soluble and have little if any cross-linking. The molecules, when dissolved in water, are nominally linear, although they may be coiled or curled to varying degree due to either substitution along the chain or as a result of electrolytes in the solvating water (Sokja et al. 2007). PAMs can be manufactured to have different molecular weights and charge densities by varying the reaction parameters and/or the relative quantities of reagents used. The charge density of PAM is often expressed as percent anionic, referring to the percentage of its monomers that contain a charged functional group. The variations can result in significant differences in the extent to which PAM will bind to different types of particles, and thus influence the flocculation efficiency. Even among products that contain anionic PAM as their active ingredient, performance can vary substantially if the PAM charge densities or molecular weights are different. One of the primary areas of concern associated with the use of PAMs is the presence of residual monomer of AMD in the polymer product, due to incomplete polymerization process. AMD is solid at room temperature, highly soluble in water, has a low potential to partition to organic matter, and has a low volatilization potential in water. Acrylamide, often referred by the acronym AMD, is considered to be a likely human carcinogen and neurotoxin (EPA US 2010). All PAMs contain some level of residual

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

AMD. However, the amount of residual AMD can vary substantially depending on what measures were taken during the manufacturing process to maximize the extent of polymerization. Within the EU, all PAMs are required to contain less than 0.1% (w/w) of residual AMD (European Parliament 1999) unless they are classified and labeled as a Category 2 carcinogen (European Parliament 2006). More stringent thresholds are also set depending on additional regulations covering specific uses like, for example, when PAM-based flocculants are used for the treatment of drinking water (no more than 0.05% of residual AMD). Most of the commercial PAMs products complied with this requirement, even when they are not marketed for drinking water treatment. Knowledge about the fate of PAM and associated residual AMD in hydrosystems (transfer, reactivity...) is limited or non-existent in the field of the use of PAM as a flocculating agent for the treatment of waters. This monomer is water soluble and unlikely to adsorb to organic and inorganic soil components, potential for leaching and groundwater contamination are often considered as the major environmental risk associated with the use of PAMs as flocculants. Several publications have discussed the aquatic toxicity of anionic PAM in the framework of the struggle against agricultural soil erosion where PAMs are used for soil stabilization (Barvenik 1994; Seybold 1994; Entry et al. 2002; Sojka et al. 2000, 2007). These articles have disregarded its toxicity potential, based largely on theoretical grounds such as the expectation that toxicity would be mitigated by the complexation with dissolved organic matter (Goodrich et al. 1991), because any PAM leaving the field would be rapidly adsorbed to soils (Lentz et al. 2002), and also because the size of the molecule would prevent passage across biological membranes (Stephens 1991). Few authors have also studied the fate of associated residual AMD when PAMs are used for soil stabilization and demonstrated that in this context AMD undergoes a quick degradation, which prevents its dispersion in the environment (Labahn et al., 2010; Arrowood, 2008, Shanker et al., 1998; Lande et al., 1979). Even if these studies are an important source of information, their results and conclusions cannot be transposed directly to the field of PAM-based flocculants because the phenomenon that can affect the fate of PAM and associated AMD are slightly different and because PAMs used for both applications have different properties (molecular weight and charge densities). It must also be noted that in the field of flocculation, the main vector of dispersion of PAM and AMD in the environment is water, whether surface or groundwater. In the following parts of this article, the mechanisms of PAM and AMD transfer and degradation will be thoroughly reviewed and their potential impacts on the fate of PAM-based flocculants in hydrosystems will be assessed.

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

#### 3. Transfer of PAM -based flocculants in hydrosystems

#### 3.1. Sorption mechanisms

A variety of PAM and AMD molecular and environmental properties interact to affect their transfer in hydrosystems. These interactions can be significant given the range of PAM use in the environment and the number of environmental and application factors that can vary. Studies related to the environmental fate of PAM have been conducted in the framework of several uses of PAMs like soil stabilization and infiltration enhancement in agriculture (Entry et al. 2008; Spofford and Pfeiffer 1996). Advances in theoretical chemistry have contributed to improvements in PAM performances through design of molecular conformations optimally suited to given industrial and environmental applications (Bicerano 1994; Bourani 1998; Bouranis et al. 1995; Chamberlain and Cole 1996). Nevertheless, many of the general principles from these studies are worth noting as a framework for understanding the environmental behavior of anionic high molecular weight PAMs. Additionally a good deal of information on the effects of coagulants and flocculants comes from the wastewater treatment literature, although often from polymers and compounds other than PAM, or in the case of PAM, often from cationic or nonionic formulations.

#### Mechanisms of PAM-based flocculants adsorption on mineral particles

The adsorption of PAMs from aqueous media onto mineral surfaces has been largely described in the literature. For instance the adsorption of PAM on soil and clay mineral surfaces has been demonstrated to be rapid and irreversible in several studies although the degree of adsorption itself is dependent on PAM conformation, soil or mineral properties, and soil solutions characteristics (Hollander *et al.* 1981; Nabzar *et al.* 1984; Nabzar *et al.* 1988; Nabler *et al.* 1992; Pradip and Fuerstna 1980; Tanaka *et al.* 1990; Stutzmann and Siffert 1977; Theng 1982; Tekin *et al.* 2005, Tekin *et al.* 2006; Deng *et al.* 2006; Tekin *et al.* 2010). As PAM adsorption implies multisegment interactions, there is a small probability that all train segments are simultaneously detached from the surface (Theng 1982). Once adsorbed, less than 3% of the adsorbed PAM is removed from clay minerals after four consecutive washes (Deng *et al.* 2006). Moreover according to Nadler *et al.* (1992), after adsorption and drying, little desorption of anionic PAM from soil occurs. Michaels and Morelos (1955) reported that 20% hydrolysis of PAM provided the greatest degree of chain extension,

facilitating its adsorption. As PAMs are drawn to mineral particle surfaces, surface-adsorbed water is driven away because of the stronger attraction for the polymer (Parfitt and Greenland 1970). Sorption isotherms of PAM generally fit with the linear form of Langmuir equation in comparison with the Freundlich isotherm (Lu et al. 2002; Deng et al. 2006; Tekin et al. 2005; Tekin et al. 2006; Tekin et al. 2010). Additionally results of sorption experiments and parameters of Langmuir isotherm found in early studies are consistent with a favorable adsorption and a high affinity of PAM to soil minerals. This high affinity is likely due to the mechanisms of multi-segment sorption of the long chain of PAM (Theng 1982). Stutzmann and Siffert (1977) showed that the fixation mechanism of partly hydrolyzed PAM onto clays in a weakly acidic media is a chemisorption phenomenon. The anionic polyelectrolyte is in fact sorbed exclusively on the external surface of the clay, where organic molecules undergo protonation and are retained by ionic interaction. Charge transfer apparently depends on the polarizing power of the exchangeable cation of the clay and a linear relationship was found between the polarizing power of the alkali elements and the quantity of material sorbed. Hydrogen bonds are thought as the main mechanism of adsorption of polymers on mineral surfaces. Adsorption studies of clay-organic complexes have shown that two kinds of H-bonding are possible. One type of H-bonding can occur between the amide groups of PAMs and the protonated aluminol groups on the edge of clays (Laird 1997). Depending on pH value, amide group of the PAM can adsorb either on silanol anchoring sites (at pH 4) or on aluminol anchoring sites (at pH 10) (Pefferkor 1987). Another type of H-bonding was proposed between carbonyl groups and edge aluminols (Laird 1997). Infrared analysis of clay-organic complexes has shown H-bonding between amide groups of PAM and water molecules in the hydration shell of exchangeable cations of a smectite (Deng et al. 2006). Finally, ion-dipole interaction has been proposed in controlling the adsorption of PAM on smectite. This interaction takes place between exchangeable cations of smectite and the carbonyl oxygens of amide groups (CONH<sub>2</sub>) of PAM (Deng et al. 2006). For anionic PAMs, adsorption on kaolinite, illite and quartz is enhanced in the presence of divalent cations through a cationic bridge process. Cationic bridges take place between divalent cations and negative groups of anionic polymer on one hand and divalent cations and negatives sites of mineral surfaces on the other hand. This binding mode occurs at high concentrations of divalent cations (Ca2+,

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

Mg<sup>2+</sup>), and enhances the sorption of anionic polymers on negative mineral surfaces (Theng 1982 Chiappa *et al.* 1999).

Adsorption of PAMs on the mineral fraction is correlated with size of particles. Clays being the mineral components with the lowest size have more affinity for PAMs than larger particles like sand and silt (Lu et al. 2002; Gravelieng et al. 1997; Malik and Letey 1991). Clays with a high specific outer-surface area such as montmorillonite and smectite are better PAMs adsorbents than clays with low specific outer-surface areas such as kaolinite and illite (Lu et al. 2002; Deng et al. 2006; Inyang and Bae 2005). Additionally the charge repulsions confer to anionic PAM coil an extended conformation making difficult its entry in the interlayer space of clay minerals (Stuzmann and Siffert 1977). Nevertheless, a small amount of PAM molecules has been shown to penetrate in the interlayer space of montmorillonite due to its large interlayer space (Inyang and Bae 2005). It was also shown that adsorption of PAM increased on montmorillonite when the degree of hydrolysis of PAM increased. PAM indeed tends to take the conformation of an extended chain when it is highly hydrolyzed. Therefore the adsorption of PAM depends on the configuration and the volume of the solvated macromolecule (Stuzmann and Siffert 1977). In contrast, a change of molecular weight has practically no influence upon the adsorption ratio.

# Physico-chemical parameters influencing the adsorption of PAM: pH, ionic strength and temperature

The pH value influences both the structure of adsorbent, adsorbate and adsorption mechanism of PAMs on solid surfaces. The effect of pH on the polymer consists on load changes of functional groups by the phenomenon of protonation or deprotonation. At a high pH value, the carboxyl group (-COOH) of polymer can be dissociated as follows:  $(-COOH = -COO^{-} + H^{+})$ , giving the polymer a negative charge. Furthermore, amides groups can be hydrolyzed and generate carboxyl groups (-CONH<sub>2</sub> = -COOH + COO<sup>-</sup>) (Deng *et al.* 2006). The net charge of natural solids like clays and silicates also depends on the pH. For instance the edge sites of aluminosilicates minerals are amphoteric groups, able to fix or release protons. Thus, the surface charge can be positive when pH is inferior to PZC (point of zero charge), neutral when pH is equal to PZC, or negative when pH is superior to PZC. pH values inferior to the PZC induce the protonation of aluminol groups which confers to solid surfaces

a positive net charge. Inversely, at pH values superior to the PZC, aluminols sites and silanols sites are deprotonated, the surface charge becomes negative. Unlike cationic PAMs, the sorption of anionic PAMs is promoted when the surface is positively charged. This is mainly due to the reduction of electrostatic repulsions between negatives charges of polymers and the negative charges of the mineral surface. When pKa[COOH/COOT] < pH < PZC, attraction of carboxylic groups towards aluminol groups is enhanced since PAM is negatively charged and the surface is positively charged. When pH > pKa[COOH/COOT] and pH > PZC, the complete dissociation of carboxylic groups reinforces the negative charges of PAM and the surface is negatively charged. This results in the decrease of the adsorption of PAM (Lee *et al.* 1991). The adsorption of PAM tends toward zero when the pH value still increases because of the very large electrostatic repulsions and the sharp reduction of AlOH sites (Deng *et al.* 2006; Lee *et al.* 1991).

The ionic strength is also an important parameter. Benhur et al. (1992) found that the adsorption of PAMs onto illite and montmorillonite clays was generally in the order cationic > nonionic > anionic regardless of the electrolyte content of the solvating water. Water that was more saline and sodic reduced the adsorption of cationic and nonionic PAMs but increased adsorption of anionic PAMs. The results obtained in saline media may be explained by a size decrease of the PAM macromolecules, allowing a closer approach to the surface of the mineral substrate, and by a chain lengthening as the degree of hydrolysis increases, induced by the electrostatic repulsions between the COO groups of the medium. Aly and Letey (1988) found that the adsorption of anionic PAMs in water of electrical conductivity (EC) 0.7 dS m<sup>-1</sup> was greater than for water of EC of 0.05 dS m<sup>-1</sup>. Entropy change as water is displaced is an important actuating force in bringing about adsorption of negative and nonionic polymers to negatively charged clay surfaces (Lyklema and Fleer 1987; Theng 1982). As the adsorption of anionic PAMs on mineral surfaces is governed by the competition between polymer attractive interactions with solid surfaces and repulsive electrostatic forces (Lecourtier et al. 1990), the sorption of anionic polyacrylamide is increased when electrostatic repulsions are screened by cation bonding on the negatively charged surface sites (Lu et al. 2002; Lu and Wu 2003). It has also been demonstrated that the adsorption of anionic PAM on the edge surfaces of kaolinite is strongly dependent on salinity (Lee et al. 1991). Indeed, two effects have been reported. First, the adsorption of mono and divalent cations from the electrolyte on the negatively charged surface screens the

electrostatic repulsion between anionic PAM and the mineral surface. Secondary, since divalent cations are involved in the cationic bridge the sorption saturation of PAM is higher in the presence of divalent cations than in the presence of monovalent cations (Lu *et al.* 2002). Moreover cation enhancement of sorption is more effective in fine-textured soils than in coarse-textured soils.

Finally, studies conducted on the effect of temperature on the adsorption of anionic PAM have shown contradictory results. Increasing temperature (from 20°C to 60°C) was found to increase the adsorption of anionic polyacrylamide on kaolinite, sepiolite and perlite (Mpofu *et al.* 2004; Tekin *et al.* 2005; Tekin *et al.* 2006; Tekin *et al.* 2010). This effect was attributed to two phenomena. Firsly, increasing temperature results in a break of polymer-water hydrogen bonds that promotes the polymer-polymer interactions. The polymer thus adopts a more compact conformation that will adsorb more than the expanded one (Mpofu *et al.* 2004). Secondly, increasing temperature may produce a swelling effect within the internal structure of the clay so the PAM can penetrate further (Tekin *et al.* 2005).

#### 3.2. PAM Transfer

### Transfer in water

Both molecular properties and product preparation can influence PAMs behavior in hydrosystems (Callebaut *et al.* 1979). Results from monitoring of PAM concentrations in the drainage water of a tunnel in Sweden where PAM was used showed that PAMs leaked out, both in connection with the injection and in connection with after-injection using other grouting agents (Weideborg *et al.* 2001).

#### Flocculation

The general principles of flocculation involving PAMs can be easily drawn from the abundant literature dedicated to the adsorption of PAMs from aqueous media onto natural mineral surfaces (Greenlan 1963; Bottero and Lartiges 1992; Barvenik 1994; Theng 1979; Theng 1982; Sokja *et al.* 2007; Benhur *et al.* 1992; Haschke *et al.* 2002; Lu *et al.* 2002; Lurie and Rebhun 1997). In an aqueous solution with sufficient electrolytes, coulombic and van der Waals forces attract suspended particles to anionic PAM. These surface attractions stabilize the structure of the aggregates by enhancing particle cohesion. PAM efficiency as flocculants is not only due to adsorption phenomena. As can be seen on

270 conformation or "tail" conformation. Loops and tails can adsorb onto other particles enabling gathering of several particles in a process known as "polymer bridging". This phenomenon increases with the 271 272 molecular weight of PAMs. 273 The charge density plays also an important role in flocculation process. In anionic PAMs, carboxylic 274 groups are distributed regularly on the molecular chain, which enhances the polymer extension by 275 electrostatic repulsion. On another hand, those charges decrease the adsorption onto natural particles 276 charged negatively (like clay particles). The use of PAMs poorly charged and with a high molecular 277 weight usually decreases the competition between both phenomena and favor bridging processes. Small amounts of dissolved Ca<sup>2+</sup> or Mg<sup>2+</sup> can also help by shrinking the electrical double layer 278 surrounding particles and bridging the anionic surfaces of particles and anionic PAM molecules. The 279 280 mechanisms by which flocculation of suspended sediments takes place in the presence of 281 polyelectrolytes was studied by Ruehrwein and Ward (1952) who associated this effect with 282 stabilization of soil and resistance to dispersion. Benhur and Letey (1989) and Benhur et al. (1989) 283 attributed this effect to the mechanism that reduced particle dispersion when sprinkler irrigating with 284 PAM, which in turn reduced surface sealing and slowed the reduction of infiltration rate. 285 At temperatures from 6 to 29 °C, flocculation for a variety of inorganic and polymer compounds tended 286 to be slower and flocs tend to be smaller than at higher temperatures (Fitzpatrick et al. 2004; Hanson 287 and Cleasby 1990). Furthermore, floc strength seems to vary with the shear conditions of the flow 288 media in which flocs are formed. Larger flocs formed at higher temperatures are more easily disrupted 289 and less capable of reformation than flocs formed at lower temperatures (Fitzpatrick et al. 2004; 290 Yeung and Pelton 1996; Yeung et al. 1997). 291 PAM solutions usually promote flocculation of suspended solids at low concentrations but can have 292 the opposite effects at higher concentrations, where the large physical domain of the macromolecules 293 themselves interfere with flocculation and actually stabilize dispersed suspensions as viscosity 294 increases. When there is too much of PAM added in the suspension, a compression of the polymer 295 can also be observed on the particle and there is not enough sites available for bridging, which 296 decreases the flocculation efficiency. The concentration, at which the effects reverse, depends on 297 several factors including PAM molecular weight, charge and conformation of the molecule, size and 298 chemistry of the dispersed solids, and chemistry of the water, particularly its electrical conductivity

Fig. 2, adsorbed PAM can present three different conformations: "train" conformation, "loop"

(Sato and Ruch 1980). The treatment of an effluent containing suspended particles requires determining precisely the optimal concentration of PAM which must be added in order to perform an efficient flocculation. This concentration is usually proportional to the particles concentration and is almost always below 1 mg.L<sup>-1</sup> of suspension.

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

299

300

301

302

#### Transfer with suspended matter

A study measured PAM concentrations in 167-m-long PAM-treated tail ditch that received this runoff (Lentz et al. 2002). The soil was a Portneuf silt loam (coarse-silty, mixed, superactive, mesic applications Durinodic Xeric Haplocalcid) with a 1.5% slope. PAM was adsorbed to soil and removed solution as the streams traversed the soil-lined channels. The removal application rate increased with the stream sediment concentration. Additionally a previous study reported that PAM applications of 1 to 2 mg.L<sup>-1</sup> controlled furrow erosion similarly on 1.5% sloping fields (Lentz and Sojka 2000). The linear PAM molecule assumes the form of a hydrated random coil when dissolved in water. Solvated PAM molecules in the furrow stream collide with soil particles when treated water infiltrates into soil or when turbulent flow drives the molecules against entrained sediment or the wetted soil perimeter. The dissolved high molecular weight polymers are in fact readily adsorbed to soil particles via electrostatic, hydrogen, and chemical bonding, and by displacement of inner solvation-sphere water molecules (LaMer and Healy 1963; Mortland 1970; Jin et al. 1987; Malik et al. 1991; Laird 1997). As a result, incoming PAM is bound to soil in the upper 1 to 5 cm of the profile (Malik et al. 1991). Dry soil adsorbs more polymers than wet soils because sorbed water reduces the number of potential soil binding sites (Chang et al. 1991). PAM is adsorbed to particulate matter and flocculates soils suspended in water. Polymer adsorption on soil occurs rapidly during the first minutes of exposure but may continue at a reduced rate for several hours or days (Van de Ven 1994). In batch tests (soil, water, and dissolved PAM mixed in a shaker), Nadler et al. (1992) reported that little or no polymer desorbed from the soil while it remained wet, and the polymer became irreversibly bonded to the soil upon drying. In flowing systems, Lee and Fuller (1985) found that polymer adsorption rate decreased with increasing velocity of flow. Polymer desorption did not occur under quiescent conditions but was observed when the adsorbent material was subjected to flow shear. Desorption increased with the increasing flow velocity. These authors also concluded that adsorbed PAMs do not penetrate soil aggregates, but only coat and stabilize their surfaces. Malik and Letey (1991) and Nadler and Letey (1989) used tritium-labeled

polymers to determine sorption isotherms of several types of polyanions on Arlington sandy loam (coarse-loamy, mixed, thermic Haplic Durixeralfs). They interpreted their results as showing that polymer sorption was restricted to the external surfaces of soil aggregates. A similar conclusion was reached by ElHardy and Abd ElHardy (1989) who saw only limited intrusion of high molecular weight PAMs into soil aggregates. Aly and Letey (1988) showed that the water quality of the solvating water used to apply the polymers also greatly influenced the degree of adsorption.

Soils with a high clay or silt content, fine texture and low organic matter content had high sorptive affinity for PAMs. According to Lu et al. (2002), organic matter decreased the amount of anionic PAM adsorption on soil. The negative effect of organic matter on PAM sorption was attributed to the reduction of accessible sorption sites by cementing inorganic soil components to form aggregates and to the enhancement of electrostatic repulsion between PAM and soil surface by its negatively charged functional groups. The length of the polymer chain and large number of adsorption sites along the molecule contribute to PAM's adsorption always attached to the adsorption surface, preventing removal of the molecule (Nadler and Letey 1989). Because of the demonstrated high sorptive ability and low mobility (Malik and Letey 1991; Malik et al. 1991), PAM is generally regarded as incapable of penetrating soil more than a few centimeters from the soil surface. This, considered in light of the relatively slow sorption kinetics of the large PAM molecule (Lu et al. 2002), has led to recognition that the depth of PAM penetration depends on PAM properties, application method, and the soil and water properties present in the application scenario (Lu and Wu 2003). Using anionic PAMs of 10-15 mg mol<sup>-1</sup>, Lu and Wu (2003) found that PAM penetration depth was about one-eighth to one-half of the water penetration depth, with a particularly high PAM retention in the top few centimeters of the soil. The PAM retained in the top 0-2 mm of soil ranged from 16% to 95% of the total applied. PAM retention was greater at shallow depths when solution contact with the soil was favored by pore arrangement, contact time, and drier soil conditions on addition of PAM solutions.

353

354

355

356

357

358

352

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

#### 3.3. Transfer of AMD

Mobility of AMD in soils has been little studied. Adsorption of AMD on kaolinite, montmorillonite and anionic, cationic, and hydrophobic resins is insignificant (Brown *et al.* 1980), at acrylamide concentrations between 500 µg L<sup>-1</sup> and several mg L<sup>-1</sup>. Arrowood (2008), who studied the adsorption of acrylamide on different soils (silica sand, coarse sandy soil, loam soil) at AMD concentrations lower

than those tested by Brown *et al.* (1980), observed acrylamide adsorption on the three soils with better affinity for the clay one. The authors concluded that the adsorption of AMD was inversely proportional to initial concentrations of acrylamide and remains insignificant when compared to the ability of bacteria to breakdown acrylamide in natural environment. The low affinity of AMD to soil and clay minerals in particular is likely due to its high hydrosolubility and small size (Sojka *et al.* 2007). Analysis of a lake water, directly connected to groundwaters, suggest a likely transfer of AMD due to its infiltration in soils (Junqua *et al.* 2013). The half-life of acrylamide monomer in rivers ranges from weeks to months (Brown *et al.* 1980).

367

359

360

361

362

363

364

365

366

#### 4. Degradation of PAM-based flocculants

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

368

#### 4.1. Mechanisms of PAM degradation

PAM-based flocculants degradation has been mainly studied for PAMs in aqueous solutions. The degradation of PAMs results in a reduction of the molecular weight of the polymer and can adversely affect the performance of such aqueous solutions in their commercial application as flocculants. Degradation involving chain scission is accompanied by a significant change in the rheological properties of the polymer solutions and this has often been used to monitor and express the extent of the degradation. A correlation between the reduction in solution viscosity and performance as a flocculating agent has been demonstrated in number of references. However the factors leading to such degradation and the mechanisms of the degradation processes are not completely elucidated. In environmental applications (such as in flocculation processes), very few experiments have been conducted to quantify the PAM degradation in natural hydrosystems. Some reports have indicated that polyacrylamide, in the presence of sunlight and glyphosate, photolytically degrades to acrylamide monomer and this is a direct introduction of acrylamide into agricultural areas (Smith and Oehme 1993, Smith et al. 1996; Smith et al. 1997). The main difficulty encountered is due to the lack of simple methods to analyze and quantify PAM in this context. Thus what is known about PAM degradation is drawn from sparse reports, often using smaller molecular weight PAMs, or from indirect measurement of decomposition. Most studies report slow degradation rates as a result of mechanical, photochemical and biological processes.

#### Mechanical degradation

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

Aqueous solutions of PAM or floc suspensions can both undergo mechanical degradation due to a variety of processes such as stirring, pumping, injection and movement through porous media and direct mechanical load. In the aggregate treatment plant, mechanical degradation of the PAM can occur due to a shearing hydrodynamic field (mixing of the PAM-based flocculants with the process waters and transportation of the sludge to tailings ponds along pipelines through pumping) or by direct mechanical load (solid/liquid separation and sludge dewatering with a press-filter). It was reported that a shearing hydrodynamic field induced chain bond scissions leading to a decrease in the molecular weight of the polyacrylamide and then to a decrease in intrinsic viscosity of PAM solutions (Paterson and Abernathy 1970; Abdel-Alim and Hamielec 1973; Nagashiro et al. 1975; Povkh and Chernyuk 1986; Nguyen and Boger 1998; Avadiar et al. 2013). In particular, mechanical degradation of polymers used for drag reduction in a turbulently flowing liquid has been studied by several authors (Rho et al. 1996; Vlachogiannis et al. 2003; Pereira and Soares 2012). Losses in the effectiveness of the polymers in reducing drag under flow were attributed either to fractures of the PAM molecules leading to changes in the molecular weight distribution or to the fact that some or all of the degradation could be associated with a decrease of aggregation in a shear flow (Wade and Kumar 1972; Vlachogiannis et al. 2003). Regarding mechanical degradation of flocs, Tang et al. (2001) showed that the mechanical strength of the floc depends on both the interparticle forces and on the floc density. In general, the rupture of floc is classified either as "surface erosion" or as "large-scale fragmentation" (Yeung and Pelton 1996). Erosion is the separation of small particles from the floc surface and it is attributed to shearing stresses on the floc surface. Floc breakage during shear is suspected to involve the rupture of hydrogen bonds (Senden et al. 2000; Taylor et al. 2002). Fragmentation refers to the break-up of flocs into pieces of comparable size caused by pressure gradients across the entire body. Since flocs break-up occurs at the weakest point in the floc structure, this usually results in more compact aggregates, though smaller than the initial flocs. According to Caulfield (2002), it cannot be stated that under the influence of a mechanical load polyacrylamides degrade to form their constituent monomeric units such as acrylamide. Moreover, several authors reported that the flocs formed using polyelectrolytes such as PAM are reformed after being broken up but do not regain their original size and structure and form a new structure more compacted (Nguyen and Boger 1985; Leong et al. 1987;

Spicer et al. 1998). An example of experiments on mechanical degradation was performed by Rasteiro (2008) who studied the degradation under hydrodynamic shearing induced by a recirculating pump of two high molecular weight cationic PAMs used for the flocculation of precipitated calcium carbonate. For the pump speeds tested, the flocs size decrease was attributed to floc erosion but it was also stated that flocs reach another equilibrium state where aggregation and fragmentation rates are the same. Moreover, it was reported that erosion may not depend on the flocculant concentration since it depends on the interparticles bonds of the flocs; however erosion increased with the pump speed. Reflocculation occured only for the higher flocculant concentrations due to the excess of polymer and most of the flocs resulting from the reflocculation process were observed to be more compact than the original ones Rasteiro (2008). Mechanical load can also induce enough shear-induced stress to cause bond scission and the formation of a macromolecular radical (Caulfield 2002). For example, it was observed that filtration under pressure of thickened suspensions from PAM flocculation of bauxite residue or brown coal lead to significant breakdown in network structures and reduction in yield stresses (Nguyen and Boger 1985; Leong et al. 1987). The implementation of shear stresses that are higher than the initial yield stresses of flocs suspension leads then to breakdown the intricacy involved within these complex network structures (Avadiar et al. 2013). Therefore, mechanical degradation of aqueous solutions of PAM or floc suspensions often involves irreversible changes of the polymeric material including a marked reduction in viscosity and a scission of the main chain bond and thus the generation of free radicals. However, none of the studies found in

440

441

442

443

444

445

446

447

448

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

#### Photodegradation of polyacrylamide

PAM photodegradation is reported to be a free radical process that can lead to a cleavage of the polymer backbone (bond scission) and the formation of lower molecular weight products (Decker 1989; Caulfield *et al.* 2002). The C-C, C-H and C-NH bonds in PAMs have bond strengths of 340, 420 and 414 kJ mol<sup>-1</sup> which can be cleaved by wavelengths of 325, 288 and 250 nm respectively (Crosby 1976). Even if the atmosphere absorbs most of the lower spectrum (less than approximately 300 nm), it still leaves components from the UV and visible regions with sufficient energy to disrupt chemical bonds (Rabek 1996). The free radicals formed from bond scission are extremely unstable and will

the literature suggest that PAMs degrade to AMD under mechanical constraints.

react with any suitable substrate. The reactions include combination to reform the saturated carboncarbon polymer backbone, disproportionation to form an unsaturated and saturated polymer chain end and reaction with other entities present. The presence of oxygen in the system has a strong impact on photodegradation of PAM as well as the impurities contained in the initial polymer. Some authors have studied PAM degradation via advanced oxidation processes, such as Fenton (Kurenkov et al. 2002), H<sub>2</sub>O<sub>2</sub>/UV (Caufield et al. 2002), photo-Fenton (Giroto et al. 2008) and O<sub>3</sub>/H<sub>2</sub>O<sub>2</sub>/UV (Ren et al. 2006), but these reactions cannot occur in environmental conditions. Most of the studies, dedicated to PAM photodegradation in environmental conditions, focus on the potential release of AMD. This phenomenon was firstly observed by Smith et al. (1996, 1997), in controlled laboratory conditions and under environmental conditions using an aqueous solution of a PAM thickening agent (PAM mixed with glyphosate). However these results, their interpretation and the overall experimental design raised some controversy, particularly the way that PAM was prepared which could lead to incomplete dissolution of PAM (Kay-Schoemake et al. 1998a; Ver Vers 1999; Caulfield et al. 2002). Ver Vers (1999) reported work using analogous degradation conditions but yielding different results. This study points out problems in proper dilution of the emulsion and attributes the detection of small amount of AMD over time to the gradual release of unreacted AMD contaminants from the incompletely dissolved emulsion. The author concluded that PAM does not degrade to AMD monomer in the presence of sunlight, even in presence of glyphosate. Kay-Shoemake et al. (1998b) showed that the treatment of solutions of high molecular weight anionic PAMs with UV radiations reduced the PAM chain length. They found also that the photodegraded PAM samples did not support bacterial growth as sole source of carbon. As it is well recognized that acrylamide is completely biodegradable (see section VI), these results suggest that AMD is not formed during the photodegradation of the polyacrylamide. El-Mamouni et al. (2002) investigated the photodegradation of a PAM solution (PAMs molecular weight ranging between 10<sup>5</sup> and 10<sup>6</sup> daltons) exposed to UV irradiation (254 nm) prior to biomineralization. They observed a shift in the molecular weight distribution, which demonstrates the degradation of the PAM chains into oligomers. A study leaded by Caulfield et al. (2003) has reported that strong UV radiation at 254 nm released AMD from solutions of a nonionic PAM. However, the release was very small. They also noted a reduction in viscosity of the polymer solution, attributed to a lowering of the molecular weight consistent with

polymer chain scission. Suzuki et al. (1978, 1979) also reported a number of low molecular weight

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

PAM decomposition products when degraded using strong UV irradiation in the presence of ozone but didn't notice any AMD monomer release. It must be noted that the studies of Kay-Schoemake *et al.* (1998a), El Mamouni *et al.* (2002), Caulfield *et al.* (2003) and Suzuki *et al.* (1978, 1979) used UV irradiations which are much more energetic than the sunlight's wavelengths. These studies cannot confirm the attenuation of PAM by sunlight in natural environments.

Holliman *et al.* (2005) submitted samples of field-conditioned cross-linked PAM gels to a 365-nm UV radiation in a daily light-dark cycle during 5 months without detectable acrylamide release. On the other hand, they observed a gradual loss of gel properties they attribute to polymer chain scission resulting in the production of PAM fragments. More recently, a study by Woodrow *et al.* (2008) reportedAMD release resulting from sunlight irradiation of aqueous polyacrylamide/iron mixtures. A solution of commercial anionic PAM with different concentration of Fe<sup>3+</sup> (from 0.02 to 4.4 ppm) was submitted to UV irradiation in a simulator able to closely approximate solar irradiance in the troposphere (equivalent to late summer noontime sunlight at 40° latitude – 300nm). Without Fe<sup>3+</sup>, only polymer chain scission was observed through HPLC measurement and decline of average molecular weight. In the presence of Fe<sup>3+</sup>, acrylamide release was also observed at acid/neutral pH whereas at alkaline pH (~ 8.0), PAM/Fe<sup>3+</sup> remained stable under irradiation.

In conclusion, PAMs are susceptible to a wide range of photodegradative processes depending on the reaction conditions. Photodegradation results in irreversible changes in both physical and chemical properties of the PAMs, but the release of acrylamide still remains in question and would require further clarification. Moreover photodegradation of PAM was not directly demonstrated in environmental conditions in hydrosystems with field studies but only in laboratory aqueous solutions without the presence of mineral particles.

### Biological degradation

Whether they are used as flocculants for water clarification or in agricultural applications for the control of soil erosion as well as in petrochemical productions to enhanced oil recovery, PAMs are in contact with micro-organisms and can be subject to biodegradation. Most of the studies on the degradation of PAM in agricultural soils concluded that the biodegradation of PAM did not result in the formation of monomer (AMD) and that PAMs were generally resistant to microbial degradation (Caulfield *et al.* 

2002). During these applications, the degradation seemed to be most likely due to environmental factors such as UV light or chemical degradation (Seybold 1994).

The ability of bacteria to utilize PAM as sole nitrogen or sole carbon sources has been examined. Kay-Shoemake *et al.* (1998a) demonstrated that PAM can be used as an organic nitrogen source for microorganisms in soil. A bacterial growth was observed when cultures were produced on soil samples with no other source of nitrogen. Intracellular and extracellular amidase activities were detected in all the enrichment cultures able to use PAM as sole source of nitrogen and in soils treated with PAM. Haveroen *et al.* (2005) also demonstrated that the addition of PAM stimulates microbial activities and methanogenesis in anaerobic environments that are poor in nitrogen sources. In another study, Kay-Shoemake *et al.* (1998b) show that indigenous bacteria, commonly found in soils, were enabled to used PAM as sole carbon source. These results suggest that these microorganisms could hydrolyse the amine group but were enable of cleaving the main carbon chain of the polymer.

PAMs are high molecular weight polymers and are unable to pass biological membranes, so the biodegradation of these polymers requires the action of extracellular enzymes, like amidases, to degrade the carbon chain. These characteristics limit the potential of biodegradation and can be at the origin of the partial degradation of PAM (Caulfield et al. 2002). Few studies demonstrated the biodegradation of these compounds. Nakamiya and Kinoshita (1995) were the first ones to report the isolation of two PAM-degrading bacterial strains from soil samples. These strains, identified as Enterobacter agglomerans A and Azomonas macrocytogenes B, were able to reduce the molecular weight of a synthesized PAM and to degrade about 15 to 20% of the initial concentration of PAM in a synthetic medium. Another study (Matsuoka et al. 2002) reported the isolation of two PAM-degrading bacteria strains from soil, identified as Bacillus sphaericus n°2 and Acinetobacter sp. No. 11. These strains grew on medium containing PAM as sole carbon and nitrogen sources and reduced, respectively, by 16% and 19% of the initial PAM concentration. However, the degradation of PAM did not result in the formation of AMD. As previously indicated, the biodegradation of PAM require extracellular amidase activities. These enzymes seem to be enabled to liberate AMD directly from PAM but can produce lower molecular weight polymers and can alter the nature of the substituents attached to the polymer backbone (Caulfield et al. 2002, Kay-Shoemake et al. 1998b).

More recently, several bacterial strains isolated during oil recovery process have demonstrated the ability to degrade Hydrolysed Polyacrylamide (HPAM) or PAM (Ma *et al.* 2010; Wen *et al.* 2010; Bao *et* 

al. 2010). Ma et al. (2010) have isolated a Clostridium bifermentans H1 strain which can use HPMA as sole carbon source and can hydrolyse the amine to carboxyl group by the molecule chain amine hydrolysis. In their experimental conditions, the removing efficiency for HPAM reached 30.8 %. Wen et al. (2010) reported the isolation of two strains of Bacillus cereus HWBI and Bacillus flexu HWBII from activated sludge and oil-contaminated soil. Both strains were able to grow on a medium containing PAM as sole carbon and nitrogen source and to degrade PAM at different rates. After 72 hours of cultivation in a mineral salt medium (MSM) supplemented with 60 mg.L<sup>-1</sup> of PAM at 30°C, more than 70 % of the PAM was consumed and PAM was cleaved into smaller molecules. Another study reported the isolation of two Bacillus sp. strains, named PM-2 and PM-3 from production water after polymer flooding in an oilfield (Bao et al. 2010). The PAM removal efficiencies observed were lower than others studies. After 7 days of cultivation at 40°C in a basal medium containing 0.5 g.L<sup>-1</sup> of HPMA as a sole source of nitrogen, 36.3 % of the HPMA was degraded. Lower HPMA removal efficiencies were observed when HPMA was used as sole carbon and nitrogen sources. These results suggested that the PAM-degrading strains obtained more nutriments from the amide sides groups of HPAM using amidase activities compared to cleaving the main carbon chain backbone (Kay-Shoemake et al. 1998b). Although the biodegradation of PAM has been studied with isolated strains in pure culture, in practical work, the biodegradation of PAM requires interactions between several microbial species. Recently, Liu et al. (2012) have described a PAM-degrading granular sludge which degraded PAM. The PAMdegrading granules which were mostly composed by filamentous and bacilli bacteria used PAM as sole carbon and nitrogen source and degrade PAM at a high rate. PAM concentration was decreased from 66.7 mg.L<sup>-1</sup> to 32.9 mg.L<sup>-1</sup> in 24 hours but no AMD monomer was detected during the biodegradation process. The main intermediate product was identified as polyacrylic acid with a low molecular weight. These studies presented in this review demonstrated that PAM can be subjected to microbial degradation. PAM was principally used as a nitrogen source by hydrolysis of the amine groups from the polymer. The presence of glucose at low concentrations which can be used as co-metabolism substrate can improve the PAM degradation but the biodegradation efficiency seems to be affected by the initial concentration of PAM (Wen et al. 2010). The biodegradation of PAM induced changes in the structure of the polymer (reduction of the molecular weight) but no evidence of release of AMD

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

monomer has been found. Although amidases are involved in the mechanism of degradation of PAM, the reaction pathway for the microbial degradation of PAM is not clearly identified.

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

568

569

#### 4.2. Mechanisms of acrylamide degradation

#### Bio-degradation of acrylamide

AMD has an inhibitory effect on sulfhydryl proteins and hence on growth of microorganisms (Cavins and Friedman 1968). However, some microorganisms are able to grow in the presence of AMD and degrade this molecule. The microbial degradation of AMD has been demonstrated for several decades in studies investigating the behavior, fate and impacts of AMD in natural environments amended with PAMs. Microbial degradation was shown to occur in soils (Shanker et al. 1990, Shukor et al. 2009a), sediments (Labahn et al. 2010), wastewater (Buranasilp and Charoenpanich 2011, Nawaz et al. 1996) and hydrosystems (Labahn et al. 2010) and is mediated by microorganisms commonly presents in these environments. Most studies deal with the biodegradation of AMD by bacteria but some fungi have also been shown to degrade AMD. In particular, filamentus fungi such as some strains of Aspergillus oryzae have interesting AMD degradation ability (Wakaizumi et al. 2009). Among bacteria having an AMD degrading ability, most documented belong to species within the genera Bacillus (Shukor et al., 2009a), Pseudomonas (Labahn et al. 2010, Sathesh Prabu and Thatheyus 2007, Shanker et al. 1990, Shukor et al. 2009b) and Rhodococcus (Nawaz et al. 1998). However it is now establish that this activity is more widespread among bacteria such as Enterobacter aerogenes (Buranasilp and Charoenpanich 2011), Enterococcus faecalis (Buranasilp and Charoenpanich 2011) Klebsiella pneumoniae (Nawaz et al. 1996), Burkholderia sp., Xanthomonas maltophilia (Nawaz et al. 1993), Kluyvera georgiana (Thanyacharoen et al. 2012), Variovorax boronicumulans (Liu ZH. et al. 2013), Geobacillus thermoglucosidasius (Cha and Chambliss 2013), Ralstonia eutropha (Cha and Chambliss 2011) or Arthrobacter strains (Yamada et al. 1979). The concentration of AMD that can be tolerated and degraded depends on the bacterial strain. As an example and among strains that tolerate the higher concentration of AMD, Bacillus cereus is able to degrade and assimilate AMD at concentrations as high as 3 g. L<sup>-1</sup> (Shukor et al. 2009a). Shanker et al. (1990) isolated a Pseudomonas sp. strain able to degrade 4 g. L<sup>-1</sup> AMD, and Enterobacter aerogenes was shown to grew well in the presence of 5 g. L<sup>-1</sup> AMD (Buranasilp and Charoenpanich 2011). It has also been demonstrated that bacteria able to degrade AMD are also able to degrade

598 other aliphatic amides such as acetamide, urea, propionamide (Buranasilp and Charoenpanich 2011; 599 Shukor et al. 2009a). 600 The biodegradation of AMD was first shown to be aerobic but recent studies have demonstrated the 601 involvement of some bacteria in the anaerobic biodegradation of AMD. In particular, nitrate reducers 602 have been shown to significantly remove AMD (Labahn et al. 2010). These authors also demonstrated 603 the potential of sulfate- and iron-reducers to degrade AMD. The biodegradation of AMD leads to the 604 production of acrylic acid (AA) and ammonia (NH<sub>3</sub>). This could explain that AMD degrading 605 microorgansims use AMD as nitrogen source and sometimes also as carbon source, and that some 606 bacteria can grow as AMD as the sole sources of N and C (Shukor et al. 2009a, Nawaz et al. 1994, 607 1996). From an experimental point of view, AMD can be analyzed directly either by HPLC or by UPLC 608 depending on the concentration (Togola et al., 2014; Guezennec et al., 2014; Touze et al., 2014; 609 VerVers, 1999). The degradation of AMD can also be easily monitored by the quantification of 610 ammonia that can be achieved using indicator such as Phenol red that changes in color (from red to 611 pink) in the presence of ammonia (Santoshkumar et al. 2010). 612 Many studies also underlined that the AMD biodegradation activity of free cells and immobilized cells 613 can be different. It is in fact usually admitted that immobilized bacterial technology offers several 614 advantages over the application of free cells in the degradations of pollutants (Nawaz et al. 1998): 615 immobilized cells are known to retain high catabolic activity, can be reused, efficiently mineralize 616 substrates and offers physical protection from predators and parasites. Nawaz et al. (1998) thus 617 demonstrated that immobilized cells of Rhodococcus sp. rapidly degraded 64 and 128 mM AMD in 3 618 and 5 hours respectively whereas free cells took more than 24 h to degrade 64 mM AMD. Moreover 619 an AMD concentration of 128 mM inhibited the growth of the free cells. Sathesh Prabu and Thatheyus 620 (2007) observed that free Pseudmonas aeruginosa cells began the degradative activity of AMD only 621 after incubation of 24 h, while immobilized cells started before 24 h. On the opposite, Buranasilp and 622 Charoenpanich (2011) showed that AMD degradation by immobilized cells of Enterobacter aerogenes 623 was slower than that of free cells. This could be explained by an inappropriate immobilization process 624 or difficulties in substrate-cell contact.

In addition to the state (free or immobilized) of cells, the biodegradation of AMD is influenced by several physical factors such as AMD concentration, temperature, pH, the presence of metals. Nawaz et al. (1998) demonstrated that the biodegradation of *Rhodococcus sp.* was lower at low temperature

625

626

(less than 60% of AMD was degraded at 10°C in 4 h whereas 100 % of AMD was degraded in less than 3 h at 28°C and 45°C). An incubation temperature of 55°C completely inhibited the degradation of AMD by this strain. pH 7 favored maximum degradation of AMD, and activity was slower at pH 8 and very little degradation was measured at pH 6. These authors also demonstrated that nickel and cobalt slowed the AMD degradation ability (when used at 5 mM) or inhibit (when used at 10 mM) the AMD degradation ability. The highest rate of degradation of AMD was observed in the presence of iron but iron concentrations higher than 10 mM inhibited AMD degradation. Sathesh Prabu and Thatheyus (2007) showed that mercury and chromium inhibited AMD degradation by *Pseudomonas aeruginosa* while nickel enhanced the process.

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

628

629

630

631

632

633

634

635

636

#### AMD biodegradation in environmental conditions

If numerous authors have investigated the mechanisms of AMD biodegradation and the microorganisms involved, very few have quantified AMD biodegradation rate and kinetics in environmental conditions (temperature, AMD concentration, natural samples...). Those study exhibit contrasting results (see Table 1) and are difficult to compare since most of biodegradation tests have been conducted in various range of AMD concentration. The work carried out by Labahn et al. (2010) on natural water and slurry samples spiked with 50 µg.L<sup>-1</sup> AMD show the impact of the temperature on AMD biodegradation: at 15°C, no degradation is detected after 72h whereas at 25°C, AMD degradation is complete after 24h. These results confirm those obtained by Nawaz et al. (1998) in controlled laboratory biodegradation study using pure strain of *Rhodococcus* sp (see section above). Croll (1974) investigated AMD biodegradation in river water samples spiked with 10 µg.L<sup>-1</sup> AMD. One of the water samples was inoculated with a culture capable of degrading acrylamide. In this case, AMD degradation was complete after 50h, the lag period being 5h. In water samples which were not inoculated, the time required to fully degrade AMD reached more than 300h with a lag period of 50h. Brown (1979) used also river water samples but with higher concentration of AMD (5 mg.L-1) and investigated the influence of light on the biodegradation. In both cases (with and without light), the results were the same: AMD was fully degraded after 125h with a lag time of 75h. In a more recent study Ver Vers (1999) demonstrated that the time required for complete AMD biodegradation could vary from 480h to more than 1100h according to the type of water samples (tap, river and lake). For

the author, those differences could indicate that some species in the water may be interacting with AMD, either accelerating or hindering monomer degradation.

The results obtained by these author show that AMD biodegradation is probably influenced by different types of factors such as the initial AMD concentration, the nature of the media in which the degradation occurs, its microbial composition... Given the conditions used, the degradation can be quick but the time required for a complete degradation of AMD is never lower than 1 day. In some cases several days are needed to degrade the monomer.

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

ammonia (Sharma et al. 2009).

657

658

659

660

661

662

663

#### Metabolism of acrylamide and enzymes involved in bio-degradation

As mentioned before, AMD can be degraded by microorganisms under aerobic and anaerobic condition, and serves as nitrogen and/or carbon sources. Despite the fact that microbial degradation of acrylamide has been explored extensively, the metabolic pathways of degradation are unclear. The microbial degradation of AMD is initially due to the presence of an enzyme named acylamide amidohydrolase (E.C. 3.5.1.4) or amidase. Amidases catalyze the hydrolysis of an amide to free carboxylic acids and free ammonium. In the case of acrylamide, the AMD is deaminated to ammonia and acrylic acid (AA). These enzymes belong to the family of hydrolases which acts on carbonnitrogen bonds other than peptide bonds. They are ubiquitous enzymes that can have various biological functions and the substrate preferences differ. In their review, Sharma et al. (2009) widely described these enzymes, their uses in industries (and their potential applications in the production of various chemicals), their structural and biochemical properties, substrates and some purification protocols. Amidase activity has been identified in various bacteria genus, commonly found in soils, including Rhodococcus, Bacillus, Brevibacterium, Alcaligenes and Pseudomonas and in fungi (Kay-Shoemake et al. 1998b, Wakaizumi et al. 2009). These micro-organisms are able to produce a single amidase or numerous isoenzymes during growth with amide substrate. Furthermore, amidases exhibited enzymatic activity with relatively limited substrate specificity while others are able to hydrolysis a broad range of spectrum. Among amidases, some have been demonstrated to be involved in the first step of the AMD-degrading microbial pathways for the catalytic hydrolysis of AMD to acrylic acid and Although some amidases are constitutive (Nawaz et al. 1994), microbial amidases are generally inducible. It has been demonstrated that amides and AMD can be an inducer of amidase expression and some carbon sources as glucose or succinate can induce a catabolic repression (Potts and Clarke 1976, Sharma et al. 2009). The regulation of amidase (encoded by amiE gene) expression has been study in Pseudomonas aeruginosa. In this microorganism, the induction of amidase synthesis is positively regulated by a regulatory protein encoded by amiR and a second regulatory gene, amiC, which negatively regulates amidase expression (Clarke et al. 1981, Cousens et al. 1987, Wilson. and Drew 1991, Wilson et al. 1993, Wilson and Drew 1995). However, under non-inducing condition, low levels of amidase activity are always present within the cells. But, the cellular mechanism for induction or sensing remains unclear because the PAM-polymer is too large to enter the cells and to act as a direct inducer. Shanker et al. (1990) have demonstrated that addition of glutamate or ammonium sulfate as additional nitrogen source induced increase in degradation potential. Several amidases using AMD as substrate have been purified from AMD-degrading bacteria (Cha and Chambliss 2013; Egorova et al. 2004; Lavrov et al. 2010; Liu et al. 2013; Makhongela et al. 2007; Nawaz et al. 1994; Nawaz et al. 1996; Ohtaki et al. 2010; Syed et al. 2012). The amidases purified from AMD-degrading bacteria are mainly monomer but that from Burkholderia sp. is a homotetramer (Syed et al. 2012). The molecular weight, pH and temperature optima depend on the enzyme (see Table 2). It has been also demonstrated that the catalytic hydrolysis of AMD by amidase can be inhibited or enhanced by metals (Nawaz et al. 1994). These authors showed that amidase activity of Rhodococcus sp. was enhanced by Fe<sup>2+</sup>, Ba<sup>2+</sup> and Cr<sup>2+</sup> but not dependent on these cations. On the other side, the enzyme activity was partially inhibited by Mg2+ and totally inhibited in the presence of Ni<sup>2+</sup>, Hg<sup>2+</sup>, Cu<sup>2+</sup> and Co<sup>2+</sup>. The biodegradation of AMD requires not only amidase but also enzymes able to metabolize the intermediate products. Indeed, the biodegradation of AMD induces the production of ammonia and acrylic acid. However, the subsequent fate of these products is not clear but probably involves specific catabolic pathways. For AMD degrading-bacteria, AA is probably reduced to generate energy for bacterial growth but the catabolic pathway is not clear. Wampler and Ensign (2005) suggested that AA is degraded to β-hydropropionate via hydroxylation reaction, then oxidized to CO<sub>2</sub> or reduced to propionic acid. Recently, Charoenpanich and Tani (2014) have studied the response of an acrylamidedegrader Enterococcus aerogenes to AMD using proteome analysis. These authors have identified

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

fifteen proteins differentially expressed after growth in presence of AMD and have proposed a model of metabolic pathway of AMD degradation based on these results (see Fig. 3).

Finally, the identification of a "universal" pathway and the enzymes involved in AMD metabolism in prokaryotes remains a challenge for the optimization of the bioremediation of AMD.

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

716

717

718

719

#### 5. Conclusion

This review summarizes the literature which gives information and scientific data on the fate of PAMbased flocculants in hydrosystems. PAM and associated AMD have been considered and three main families of phenomenon have been investigated: transport, adsorption and degradation. Most of the information gathered in this review was derived from studies conducted in the frame of PAM use for agricultural application. Due to PAM ability to adsorb onto mineral particles, its transport in surface water, groundwater and soils is rather limited and restricted to specific conditions. PAM adsorption is rapid and irreversible, and desorption occurs only at a very small extent. In the contrary, the adsorption of acrylamide onto particles is very low, which is likely due to its high hydrosolubility and small size. This low affinity to soil and clay minerals could favor its transfer in surface waters and ground water, but very few studies reports AMD analysis in natural water. Moreover, several studies have demonstrated microbial degradation of acrylamide in environments amended with polyacrylamide. The biodegradation of acrylamide could thus limit its transfer in the environment. PAMs are high molecular weight polymers and are unable to pass biological membranes, so the biodegradation of these polymers requires the action of extracellular enzymes, like amidases, to degrade the carbon chain. These characteristics limit the potential of PAM biodegradation. PAM can be also subject of photodegradation and mechanical degradation. In any case, most of the studies report slow degradation rates without AMD release. The main conclusion of this review is that, despite the abundant literature dedicated to PAM use as flocculants, there is an obvious lack of pertinent and detailed data about the behavior, the fate and the impact of PAM-based flocculants in environments. Lot of work has still to be carried out to elucidate the mechanisms of degradation processes as well as to quantify the transfer of PAM and AMD in hydrosystems.

743

744

745

**Acknowledgments:** The research leading to this publication has received funding from the ANR in the framework of AquaPOL project (CES programme, project n°1443).

746	
747	References
748	
749	Abdel-Alim AH, Hamielec AE (1973) Shear degradation of water-soluble polymers. I. Degradation of
750	polyacrylamide in a high-shear couette viscometer. J. Appl. Polym. Sci. 17:3769-3778
751	Aly SM, Letey J (1988) Polymer and water-quality effects on flocculation of montmorillonite. So
752	Science Society of America Journal 52:1453-1458
753	Andersen, F.A. 2005. Amended final report on the safety assessment of polyacrylamide and
754	acrylamide residues in cosmetics, International Journal of Toxicology, 24:21-50.
755	Arrowood TJ (2008) Determining the Fate and Transport of the Acrylamide Monomer (AMD) in Soi
756	and Groundwater Systems, University of Nevada, University of Nevada at Las Vegas, Las
757	Vegas, NV, United States (USA), 132 pp
758	Avadiar L, Leong Y, Fourie A, Nugraha T (2013) Behaviours of Kaolin Suspensions with Differen
759	Polyacrylamide (PAM) Flocculants under Shear. Chemeca 2013, Barton, ACT, 2013
760	Bao M, Chen Q, Li Y, Jiang G (2010) Biodegradation of partially hydrolyzed polyacrylamide by
761	bacteria isolated from production water after polymer flooding in an oil field. J. Hazard. Mater
762	184:105-110
763	Barvenik FW (1994) Polyacrylamide characteristics related to soil applications. Soil Science 158:235
764	243
765	Benhur M, Faris J, Malik M, Letey J (1989) Polymers as soil conditioners under consecutive irrigations
766	and rainfall. Soil Science Society of America Journal 53: 1173-1177
767	Benhur M, Letey J (1989) Effect of polysaccharides, clay dispersion, and impact energy on wate
768	infiltration. Soil Science Society of America Journal 53:233-238
769	Benhur M, Malik M, Letey J, Mingelgrin U (1992) Adsorption of polymers on clays as affected by clay
770	charge and structure, polymer properties, and water-quality. Soil Science 153:349-356
771	Bicerano J (1994) Predicting key polymer properties to reduce erosion in irrigated soil. Soil Science
772	158 :255-266
773	Bottero, Lartiges (1992) Séparation liquide/solide par coagulation-floculation : les
774	coagulants/floculants, mécanismes d'agrégation, structures et densité des flocs. Mines e
775	Carrières A

776	Bouranis DL, Theodoropoulos AG, Drossopoulos JB (1995) Designing synthetic-polymers as soil
777	conditioners. Communications in Soil Science and Plant Analysis 26:1455-1480
778	Bouranis DL (1998) Designing synthetic soil conditioners via postpolymerization reactions. Handbook
779	of Soil Conditioners, 333-362
780	Brown L, Rhead M (1979) Liquid-chromatographic determination of acrylamide monomer in natural
781	and polluted aqueous environments. Analyst 104:391-399
782	Brown L, Bancroft KCC, Rhead MM (1980) Laboratory studies on the adsorption of acrylamide
783	monomer by sludge, sediments, clays, peat and synthetic resins. Water Research 14:779-781
784	Buranasilp K, Charoenpanich J (2011) Biodegradation of acrylamide by Enterobacter aerogenes
785	isolated from wastewater in Thailand. J Environ Sci (China) 23:396-403
786	Callebaut F, Gabriels D, De Boodt M (1979) The effect of polymer structure on soil physico-chemical
787	properties and soil water evaporation. Journal of Chemical Technology and Biotechnology.
788	29(12):723–729
789	Caulfield MJ, Qiao GG, Solomon DH (2002) Some aspects of the properties and degradation of
790	polyacrylamides. Chem Rev 102:3067-84
791	Caulfield MJ, Hao X, Qiao GG, Solomon DH (2003) Degradation on polyacrylamides. Part I. Linear
792	polyacrylamide. Polymer 44:1331-1337
793	Cavins JF, Friedman M (1968) Specific modification of protein sulfhydryl groups with alpha,beta-
794	unsaturated compounds. J Biol Chem 243:3357-60
795	Cha M, Chambliss GH (2011) Characterization of Acrylamidase isolated from a newly isolated
796	acrylamide-utilizing bacterium, Ralstonia eutropha AUM-01. Curr. Microbiol. 62:671-678
797	Cha M, Chambliss GH (2013) Cloning and sequence analysis of the heat-stable acrylamidase from a
798	newly isolated thermophilic bacterium, Geobacillus thermoglucosidasius AUT-01.
799	Biodegradation 24:57-67
800	Chamberlain P, Cole R (1996) Influence of structure and formulation on the efficacy of
801	polyacrylamides as soil stabilizers, Managing Irrigation-Induced Erosion and Infiltration with
802	Polyacrylamide, College of Southern Idaho, Twin Falls, ID, USA, pp. 83-87
803	Chang SH, Ryan ME, Gupta RK. Swiatkiewicz B (1991) The adsorption of water soluble polymers on
804	mica, talc limestone, and various clay minerals. Colloids and Surfaces 59:59-70

805	Charoenpanich, J and Tani, A. (2014). Proteome Analysis of Acrylamide-induced Proteins in a Novel
806	Acrylamide-degrader Enterobacter aerogenes by 2D Electrophoresis and MALDI-TOF-MS.
807	CMU. J. Nat. Sci. 13:11.
808	Chiappa L, Mennella A, Lockhart TP, Burrafato G (1999) Polymer adsorption at the brine/rock
809	interface: the role of electrostatic interactions and wettability. Journal of Petroleum Science
810	and Engineering 24:113-122
811	Clarke PH, Drew RE, Turberville C, Brammar WJ, Ambler RP, Auffret AD (1981) Alignment of cloned
812	amiE gene of Pseudomonas aeruginosa with the N-terminal sequence of amidase. Biosci Rep
813	1:299-307
814	Cousens DJ, Clarke PH, Drew R (1987) The amidase regulatory gene (amiR) of Pseudomonas
815	aeruginosa. J Gen Microbiol 133:2041-52
816	Croll BT, Arkell GM, Hodge RPJ (1974) Residues of acrylamide in water. Water Research 8, 989-993
817	Crosby DG (1976): Herbicide photochemical decomposition. In: Kearney PCaK, D.D. (Editor),
818	Berbicides: Chemistry Degradation and Mode of Action. Marcel Dekker Inc., New York, pp.
819	836-841
820	de Rosemond SJC, Liber K (2004) Wastewater treatment polymers identified as the toxic component
821	of a diamond mine effluent. Environ. Toxicol. Chem. 23:2234–2242.
822	Decker C (1989) Effect of UV radiation polymers. In: Cheremisinoff NP (Editor), Handbook of Polymer
823	Science and Technology. Marcel Dekker Inc., New York, pp. 541-608
824	Deng YJ, Dixon JB, White GN, Loeppert RH, Juo ASR (2006) Bonding between polyacrylamide and
825	smectite. Colloids and Surfaces a-Physicochemical and Engineering Aspects 281:82-91
826	Egorova K, Trauthwein H, Verseck S, Antranikian G (2004) Purification and properties of an
827	enantioselective and thermoactive amidase from the thermophilic actinomycete
828	Pseudonocardia thermophila. Appl. Microbiol. Biotechnol. 65:38-45
829	El-Mamouni R, Frigon JC, Hawari J, Marroni D, Guiot S (2002) Combining photolysis and
830	bioprocesses for mineralization of high molecular weight polyacrylamides. Biodegradation
831	13:221-227
832	ElHardy OA, Abd ElHardy BM (1989) The interaction between polyacrylamide as a conditioner for
833	sandy soils and some plant nutrients. I. Effect on the mechanical strenghy and stability and
834	soil structure. Egyptian Journal of Soil Science 219:51-56

835	Entry JA, Sojka RE, Watwood M, Ross C (2002) Polyacrylamide preparations for protection of water
836	quality threatened by agricultural runoff contaminants. Environ Pollut 120:191-200
837	Entry JA, Sojka RE, Hicks BJ (2008) Carbon and nitrogen stable isotope ratios can estimate anionic
838	polyacrylamide degradation in soil. Geoderma 145:8-16
839	EPA US (2010) Toxicological Review of Acrylamide in Support of Summary Information on the
840	Integrated Risk Information Systems (IRIS), U.S. Environmental Protection Agency
841	European Parliament (1999) Directive 1999/45/EC concerning the approximation of the laws,
842	regulations and administrative provisions of the Member States relating to the classification,
843	packaging and labelling of dangerous preparations. Official Journal of the European Union
844	L200/1. European Union, Brussels
845	European Parliament (2006) Regulation 1907/2006/EC concerning the Registration, Evaluation,
846	Authorisation and Restriction of Chemicals (REACH). Official Journal of the European Union
847	L396/1. European Union, Brussels
848	European Union (2002). Risk assessment report on acrylamide. CAS N°: 79-06-1 (http://europa.eu.int)
849	Fitzpatrick CSB, Fradin E, Gregory J (2004) Temperature effects on flocculation, using different
850	coagulants. Water Science and Technology 50:171-175
851	Giroto JA; Teixeira AC, Nascimento CA et al. (2008) Photo-Fenton removal of water-soluble polymers.
852	Chemical Engineering and Processing. 47 2361-2369
853	Goodrich MS, Dulak LH, Friedman MA, Lech JJ (1991) Acute and long-term toxicity of water-soluble
854	cationic polymers to rainbow-trout (oncorhynchus-mykiss) and the modification of toxicity by
855	humic-acid. Environmental Toxicology and Chemistry 10:509-515
856	Graveling GJ, Ragnarsdottir KV, Allen GC, Eastman J, Brady PV, Balsley SD, Skuse DR (1997)
857	Controls on polyacrylamide adsorption to quartz, kaolinite, and feldspar. Geochimica Et
858	Cosmochimica Acta 61:3515-3523
859	Greenlan DJ (1963) Adsorption of polyvinyl alcohols by montmorillonite. Journal of colloid science
860	18:647-664
861	Guezennec AG, Michel C, Desroche N, Togola A, Touzé S (Submitted 2014) Microbial aerobic and
862	anaerobic degradation of acrylamide in sludges and industrial and natural waters - sand and
863	gravel quarry case study. Environmental Science and Pollution Research (SI AQUAPOL)

864	Hamilton M, Reinert K, Freeman MB (1994) Aquatic risk assessment of polymers. Environmental
865	Science and Technology 28:187A-192A
866	Hanson AT, Cleasby JL (1990) The effect of temperature on turbulent flocculation - fluid-dynamics
867	and chemistry. Journal American Water Works Association 82:56-73
868	Harford AJ, Hogan AC, Jones DR, van Dam RA (2011) Ecotoxicological assessment of a
869	polyelectrolyte flocculant. Water Research 45: 6393-6402
870	Haschke H, Miles MJ, Sheppard S (2002) Adsorption of individual polyacrylamide molecules studied
871	by atomic force microscopy. Single Molecules 3:171-172
872	Haveroen ME, MacKinnon MD, Fedorak PM (2005) Polyacrylamide added as a nitrogen source
873	stimulates methanogenesis in consortia from various wastewaters. Water Res 39:3333-41
874	Heath AR, Bahri PA, Fawell PD, Farrow JB (2006) Polymer flocculation of calcite: Experimental results
875	from turbulent pipe flow. AIChE Journal 52:1284-1293
876	Hollander AF, Somasundaran P, Gryte CC (1981) Adsorption characteristics of polyacrylamide co-
877	polymers on sodium kaolinite. Journal of Applied Polymer Science 26:2123-2138
878	Holliman PJ, Clark JA, Williamson JC, Jones DL (2005) Model and field studies of the degradation of
879	cross-linked polyacrylamide gels used during the revegetation of slate waste. Science of the
880	Total Environment 336:13-24
881	Inyang HI, Bae S (2005) Polyacrylamide sorption opportunity on interlayer and external pore surfaces
882	of contaminant barrier clays. Chemosphere 58:19-31
883	Jin RR, Hu WB, Hou XJ (1987) Mechanism of selective flocculation of hematite from quartz with
884	hydrolyzed polyacrylamide. Colloids and Surfaces 26:317-331
885	Junqua G, Spinelli S, Gonzalez C, (2013) Occurrence and fate of acrylamide in water-recycling
886	systems and sludge in aggregate industries Environmental Science and Pollution Research in
887	press doi:10.1007/s11356-014-3022-5
888	Kay-Shoemake JL, Watwood ME, Lentz RD, Sojka RE (1998a) Polyacrylamide as an organic nitrogen
889	source for soil microorganisms with potential effects on inorganic soil nitrogen in agricultural
890	soil. Soil Biology and Biochemistry 30:1045-1052
891	Kay-Shoemake JL, Watwood ME, Sojka RE, Lentz RD (1998b) Polyacrylamide as a substrate for
892	microbial amidase in culture and soil. Soil Biology and Biochemistry 30:1647-1654

893	Kurenkov VF, Hartan HG, Lobanov FI (2002) Degradation of polyacrylamide and its derivatives in
894	aqueous solutions. Russian Journal of Applied Chemistry. 75:1039-1050
895	Labahn SK, Fisher JC, Robleto EA, Young MH, Moser DP (2010) Microbially Mediated Aerobic and
896	Anaerobic Degradation of Acrylamide in a Western United States Irrigation Canal. Journal of
897	Environmental Quality 39:1563-1569
898	Laird DA (1997) Bonding between polyacrylamide and clay mineral surfaces. Soil Science 162:826-
899	832
900	LaMer VK, Healvy TW (1963) Adsorption-flocculation reactions of macromolecules at the solid-liquid
901	interface. Review of Pure and Applied Chemistry 13:112-132
902	Lande SS, Bosch SJ, Howard PH (1979) Degradation and leaching of acrylamide in soil. J. Environ.
903	Qual. 8:133-137
904	Lavrov KV, Zalunin IA, Kotlova EK, Yanenko AS (2010) A new acylamidase from Rhodococcus
905	erythropolis TA37 can hydrolyze N-substituted amides. Biochemistry (Mosc) 75:1006-1013
906	Lecourtier J, Lee LT, Chauveteau G (1990) Adsorption of polyacrylamide on siliceous minerals.
907	Colloids and Surfaces 47:219-231
908	Lee JJ, Fuller GG (1985) Adsorption and desorption of flexible polymer-chains in flowing systems.
909	Journal of Colloid and Interface Science 103:569-577
910	Lee LT, Somasundaran P (1991) Effect of inorganic and organic additives on the adsorption of
911	nonioninc polyacrylamide on hematite. Journal of Colloid and Interface Science 142:470-479
912	Lentz RD, Sojka RE (2000) Applying polymers to irrigation water: Evaluating strategies for furrow
913	erosion control. Transactions of the Asae 43:1561-1568
914	Lentz RD, Sojka RE, Mackey BE (2002) Fate and efficacy of polyacrylamide applied in furrow
915	irrigation: Full-advance and continuous treatments. Journal of Environmental Quality 31:661-
916	670
917	Leong YK, Creasy DE, Boger DV, Nguyen QD (1987) Rheology of brown coal-water suspensions.
918	Rheologica Acta 26:291-300
919	Liber K, Weber L, Levesque C (2005) Sublethal toxicity of two wastewater treatment polymers to lake
920	trout fry (Salvelinus namaycush). Chemosphere 61:1123-1133
921	Liu L, Wang Z, Lin K, Cai W (2012) Microbial degradation of polyacrylamide by aerobic granules.
922	Environ Technol 33:1049-54

923	Liu ZH, Cao YM, Zhou QW, Guo K, Ge F, Hou JY, Hu SY, Yuan S, Dai YJ (2013) Acrylamide
924	biodegradation ability and plant growth-promoting properties of Variovorax boronicumulans
925	CGMCC 4969. Biodegradation In Press
926	Lu JH, Wu L, Letey J (2002) Effects of soil and water properties on anionic polyacrylamide sorption.
927	Soil Science Society of America Journal 66:578-584
928	Lu JH, Wu LS (2013) Polyacrylamide distribution in columns of organic Matter-Removed Soils
929	following Surface Application. J. Environ. Qual. 32:674-680
930	Lurie M, Rebhun M (1997) Effect of properties of polyelectrolytes on their interaction with particulates
931	and soluble organics. Water Science and Technology 36:93-101
932	Lyklema J, Fleer GJ (1987) Electrical contributions to the effect of macromolecules on colloid stability.
933	Colloids and Surfaces 25:357-368
934	Ma Y, Yu H, Pan W, Liu C, Zhang S, Shen Z (2010) Identification of nitrile hydratase-producing
935	Rhodococcus ruber TH and characterization of an amiE-negative mutant. Bioresour. Technol.
936	101:285-291
937	McCollister DD, Oven F & Rowe VK (1964) Toxicology of acrylamide. Toxicol. Appl. Pharmacol.
938	6:172–181
939	Makhongela HS, Glowacka AE, Agarkar VB, Sewell BT, Weber B, Cameron RA, Cowan DA, Burton
940	SG (2007) A novel thermostable nitrilase superfamily amidase from Geobacillus pallidus
941	showing acyl transfer activity. Appl. Microbiol. Biotechnol. 75:801-811
942	Malik M, Letey J (1991) Adsorption of polyacrylamide and polysaccharide polymers on soil materials.
943	Soil Science Society of America Journal 55:380-383
944	Malik M, Nadler A, Letey J (1991) Mobility of polyacrylamide and polysaccharide polymer through soil
945	materials. Soil technology 4:255-263
946	Matsuoka H, Ishimura F, Takeda T, Hikuma M (2002) Isolation of polyacrylamide-degrading
947	microorganisms from soil. Biotechnology and Bioprocess Engineering 7:327-330
948	Michaels AS, Morelos O (1955) Polyelectrolyte adsorption by kaolinite. Industrial and Engineering
949	Chemistry 47, 1081-1809
950	Molak, V. Acrylamide: A Review of the Literature in NIOH and NIOSH Basis for an Occupational
951	Health Standard. US Department of Health and Human Services, 1991.
952	Mortland (1970) Clay-organic complexes and interactions. Advances in Agronomy 22:75-117

953	Mpofu P, Addai-Mensah J, Ralston J (2004) Temperature influence of nonionic polyethylene oxide and
954	anionic polyacrylamide on flocculation and dewatering behavior of kaolinite dispersions.
955	Journal of Colloid and Interface Science 27: 145-156
956	Nabzar L, Pefferkorn E, Varoqui R (1984) Polyacrylamide sodium kaolinite interactions – flocculation
957	behavior of polymer clay suspensions. Journal of Colloid and Interface Science 102:380-388
958	Nabzar L, Pefferkorn E, Varoqui R (1988) Stability of polymer clay suspensions – the polyacrylamide
959	sodium kaolinite system. Colloids and Surfaces 30:345-353
960	Nadler A, Letey J (1989) Adsorption-isotherms of polynions on soils using tritium labeled compounds.
961	Soil Science Society of America Journal 53:1375-1378
962	Nadler A, Malik M, Letey J (1992) Desorption of polyacrylamide and polysaccharide polymers from
963	soil materials. Soil Technology 5:91-95
964	Nagashiro W, Tsunoda T, Tanaka M, Oikawa M (1975) Degradation of polyacrylamide molecules in
965	aqueous-solutions by high-speed strirring. Bulletin of the Chemical Society of Japan 48:2597-
966	2598
967	Nakamiya K, Kinoshita S (1995) Isolation of polyacrylamide-degrading bacteria. Journal of
968	Fermentation and Bioengineering 80:418-420
969	Nawaz MS, Franklin W, Cerniglia CE (1993) Degradation of acrylamide by immobilized cells of a
970	Pseudomonas sp. and Xanthomonas maltophilia. Can. J. Microbiol. 39:207-212
971	Nawaz MS, Khan AA, Seng JE, Leakey JE, Siitonen PH, Cerniglia CE (1994) Purification and
972	characterization of an amidase from an acrylamide-degrading Rhodococcus sp. Appl Environ
973	Microbiol 60:3343-8
974	Nawaz MS, Khan AA, Bhattacharayya D, Siitonen PH, Cerniglia CE (1996) Physical, biochemical, and
975	immunological characterization of a thermostable amidase from Klebsiella pneumoniae NCTR
976	1. J. Bacteriol. 178:2397-2401
977	Nawaz MS, Billedeau SM, Cerniglia CE (199): Influence of selected physical parameters on the
978	biodegradation of acrylamide by immobilized cells of Rhodococcus sp. Biodegradation 9:381-
979	387
980	Nguyen QD, Boger DV (1985) Thixotropic behaviour of concentrated bauxite residue suspensions
981	Rheol Acta 24:427-437

982	Nguyen QD, Boger DV (1998) Application of rheology to solving tailings disposal problems.
983	International Journal of Mineral Processing 54:217-233
984	Ohtaki A, Murata K, Sato Y, Noguchi K, Miyatake H, Dohmae N, Yamada K, Yohda M, Odaka M
985	(2010) Structure and characterization of amidase from Rhodococcus sp. N-771: Insight into
986	the molecular mechanism of substrate recognition. Biochim. Biophys. Acta 1804:184-192
987	Parfitt RL, Greenland JD (1970) Adsorption of polysaccharides by montmorillonite. Soil Science
988	Socienty of America Journal 34:562-866
989	Paterson RW, Abernathy FH (1970) Turbulent flow drag reduction and degradation with dilute polymer
990	solutions. J. Fluid. Mech 43:689-710
991	Pefferkorn E, Nabzar L, Varoqui R (1987) Polyacrylamide Na-kaolinite interactions - effect of
992	electrolyte concentration on polymer adsorption. Colloid and Polymer Science 265:889-896
993	Pereira AS, Soares EJ (2012) Polymer degradation of dilute solutions in turbulent drag reducing flows
994	in a cylindrical double gap rheometer device. J. Non Newtonian Fluid Mech. 179-180:9-22
995	Potts JR, Clarke PH (1976) The effect of nitrogen limitation on catabolite repression of amidase,
996	histidase and urocanase in Pseudomonas aeruginosa. J Gen Microbiol 93:377-87
997	Povkh LI, Chernyuk VV (1986) An experimental investigation of the effect of a polyacrylamide additive
998	on the pressure drop in an expansion Journal of engineering physics 51:1001-1004
999	Pradip YAA, Fuerstenau DW (1980) The adsorption of polyacrylamide flocculants on apaties. Colloid
1000	and Polymer Science 258:1343-1353
1001	Rabek JF (1996) In Photodegradation of Polymers: Physical Characteristics and Applications.
1002	Springer-Verlag. Berlin
1003	Rasteiro MG, Garcia FAP, Ferreira P, Blanco A, Negro C, Antunes E (2008) Evaluation of flocs
1004	resistance and reflocculation capacity using the LDS technique. Powder Technology 183:231-
1005	238
1006	Ren G-m, Sun D-z, Chung Jong S (2006) Kinetics study on photochemical oxidation of polyacrylamide
1007	by ozone combined with hydrogen peroxide and ultraviolet radiation. Journal of Environmental
1008	Sciences-China 18:660-664
1009	Rho T, Park J, Kim C, Yoon HK, Suh HS (1996) Degradation of polyacrylamide in dilute solution.
1010	Polymer Degradation and Stability 51:287-293

1011	Ruehrwein RA, Ward DW (1952) Mechanism of clay aggregation by polyelectrolytes. Soil Science
1012	73:485-492
1013	Santoshkumar M, Nayak AS, Anjaneya O, Karegoudar TB (2010) A plate method for screening of
1014	bacteria capable of degrading aliphatic nitriles. J. Ind. Microbiol. Biotechnol. 37:111-115
1015	Sathesh Prabu C, Thatheyus AJ (2007) Biodegradation of acrylamide employing free and immobilized
1016	cells of Pseudomonas aeruginosa. International Biodeterioration & Biodegradation 60:69-73
1017	Sato T, Ruch R (1980) Stabilization of colloidal dispersions by polymer adsorption. In: Dekker (Editor),
1018	Surfactant science serie. Marcel Dekker Inc., New York
1019	Scott JP, Fawell PD, Ralph DE, Farrow JB (1996) The shear degradation of high-molecular-weight
1020	flocculant solutions. Journal of Applied Polymer Science 62:2097-2016
1021	Senden TJ, Di Meglio JM, Silberzan I (2000) The conformation of adsorbed polyacrylamide and
1022	derived polymers. Comptes Rendus De L Academie Des Sciences Serie Iv Physique
1023	Astrophysique 1 :1143-1152
1024	Seybold CA (1994) Polyacrylamide review: Soil conditioning and environmental fate. Communications
1025	in Soil Science and Plant Analysis 25:2171-2185
1026	Shanker R, Ramakrishna C, Seth PK (1990) Microbial degradation of acrylamide monomer. Arch.
1027	Microbiol. 154:192-198
1028	Sharma M, Sharma N, Bhalla T (2009) Amidases: versatile enzymes in nature. Reviews in
1029	Environmental Science and Biotechnology 8:343-366
1030	Shukor MY; Gusmanizar N; Azmi NA et al. (2009a) Isolation and characterization of an acrylamide-
1031	degrading Bacillus cereus. Journal of environmental biology. 30(1)57-64
1032	Shukor MY, Gusmanizar N, Ramli J, Shamaan NA, MacCormack WP, Syed MA (2009b) Isolation and
1033	characterization of an acrylamide-degrading Antarctic bacterium. J. Environ. Biol. 30:107-112
1034	Smith, EA and Oehme FW (1993) Rapid direct analysis of acrylamide residue in polyacrylamide
1035	thickening agents by HPLC. Journal of Chromatographic Science 31:192-195.
1036	Smith EA, Prues SL, Oehme FW (1996) Environmental degradation of polyacrylamides .1. Effects of
1037	artificial environmental conditions: Temperature, light, and pH. Ecotoxicology and
1038	Environmental Safety 35:121-135
1039	Smith EA, Prues SL, Oehme FW (1997) Environmental degradation of polyacrylamides .2. Effects of
1040	environmental (outdoor) exposure. Ecotoxicology and Environmental Safety 37:76-91

1041	Sojka RE, Entry JA (2000) Influence of polyacrylamide application to soil on movement of
1042	microorganisms in runoff water. Environ Pollut 108:405-12
1043	Sojka RE, Bjorneberg DL, Entry JA, Lentz RD, Orts WJ (2007) Polyacrylamide in Agriculture and
1044	Environmental Land Management. Advances in Agronomy 92:75-162
1045	Spicer PT, Pratsinis SE, Raper J, Amal R, Bushell G, Meesters G (1998) Effect of shear schedule on
1046	particle size, density, and structure during flocculation in stirred tanks. Powder Technology
1047	97:26-34
1048	Spofford TL, Pfeiffer KL (1996) Agricultural irrigation polyacrylamide application standard, Managing
1049	Irrigation-Induced Erosion and Inflitration with Polyacrylamide, College of Southern Idaho,
1050	Twin Falls, Id USA
1051	Stephens SH (1991) Final report on the safety of polyacrylamide. Journal of the American college of
1052	toxicology 10:193-202
1053	Stutzmann T, Siffert B (1977) Contribution to adsorption mechanism of acetamide and polyacrylamide
1054	on to clays. Clays and Clay Minerals 25:392-406
1055	Suzuki K, Sugiyama A, Nakazato K (1978) Study of acrylamide-gel chromatography 3 spherical gels of
1056	polyacrylamide imdized by heat-treatment. Nippon Kagaku Kaishi, 1385-1389
1057	Suzuki K, Nakazato K, Takasaki T (1979) Study of acrylamide-gel chromatography 4 spherical gels of
1058	polyacrylamide co-polymerized with acrylonitrile. Nippon Kagaku Kaishi, 1327-1331
1059	Syed MA, Ahmad SA, Kusnin N, Shukor MY (2012) Purification and characterization of amidase from
1060	acrylamide-degrading bacterium Burkholderia sp. strain DR.Y27. African Journal of
1061	Biotechnology 11:329-336
1062	Tanaka H, Odberg L, Wagberg L, Lindstrom T (1990) Adsorption of cationic polyacrylamide onto
1063	monodisperses polystyrene lattices and cellulose fiber - effect of molecular-weight and
1064	charge-density of cationic polyacrylamides. Journal of Colloid and Interface Science 13: 219-
1065	228
1066	Tang S, Ma Y, Shiu C (2001) Modeling the mechanical strength of fractal aggregates. Colloids Surf.
1067	Physicochem. Eng. Aspects 180:7-16
1068	Taylor ML, Morris GE, Self PG, Smart RS (2002) Kinetics of adsorption of high molecular weight
1069	anionic polyacrylamide onto kaolinite: The flocculation process. Journal of Colloid and
1070	Interface Science 250: 28-36

1071	Tekin N, Demirbas O, Alkan M (2005) Adsorption of cationic polyacrylamide onto kaolinite.
1072	Microporous and Mesoporous Materials 85:340-350
1073	Tekin N, Dincer A, Demirbas O, Alkan M (2006) Adsorption of cationic polyacrylamide onto sepiolite.
1074	Journal of Hazardous Materials 134:211-219
1075	Tekin N, Dincer A, Demirbas O, Alkan M (2010) Adsorption of cationic polyacrylamide (C-PAM) on
1076	expanded perlite. Applied Clay Science 50:125-129
1077	Thanyacharoen U, Tani A, Charoenpanich J (2012) Isolation and characterization of Kluyvera
1078	georgiana strain with the potential for acrylamide biodegradation. J Environ Sci Health A Tox
1079	Hazard Subst Environ Eng 47:1491-9
1080	Theng BKG (1979) Formation and properties of clay-polymer complexes. Developement in Soil
1081	Sciences 9:9-11
1082	Theng BKG (1982) Clay-polymer interactions - summary and perspectives. Clays and Clay Minerals
1083	30:1-10
1084	Togola A, Coureau C, Guezennec AG, Touzé S (Submitted 2014). A sensitive analytical procedure for
1085	acrylamide in environmental water samples by offline SPE-UPLC/MS/MS. Environ Sci Pollut
1086	Res (SI AQUAPOL)
1087	Touzé S, Guerin V, Guezennec AG, Binet S, Togola A (2014). Dissemination of acrylamide monomer
1088	from polyacrylamide based flocculant use - sand and gravel quarry case study. Environ Sci
1089	Pollut Res (SI AQUAPOL)
1090	UNPG (2013) Polyacrylamide based flocculant used in quarries (in French). Union National des
1091	Producteurs de Granulats UNPG
1092	Van de Ven TGM (1994) Kinetic aspects of polymer and polelectrolyte adsorption on surfaces.
1093	Advances in Colloid and Interface Science 48:121-140
1094	Ver Vers LM (1999) Determination of acrylamide monomer in polyacrylamide degradation studies by
1095	high-performance liquid chromatography. Journal of Chromatographic Science 37:486-494
1096	Vlachogiannis M, Liberatore MW, McHugh AJ, Hanratty TJ (2003) Effectiveness of a drag reducing
1097	polymer: Relation to molecular weight distribution and structuring. Physics of Fluids 15:3786-
1098	3794
1099	Wade JHT, Kumar P (1972) Electronic microscope studies of polymer degradation. J. Hydronaut. 6-40

1100	Wakaizumi M, Yamamoto H, Fujimoto N, Ozeki K (2009) Acrylamide degradation by filamentous fungi
1101	used in food and beverage industries. J. Biosci. Bioeng. 108:391-3
1102	Wampler DA, Ensign SA (2005) Photoheterotrophic metabolism of acrylamide by a newly isolated
1103	strain of Rhodopseudomonas palustris. Appl. Environ. Microbiol. 7: 5850-5857
1104	Weideborg M, Kallqvist T, Odegard KE, Sverdrup LE, Vik EA (2001) Environmental risk assessment of
1105	acrylamide and methylolacrylamide from a grouting agent used in the tunnel construction of
1106	Romeriksporten, Norway. Water Research 35:2645-2652
1107	Wen Q, Chen Z, Zhao Y, Zhang H, Feng Y (2010) Biodegradation of polyacrylamide by bacteria
1108	isolated from activated sludge and oil-contaminated soil. J. Hazard. Mater. 175:955-959
1109	Wilson S, Drew R (1991) Cloning and DNA sequence of amiC, a new gene regulating expression of
1110	the Pseudomonas aeruginosa aliphatic amidase, and purification of the amiC product. J
1111	Bacteriol 173:4914-21
1112	Wilson SA, Wachira SJ, Drew RE, Jones D, Pearl LH (1993) Antitermination of amidase expression in
1113	Pseudomonas aeruginosa is controlled by a novel cytoplasmic amide-binding protein. Embo J
1114	12:3637-42
1115	Wilson SA, Drew RE (1995) Transcriptional analysis of the amidase operon from Pseudomonas
1116	aeruginosa. J Bacteriol 177:3052-7
1117	World Health Organization (1985) Environmental Health Criteria 1985, 49, 1. International programme
1118	on chemical safety Web. http://www.inchem.org/documents/ehc/ehc/ehc49.htm
1119	Woodrow JE, Seiber JN, Miller GC (2008) Acrylamide release resulting from sunlight irradiation of
1120	aqueous polyacrylamide/iron mixtures. Journal of Agricultural and Food Chemistry 56:2773-
1121	2779
1122	Yamada H, Asano Y, Hino T, Tani Y (1979) Microbial utilization of acrylonitrile. Journal of fermentation
1123	technology 5: 8-14
1124	Yeung A, Gibbs A, Pelton R (1997) Effect of shear on the strength of polymer-induced flocs. Journal of
1125	Colloid and Interface Science 196:113-115
1126	Yeung AKC, Pelton R (1996) Micromechanics: A new approach to studying the strength and breakup
1127	of flocs. Journal of Colloid and Interface Science 184:579-585

1128	Young MH, Tappen JJ, Miller GC, Carroll S., Susfalk R.B. (2007). Risk Characterization: Using Linear					
1129	Anionic Polyacrylamide to Reduce Water Seepage from Unlined Water Delivery Canal					
1130	Systems. Publication no. 41226. Desert Research Institute, Las Vegas, NV.					
1131						

$$CH_2 = CH - C - NH_2 \qquad CH_2 = CH - C - OH \\ n \qquad || \qquad + m \qquad || \qquad + NaOH \rightarrow \left[ \begin{array}{c} CH_2 - CH \\ | \\ C = O \\ | \\ NH_2 \end{array} \right]_n - \left[ \begin{array}{c} CH_2 - CH \\ | \\ C = O \\ | \\ ONa \end{array} \right]_m$$

#### Fig. 1 Synthesis pathway of anionic PAMs




Fig. 2 Conformation of a polymer adsorbed onto the surface of a mineral particle




Fig. 3 Metabolic pathway of AMD degradation in Enterobacter aerogenes proposed by Charoenpanich and Tani (2014).

## 1141 Table 1 Aerobic biodegradation of acrylamide in various environmental samples

References	Acrylamide	Temperature	Lag time	Time for complete AMD	
	concentration			degradation	
Labahn <i>et al.</i> (2010)	50 μg.L <sup>-1</sup>	15°C	No degradation observed after 72 h		
		25°C	0-12h	24 h	
Croll (1973)	10 μg.L <sup>-1</sup>	Non indicated	5h-50h	50h-300h	
Brown (1979)	5 mg.L <sup>-1</sup>	20°C	75h	125 h	
Vers (1999)	1,5-2,5 mg.L <sup>-1</sup>	Non indicated	0h	from 480 h to more than	
				1100 h	

1142

1143

# Table 2 Molecular weight, pH and temperature optima of amidases purified from AMDdegrading bacteria.

Bacterial strains	Molecular	Optimum	Optimum	Reference
	weight (kDa)	рН	temperature	
Geobacillus thermoglucosidasius AUT-01	38.0	6.2	70°C	Cha and Chambliss, 2013
Geobacillus pallidus BTP-5x MTCC 9225	38.5	8.0	60°C	Sharma et al. 2012
Ralstonia eutropha AUM-01	38.0	6.3	55°C	Cha and Chambiss, 2011
Variovorax boronicumulans CGMCC 4969	42.0	ND*	ND*	Liu <i>et al.</i> 2013
Burkholderia sp. DR.Y27	47.0	8.0	40°C	Syed <i>et al.</i> 2012
Rhodococcus sp.	44.5	8.5	40°C	Nawaz et al. 1994
Rhodococcus sp. N-771	54.7	5.9	55°C	Ohtaki et al. 2010
Klebsiella pneumoniae NCTR 1	62.0	7.0	65°C	Nawaz et al. 1996
Geobacillus pallidus RAPc8	38.0	7.0	50°C	Makhongela <i>et al.</i> 2007
Pseudonocardia thermophila DSMZ 43832	52.0	7.0	70°C	Egorova et al. 2004
Rhodococcus erythropolis TA37	55.0	8.0	55°C	Lavrov et al. 2010
Rhodococcus erythropolis TA37	55.0	8.0	55°C	Lavrov et al. 2010

1146 \* ND: Not Determined

1147