



**HAL**  
open science

## Calculation of groundwater response times in eleven Brittany catchments

Bruno Mougin, Jean-Michel Baltassat, Raymonde Blanchin, Francis Mathieu,  
Eric Putot, Jean-Michel Schroetter, Eric Thomas, Robert Wyns

► **To cite this version:**

Bruno Mougin, Jean-Michel Baltassat, Raymonde Blanchin, Francis Mathieu, Eric Putot, et al.. Calculation of groundwater response times in eleven Brittany catchments. G-DAT 2012 - Groundwater dating meeting - Rennes - France 15-19 October 2012, Oct 2012, Rennes, France. hal-01180216

**HAL Id: hal-01180216**

**<https://brgm.hal.science/hal-01180216>**

Submitted on 24 Jul 2015

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## **Calculation of groundwater response times in eleven Brittany catchments.**

B. Mougín<sup>1</sup>✉, J-M. Baltassat<sup>2</sup>, R. Blanchin<sup>3</sup>, F. Mathieu<sup>2</sup>, E. Putot<sup>4</sup>, J-M. Schroetter<sup>1</sup>, E. Thomas<sup>1</sup> and R. Wyns<sup>5</sup>

(1) Direction of the Territorial Actions, BRGM Bretagne, 2 rue de Jouanet, 35700 Rennes, France.

✉Corresponding author : [b.mougin@brgm.fr](mailto:b.mougin@brgm.fr)

(2) Direction Risks and Prevention. Risk cavities, arrangement of the basement and the imaging. BRGM, 3 avenue Claude Guillemin, BP 36009, 45060 Orléans, France.

(3) Direction of Géoressources. Knowledge and exploration of the mineral site. BRGM, 3 avenue Claude Guillemin, BP 36009, 45060 Orléans, France.

(4) Direction Water, Environment and Ecotechnologies. Evaluation and valuation of the knowledge on the water. BRGM, 3 avenue Claude Guillemin, BP 36009, 45060 Orléans, France.

(5) Direction of Géoressources. Geology of the town and country planning. BRGM, 3 avenue Claude Guillemin, BP 36009, 45060 Orléans, France.

### **Abstract**

« SILURES Bretagne » is a scientific program (Information system for the Localization and the Use of groundwater resources), which aims to realize decision-making tools for a policy of management of the water (better consideration of groundwater, definition of priorities in the actions of restoration quality of Breton superficial waters). One of the stages of this project consisted in modelling the hydrograms of rivers to know the contribution that groundwater makes to the flows of Breton rivers and estimate the slowness of groundwater physical environment. By basing on the conceptual diagram of hard-rocks aquifer platforms (R. Wyns and al. 2004, B. Dewandel and al. 2006), 70 global modellings rains/river flow were realized in the step of daily time with the software BRGM Gardenia<sup>®</sup>.

On 11 of 70 catchments studied (Elorn, Aulne, Yar, Horn, Coët-Dan, Dourduff, Maudouve, Noë sèche, Oust, Yvel and Nançon), the volumes of groundwater in the first 50 metres of basement were calculated. By modelling the thickness of the aquifer layers (regolith and fissured horizon) in the rocks that form the bed of a catchment, and the content of free water in rocks measure with Protonic Magnetic Resonance system, the volume of groundwater present in the zone can be estimated (R. Wyns and al. 2004).

Knowing the amount of groundwater flow exiting a river catchment, as well as the average speed a water droplet takes to reach the water table from the ground, (according to the bibliography, this speed varies between 1.75 and 2.5 m/yr.), response times of groundwater can be estimated (the time taken for a drop of water to seep from the ground to the water table and then from the water table to the river). These times are very varied (between 2 and 8 years), depends very much on the geology of the catchment and also on the amount of rainfall they have each experienced.

These times do not correspond to the amount of time taken for water quality to be recovered. This is for a mixture of reasons based around the ground, the water table, the regolith and the fissured horizon. However, these are minimum times and it is imperative to obtain tangible results on the quality of the water tables and consequently the water system, which can then be followed by action on the surface.

### **References**

DEWANDEL, B., P. LACHASSAGNE, R. WYNS, J.C. MARÉCHAL, and N.S. KRISHNAMURTHY. 2006. A generalized 3-D geological and hydrogeological conceptual model of granite aquifers controlled by single or multiphase weathering. *Journal of Hydrology*, no. 330: 260-284.

R. WYNS, J-M. BALTASSAT, P. LACHASSAGNE, A. LEGCHENKO, J. VAIRON and F. MATHIEU (2004). Application of proton magnetic resonance soundings for groundwater reserve mapping in weathered basement rocks (Brittany, France), *Bulletin de la Société Géologique de France*, t. 175, n°1, pp. 21-34.