



HAL
open science

Land use effect on nitrate storage and transport through unconfined Chalk aquifer

Géraldine Picot-Colbeaux, Dominique Thiéry, Nicolas Devau, Marine Josse, Nicolas Surdyk, Hubert Péru, Marie Pettenati, Marc Parmentier, Laurent André

► To cite this version:

Géraldine Picot-Colbeaux, Dominique Thiéry, Nicolas Devau, Marine Josse, Nicolas Surdyk, et al.. Land use effect on nitrate storage and transport through unconfined Chalk aquifer. AquaConSoil, Jun 2017, Lyon, France. hal-01425345

HAL Id: hal-01425345

<https://brgm.hal.science/hal-01425345v1>

Submitted on 3 Jan 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Land use effect on nitrate storage and transport through unconfined Chalk aquifer

Picot-Colbeaux Géraldine^{*}, Thiéry Dominique^{*}, Devau Nicolas^{*}, Marine Josse^{**}, Surdyk Nicolas^{*}, Hubert Péru^{***}, Pettenati Marie^{*}, Parmentier Marc^{*}, André Laurent^{*}.

^{*}BRGM, 3 Av Claude Guillemin, 45000 Orléans, France / Corresponding author: g.picot@brgm.fr

^{**} SIEP du Santerre, 1 rue d'Hassel, BP 20022, 80170 Rosière-en-Santerre, France

^{***} Agrosol, 230 Rue de Villers Châtel, 62690 Camblyneul, France

Chalk aquifer is the main water resource for domestic water supply in many parts in northern France. In this region, groundwater is frequently affected by quality problems concerning nitrates. Often close to or above the drinking water standards, nitrate content in groundwater is mainly due to historical agriculture practices, combined with aquifer recharge through the vadose zone. The complexity of processes occurring into such an environment leads to combine a lot of knowledge in agronomy, geochemistry and hydrogeology in order to understand, model and predict the spatiotemporal evolution of nitrate content and provide a decision support tool for the water producers and stakeholders. To succeed in this challenge, conceptual and numerical models representing accurately the Chalk aquifer specificity will be developed, including a multidisciplinary approach to simulate storage and transport from the ground surface to the underlying groundwater. This involves a new agronomic module "MONICA" (**MO**delling **NI**trates transfert taking into account **C**rops and **A**gricultural practices), a soil-crop model calculating the nitrogen mass balance in arable soil, integrated in the 3D transient groundwater numerical code "MARTHE". This approach integrating existing multi-disciplinary tools is a real challenge. It enables to decrease the number of calibration parameters by selecting the relevant equations and simplifying them without altering the signal. The numerical development is applied on a 2D vertical cross-section in the vadose zone representing experimental nitrate vertical measurements in soil profiles (0-22 m depth) in the Somme region (France). The experiment results highlight the land use management effect on nitrate evolution into the vadose zone (e.g. forest instead of crops). Simulations constrained by climate forcing, land use and nitrogen inputs over several decades reproduce the nitrate spatial and temporal distribution. This approach will be ultimately used to model in 3D the drinking water catchment area. It will be calibrated using nitrate contents time series of nitrate content measured in the domestic water pumping well available since 1995 (field in northern France – Avre Basin region). This numerical tool will help the decision-making in all activities in relation with water uses.