

Using IDPR to characterize recharge area of karst aquifers from catchment to regional scales

Yvan Caballero, Stephanie Pinson, Jean-Baptiste Charlier, Sandra Lanini

▶ To cite this version:

Yvan Caballero, Stephanie Pinson, Jean-Baptiste Charlier, Sandra Lanini. Using IDPR to characterize recharge area of karst aquifers from catchment to regional scales. Eurokarst 2018, Jul 2018, Besançon, France. hal-01757323

HAL Id: hal-01757323 https://brgm.hal.science/hal-01757323

Submitted on 3 Apr 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Using IDPR to characterize recharge area of karst aquifers from catchment to regional scales

Yvan Caballero¹, Stéphanie Pinson², Jean-Baptiste Charlier¹, Sandra Lanini¹

¹ BRGM, 1039 rue de Pinville, F-34000 Montpellier, France

The shape and the nature of hydrographic networks on karst environments are closely linked to the infiltration capacity of geological formations. Thus, the presence or absence of a river in a favorable topographic context can be interpreted in terms of karstic aquifers recharge potential. We present the GIS built index of infiltration and runoff properties of landscape (called IDPR) as an interesting tool for the characterization of the karst extension and for the further recharge estimation of such aquifers. A new version of the IDPR tool has been released over France in 2017 which spatial resolution (25 m) becomes very useful for the detection of contributive zones for karst aquifers recharge. Examples of the IDPR application at the river basin scale (Fontaine de Vaucluse) and at the regional scale (Rhone river basin) will be presented. Base flow estimation methods are used for the calibration of the IDPR index in terms of infiltration capacity, leading the IDPR index to be useful for recharge estimation.

² BRGM, 3 avenue Claude Guillemin BP 36009 45060 Orléans

^{*} corresponding author: e-mail: y.caballero@brgm.fr Tel: +33 (0)4 67 15 79 62