



# Contribution of Image correlation SEM-EDS-Raman to the study of geomaterials: a promising approach

Guillaume Wille

## ► To cite this version:

Guillaume Wille. Contribution of Image correlation SEM-EDS-Raman to the study of geomaterials: a promising approach. ECASIA 2019 - 18th European Conference on Applications on Surface and Interface Analysis, Institute of Solid State and Materials Research (IFW Dresden); Technical University Dresden (TUD), Sep 2019, Dresden, Germany. hal-02160922

HAL Id: hal-02160922

<https://brgm.hal.science/hal-02160922>

Submitted on 4 Oct 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# CONTRIBUTION OF IMAGE CORRELATION SEM-EDS-RAMAN TO THE STUDY OF GEOMATERIALS

## a promising approach

Dr Guillaume WILLE

BRGM - Water, Environment, Process Development and Analysis Division  
3 avenue Claude Guillemin – BP36009, 45060 ORLEANS Cedex 2  
[g.wille@brgm.fr](mailto:g.wille@brgm.fr)



## In collaboration with:

Dr Didier LAHONDRE<sup>1</sup>, Ms Jerome DURON<sup>1</sup>, Dr Catherine LEROUGE<sup>1</sup>, Dr Xavier Bourrat<sup>1</sup>, Dr Ute SCHMIDT<sup>2</sup>, Dr Jeremie SILVENT<sup>3</sup>

<sup>1</sup> BRGM, 3 avenue Claude Guillemin – BP36009, 45060 ORLEANS Cedex 2


<sup>2</sup> WITec GmbH, Ulm, Allemagne

<sup>3</sup> TESCAN France, Fuveau, France

*Actinolite-asbestos vein  
interspersed with ophiolytic  
metabasaltes (Corsica, France)  
D. Lahondere, BRGM*



- Introduction: Interest of multimodal analysis in geosciences
- Coupling SEM-EDS and Raman spectroscopy
  - Why ? How ?
- Coupling SEM-EDS and Raman spectroscopy
  - Examples
- Coupling SEM-EDS and Raman spectroscopy
  - A case study: application to the identification and characterization of the natural occurring asbestos (NOA)
- Conclusion



# Introduction: Interest of multimodal analysis in geosciences

SEM and all associated techniques is of great interest in the analysis and characterization of geomaterials


## MULTIMODAL APPROACH

A multimodal approach is the combined use – synchronously or asynchronously – of several analytical techniques, each of which can provide a part of a set of physical and chemical data


# Complementary analytical data

## Co-location of physical and chemical data

- Morphology
- chemistry
- Crystallography, atomic / molecular organization
- Etc...




EPMA imaging on an iron oxide grain  
a) Transmission optical microscopy  
b) Polarized light microscopy  
c) Backscattered electrons imaging  
d) Secondary electrons imaging  
e) WDS - Fe K $\alpha$  mapping



« Milky » pearls (vaterite defect) (SEM CL / BSE / SE on FIB slice)


## Co-located multi-scale data

- Multi-scale coupled data
- Microscopy:
  - Macroscopy (cm / mm)
  - Visible Light Microscopy ( $\mu\text{m}$ )
  - Scanning electron microscopy (nm)
  - Transmission electron microscopy ( $\text{\AA}$ )
- Analytical capacities
  - Various scales and spatial resolution
  - Various detection limits / sensitivity



# Coupling SEM-EDS and Raman spectroscopy

Why ? How ?




μ-Raman spectroscopy analysis of a fluid inclusion in a quartz grain  
After C. Beny et al., *Chemical Geology* 37 (1982) 113–127

# Scanning Electron Microscopy

## SEM

- Electron beam generated by an electron gun, accelerated and focused in an « electron column »
- Various imaging modes (matter / electron beam interactions):
  - Secondary electrons imaging (topography)
  - Backscattered electrons imaging (chemical contrast ± crystal orientation contrast)
  - Other imaging modes (cathodoluminescence, transmitted electron...)




Examples of SEM images:

Top: SE ( $\text{TiO}_2$  nanoparticles)

Middle: BSE (Granite)


Bottom: panchromatic CL (Cassiterite  $\text{SnO}_2$ )



EDS mapping of Iron and Lead in a lead ore  
(Pontgibaud mine, France)

## EDS

- Emission of characteristic X-ray
- Elemental analysis:
  - Qualitative (identification of elements)
  - Quantitative (Wt%)
  - Imaging (elements distribution)




EDS spectra of Pt / Rh alloy



# Micro-Raman spectroscopy

## Principle


- Vibrational spectroscopy based on the inelastic diffusion of monochromatic light (laser beam)
- Various structural information:
  - Crystal structure, degree of crystallinity
  - Presence de chemical groups (-OH, -CO<sub>3</sub>, etc ...)
  - Amorphous materials



Vibration modes of the water molecule H<sub>2</sub>O



Raman spectra of TiO<sub>2</sub> rutile (quadratique P)  
and anatase (quadratique C)



Raman spectrum of  
SiO<sub>2</sub> nanoparticles compared to the Raman spectrum  
of opal (hydrated amorphous form of silica)  
(RUFF database - <http://rruff.info/>)

# Coupling SEM-EDS and Raman

A case study, the mineral

## Composition


« textbook » composition

+

"deviations" dues to the presence of minor / trace elements

## In the SEM

## EDS, WDS



**Minéral**

- Pyrite ( $\text{FeS}_2$ )**
- a) Pyrite inclusions in Iron oxide - BSE\*
  - b) Centimetric pyrite (Elba, Italie)\*\*
  - c) Orientation map in a pyrite - EBSD\*

## Morphology, shape

Automorphs crystals,  
surface roughness...

## Cristallography

Crystal structure

+

Distortions (defects, dislocations...)

## In the SEM


## EBSD / TKD Raman

## In the SEM

## Imaging Modes (SE, BSE, CL...)

# Coupling SEM-EDS and Raman

## The origin



1986 - M. Delhaye & M. Truchet: Patent for an analytical microscope coupling electron microscopy and Raman microscopy

J. Microsc. Spectrosc. Electron., Vol. 13, 1988, 187-195

### COUPLAGE D'UNE SONDE RAMAN LASER ET D'UNE SONDE DE CASTAING DANS UN MICROSCOPE ELECTRONIQUE

Michel TRUCHET \* et Michel DELHAYE\*\*  
\* Laboratoire d'Histophysiology fondamentale et appliquée,  
U.R.A. 689, C.N.R.S., Université Pierre et Marie Curie,  
12, rue Cuvier, 75005 PARIS, France  
\*\* Laboratoire de Spectrochimie Infrarouge et Raman, I.F.C.N.R.S. 3431  
Université des Sciences et Techniques de Lille-Flandres-Artois,  
59655 VILLENEUVE D'ASCQ Cedex, France

accepté en février 1988

#### ABSTRACT

The photon microscope of the Raman microprobe limits the spatial resolution to the micrometer scale, and the wavelength width to the visible light. In this paper is described a new objective, made of an ellipsoidal step associated with a plane mirror, at the first focus. This design allows a numerical aperture of 0.99, a total aberration from U.V. to I.R. and makes possible molecular Raman analysis of samples into the column of an electron microscope and/or a Castaing's electron microprobe, for simultaneous elemental analysis at submicron scale.

1988 - M. Truchet & M. Delhaye : 1st publication





FIG. 4 : Schéma vertical très schématisé d'un colonne de microscope électronique à transmission équipé pour la spectroscopie des rayons X et dispenseur de longueur d'onde pour la montage de Castaing, et paroie semi-transparente de séparation des flux photoniques permettant l'analyse simultanée par spectroscopie Raman. Ce dispositif correspond au dispositif elliptoïdale tel que le Figure 1, monté à l'ascenseur, et associé à un objectif de Castaing. CE : canon à électrons. C1, C2 et C3 : condenseurs. M.E.T. : microscope à transmission (partie image). SX : spectromètre à rayons X. SR : spectromètre Raman. LST : lame semi-transparente.

# Micro-Raman spectroscopy

## SEM-Raman

- 2 types of SEM-Raman coupling : coaxial or parallel
- Coaxial setup
  - Resolution:  $\sim 2.5 \mu\text{m}$  @  $\lambda = 514 \text{ nm}$
  - Spectral analysis: loss of intensity (compared to conventional Raman spectroscope)
  - Imaging mode: possible but limited (time / pixel)
- Parallel setup
  - Resolution:  $< 400 \text{ nm}$  @  $\lambda = 532 \text{ nm}$
  - Spectral analysis: comparable with a conventional Raman spectroscope
  - Imaging: comparable with a conventional Raman spectroscope ( $250 \times 250 \mu\text{m}$ )





Co-axial setup  
Renishaw SEMSca / Tescan MIRA

Parallel setup  
WITec RISE / Tescan MIRA



11






SEM-Raman analysis of a composite Carbon / SiC (Tescan – WITec RISE)

\*Jiruse et al, 2014


# Coupling SEM-EDS and Raman


Example: polymorphs of calcium carbonates in a defective pearl



WDS profile (EPMA) on both sides of the interface



SEM - panchromatic CL and  $\mu$ -XRF maps





# Coupling SEM-EDS and Raman spectroscopy

## Examples



SEM-Raman on a transverse section of an actinolite fibers bundle

# Ex. 1 – Zonation in tin oxide cassiterite

SEM - Raman - EBSD - WDS

G. Wille, C. Lerouge (BRGM), U. Schmidt (WITec)

- Cassiterite  $\text{SnO}_2$  is the main tin ore (Sn)
- $\text{SnO}_2$  crystal structure similar to Rutile ( $\text{TiO}_2$ )
- Various possible trace elements: Ti, Fe, Ta, Nb, Zn, W, Mn, Sc, Ge, In, Ga...
- The knowledge of chemistry is required for:
  - Understanding of the geological context of the mineral resource
  - Feasibility of the tin production process
  - Waste recycling / treatment
- 2 possible substitution:
  - Homovalent:  $\text{Sn}^{4+} \leftrightarrow \text{Ti}^{4+}$
  - Heterovalent:  $2.(\text{Nb},\text{Ta})^{5+} + (\text{Fe},\text{Mn})^{2+} \leftrightarrow 3.\text{Sn}^{4+}$





Tin ore from the Montbelleux mine  
(Luitré, Ille-et-Vilaine - France)

C. Lerouge et al. European Journal of Mineralogy, 2018, 29(4), p. 739-753


# Ex. 1 – Zonation in tin oxide cassiterite

SEM - Raman - EBSD - WDS

- SEM - CL shows a strong contrast that may be associated with trace elements distribution and / or crystal orientation
- EPMA (WDS) analysis is applied for mapping and quantification of trace elements content – Some CL contrasts can be linked to EPMA data
- EBSD provide 2 informations on the crystallography of cassiterite grains
  - Millimetric monocrystalline grains
  - Elbow twin ( $\sim 70^\circ$ ) commonly encountered in rutile structure



15





SEM - CL

WDS maps (EPMA) and EBSD orientation map of the same area

# Ex. 1 – Zonation in tin oxide cassiterite


SEM - Raman - EBSD - WDS

- The correlation of the data obtained from the different techniques on the same area of the sample allow a fine analysis of the substitution of Sn by the other elements



EBSD

EPMA(WDS)



Raman mapping and Raman spectra extracted  
Comparison with EPMA data (structural formula)



# Ex. 2 – Industrial process for the obtention of white pigments

Industrial process for the production of high quality white pigments from natural silica stones (beach pebbles)

- White pigments obtained from high temperature heating of silica pebbles
- Improvement of the product quality by studying different parameters
  - Source of the raw materials
  - Composition of the final product: % main phase / secondary phases
- ⇒ Overall characterization (XRD, chemistry)
- ⇒ Micro-characterisation: morphology, chemistry, cristallography



Blue flint in a Limestone cliff  
(Normandy, France)







# Ex. 2 – Industrial process for the obtention of white pigments



Industrial process for the production of high quality white pigments from natural silica stones (beach pebbles)

- Final composition: cristobalite, présence de quartz  $\beta$ 
  - Distribution of the phases ? → EBSD doesn't work (poorly crystallized)
- SEM observation : evidence of a phase containing Ca and Si
  - Lamellar structure
  - Alternance of lamella and Silica
  - EPMA: composition  $\text{CaSiO}_3$  → Wollastonite not stable at the process temperature




⇒ identification and description by Raman imaging in the SEM



# Application – other examples




19







CVD deposition of graphene on siliconium

Image SEM (SE) + Raman IG' / IG  
Blue, red: NLG < 3  
green: NLG ≥ 3



# Coupling SEM-EDS and Raman spectroscopy

A case study: application to the identification and characterization of the natural occurring asbestos (NOA)



# Asbestos

## Asbestos

From the greek word *Asbestos* (incombustible)

This term refers to a group of 6 natural fibrous silicates (as well as any mixture of these fibers).

Known and used since the greek and roman antiquity, for their physical and chemical properties.


commercial definition → limited to the varieties exploited industrially

legal and regulatory definition → defined in each country or group of countries. Ex. in the european union 2009/148/EC on the protection of workers from the risk related to exposure to asbestos at work

*Breathable Fiber (WEO 1998) =  $L > 5 \mu\text{m}$  ;  $D < 3 \mu\text{m}$  ;  $L/D > 5$*


*Asbestiform fiber (EPA) =  $L/D > 20$ , fine fibers ( $< \mu\text{m}$ )*

Serpentines	
Chrysotile	$\text{Mg}_3\text{Si}_2\text{O}_5(\text{OH})_4$
Amphiboles	
Tremolite	$\text{Ca}_2\text{Mg}_5\text{Si}_8\text{O}_{22}(\text{OH})_2$
Actinolite	$\text{Ca}_2(\text{Mg},\text{Fe})_5\text{Si}_8\text{O}_{22}(\text{OH})_2$
Anthophyllite	$(\text{Mg},\text{Fe})_7\text{Si}_8\text{O}_{22}(\text{OH})_2$
Amosite	$(\text{Mg},\text{Fe})_7\text{Si}_8\text{O}_{22}(\text{OH})_2$
Crocidolite	$\text{NaFe}_5\text{Si}_8\text{O}_{22}(\text{OH})_2$




Chrysotile fibers in a vinyl floor tile  
(SEM – SE –low vacuum mode)

# Asbestos



Astros Toaster  
No. 3000 Crown Asbestos Toaster consists of an asbestos disc covered with steel wire mesh, the lower surface being overlaid with sheet steel. Has a corrugated steel rim and always cool. Alaska handle. For toasting bread, rusks or crackers on gas, gasoline or coal stove it is fine. Can also be used under cooking utensils to keep food from scorching or for any purpose for which the asbestos stove-mats are used. Diameter, 8½ inches. Weight, 10 ounces. Price, each..... 9c



# Naturally Occuring Asbestos


## The geologist point of view

The chemical composition of several rocks allows the crystallisation of serpentines or amphiboles able to crystallise in an asbestos form shape.

:


- Ultrabasic rocks: peridotite, serpentinized peridotites, serpentinite, (méta)-pyroxenite
- Basic metamorphized rocks: amphibolites, metabasalts, metagabbro, metadolerites, prasinites, spilites, etc...
- Some metamorphized carbonated rocks

Asbestiform minerals / fibers can also be found in soils and sediments resulting from the alteration and erosion of these rocks.




top: chrysotile  
bottom Tremolite-asbestos


# Naturally Occurring Asbestos in France



Main area  
(D. Lahondere, BRGM)



North of Corsica  
(D. Lahondere, BRGM)




Bastia and around  
(D. Lahondere, BRGM)

# Naturally Occuring Asbestos in France

## Main risks

- Natural erosion of rocks / soils releasing fibers
- (traditionnal) Use of local rocks for building construction, embankment...
- Civil engineering (road construction, tunnel drilling...)
- Materials quarried for civil engineering (railway ballast, aggregates etc...)



Murato church  
(D. Lahondere, BRGM)

## Analytical challenge

- Complex material, purely mineral and natural
- Presence of non-asbestos minerals with similar compositions
- Differentiation fiber / cleavage fragments

The usual standards and methods are often unsuited

Table 2. – Location and extent of pleural calcifications observed in Murato, according to the 1980 ILO International Classification

Extent	Location					
	Diaphragm		Chest wall		Pericardium/mediastinum	
	Right	Left	Right	Left	Right	Left
1	3	8	12	6	1	3
2	12	13	13	15	6	4
3	0	0	7	7	3	0
Total	15	21	32	28	10	7
%	47	66	100	88	31	22

ILO: International Labour Office.

Table 3. – Airborne asbestos pollution as assessed using transmission electron microscopy ( $\times 10^4 \text{ g m}^{-3}$ )


	Murato				Vezzani			
	I	H	M	L	I	H	M	L
Chrysotile	0.6	1	0.4	0.3	0.3	-	0.2	0.1
Tremolite	44	34	6	72	1	-	-	** p<0.05*

I: indoors; H, M, L: outdoors at different levels in the village (high, medium, low); \*\*: not significant. \*: Murato values versus Vezzani.

Health hazard of NOA  
the example of the north of Corsica  
F. Rey et al., Eur. Respir. J., (1993), 6, 978-982




# Naturally Occuring Asbestos



SEM (BSE)



# Naturally Occuring Asbestos



## EPMA analysis

- Large particles ( $> 3\mu\text{m}$ ) → ok
- Thin fibers ( $< 3\mu\text{m}$ ) → result not usable - contribution of the matrix in the result

⇒ **For thin fibers, another technique is requested for the identification**

	SiO <sub>2</sub>	TiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	Cr <sub>2</sub> O <sub>3</sub>	FeO	MnO	MgO	CaO	Na <sub>2</sub> O	K <sub>2</sub> O	Total
Xa	52.343	0.048	2.691	0.000	17.652	0.738	12.642	11.334	0.291	0.007	97.747
Xf	54.258	0.000	6.863	0.000	15.198	0.481	10.966	10.814	1.661	0.066	100.308
matrix	60.115	0.000	25.032	0.009	0.164	0.000	0.000	6.246	8.195	0.087	99.849



EPMA (WDS)

# Naturally Occuring Asbestos - In Situ characterization

SEM - Raman / SEM – FIB complementarity

G. Wille, D. Lahondere, J. Duron, X. Bourrat (BRGM), J. Silvent (Tescan), U. Schmidt (WITec)

- Amphibole fibers dispersed in a mineral matrix
- In-situ diagnosis with a limited sample preparation
  - Chushing: risk of cleavage fragments (non-fibrous amphiboles)
  - Amphibole identification
  - Asbestiform / non asbestiform morphology
- Distribution of fibers in the sample
  - 3D analysis







Thin section of a blue micro-diorite containing fibrous actinolite in a quartz matrix  
(Sainte Florence, France)

# Naturally Occuring Asbestos - In Situ characterization

## Raman in SEM: 2D / 3D analysis

- 2D: identification of actinolite fibers up to 400 nm in diameter + approximation of the Mg/Fe ratio (*Bersani et al, 2019*)
- 3D: Fibrous morphology and distribution of actinolite fibers in the analyzed volume





Raman 3D

120 μm x 120 μm x 20 μm

# Naturally Occuring Asbestos - In Situ characterization


Fibers < 400 nm → SEM-FIB 3D analysis

- 3D Fibrous morphology and distribution of actinolite fibers in the analyzed volume up to 100 nm (or better)



**High resolution in situ method**

**FIB 3D**  
563 slices / Voxel 60 µm  
Width: 785 px (47.10 µm)  
Height: 799 px (47.94 µm)  
Depth: 563 px (33.78 µm)








**Volume**  
 $76274 \mu\text{m}^3$


**Fibers**  
 $1464,40 \mu\text{m}^3$  soit 1.94 % du volume

# Naturally Occuring Asbestos - In Situ characterization

## Ferro-actinolite fibers bundle - SEM-FIB 3D

- Asbestiform morphology
- Numerous parallel fibers = bundle
- Defects (cracks)
- Location of TEM slice sampling in the SEM-FIB





# Coupling SEM-EDS and Raman spectroscopy

## Conclusion

A unique tool for a complete mineralogical characterization of the geological samples


The characterization of geo-materials usually requires various informations: Chemistry (major / trace elements), cristallography, morphology

⇒ *Need for multimodal / multitechniques approach*

**SEM + EDS + Raman**

Combination of data, collected at the same time, at the same place, at the same scale

⇒ *Multi-parameters, co-localized*



## *Application to NOA* *In-situ method for identification, determination of the asbestiform character, volume fraction of fibrous amphiboles*

# Coupling SEM-EDS and Raman spectroscopy

## Conclusion

### Confocal Raman imaging in the SEM

Coupling morphology (SEM), chemistry (EDS) and structure (Raman)

Raman in the SEM: 2D / 3D capacities

Non-destructive in-situ method

⇒ *Surface / volume information*

### SEM-Raman and FIB-SEM

FIB 3D: higher resolution but destructive

FIB for TEM: Raman 3D can help

⇒ *Complementarity*



**THANK YOU**  
**Questions ?**