



HAL
open science

Numerical simulation of dynamic rupture and ground motion on a fault non-uniformly loaded along dip

Hideo Aochi, Kenichi Tsuda

► **To cite this version:**

Hideo Aochi, Kenichi Tsuda. Numerical simulation of dynamic rupture and ground motion on a fault non-uniformly loaded along dip. European Geoscience Union, May 2022, Vienna, Austria. hal-03576651

HAL Id: hal-03576651

<https://brgm.hal.science/hal-03576651>

Submitted on 16 Feb 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

EGU22-1672

EGU General Assembly 2022

© Author(s) 2022. This work is distributed under the Creative Commons Attribution 4.0 License.



Numerical simulation of dynamic rupture and ground motion on a fault non-uniformly loaded along dip

Hideo Aochi^{1,2} and Kenichi Tsuda³

¹BRGM, Orleans, France (h.aochi@brgm.fr)

²Laboratoire de Géologie de l'Ecole Normale Supérieure, CNRS UMR 8538, PSL Research University, Paris, France

³Shimizu Corporation, Tokyo, Japan

It is widely accepted that the rupture area of earthquake is controlled by fault geometry and the interaction between segments. Besides, many earthquakes do not rupture the whole seismogenic depth but only some limited depth zone. It is not so often to observe that a moderate earthquake such as the 2019 Mw4.9 Le Teil, France, earthquake shows a clear surface rupture and the very shallow rupture area limited at the first 1-2 km depth. Aochi and Tsuda (EGU, 2021) propose the concept that the fault is not uniformly loaded along dip due to the 1D layered structure. Namely, the stress is loaded mainly on the stiff layers, while the soft layers play a role of barrier. We use a boundary element method and a spectral element method for simulating the dynamic rupture propagation and wave propagation. We then demonstrate that the shallowest soft layer can be slipped if the rupture at deeper portion is sufficiently developed. On the other hand, a depth soft layer is difficult to be ruptured, mainly because the absolute stress level is high. In our synthetic scenarios, we compare the ground motions around the fault. In the usual model where the stress is uniformly loaded on all the depths, we observe a strong coherent pulse as the rupture progresses fast to the ground surface. However, we observe more than one pulse in our setting. Such heterogeneous condition along dip should be important to investigate the causality of the seismic asperity and the influence on the resultant near-field ground motion.