



Mechanisms and kinetics of carbon steel corrosion/scaling and inhibition in actual or reconstituted and treated geothermal waters

Chahinez Helali, Stéphanie Betelu, Ioannis Ignatiadis

► To cite this version:

Chahinez Helali, Stéphanie Betelu, Ioannis Ignatiadis. Mechanisms and kinetics of carbon steel corrosion/scaling and inhibition in actual or reconstituted and treated geothermal waters. SPE Workshop: Bridging the Gap Between Geothermal and Oil & Gas 4. Geothermal fluids and flow assurance: Impact of geothermal brines on operations, Dec 2021, LA HAGUE, The NETHERLANDS, Netherlands. hal-03582632

HAL Id: hal-03582632

<https://brgm.hal.science/hal-03582632>

Submitted on 21 Feb 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

MECHANISMS AND KINETICS OF CARBON STEEL CORROSION/SCALING AND INHIBITION IN ACTUAL OR RECONSTITUTED AND TREATED GEOTHERMAL WATERS

Chahinez HELALI, Stéphanie BETELU and Ioannis IGNATIADIS

BRGM, Direction Eau, Environnement, Procédés et Analyses (DEPA), 3,
Avenue Claude Guillemin, BP 6009, 45060 ORLEANS, FRANCE.

Key Words

Actual geothermal water, standardized reconstituted geothermal water, carbon steel, corrosion, scaling, petrosourced inhibitor, biosourced inhibitor, hydrogen sulfide, iron sulfide, hydrogeochemical modelling, electrochemical techniques

ABSTRACT

Most of the geothermal installations in France are exploiting low-enthalpy geothermal waters of the Dogger aquifer in the Paris Basin. The geothermal operations are made up of two wells (production-injection, both are about 1,800 m deep), and of surface installations. The operating principle is simple: the waters flow assisted through the carbon steel XC38 (CSXC38) casings to the surface and, after flowing through heat-exchangers, are re-injected into the same aquifer, a few hundred meters farther away. Initially, field experience has shown that, in both production and injection well casings, there is corrosion, scaling and, in some cases, partial clogging.

The geothermal waters, exploited by 50 doublets, are highly mineralized and contain dissolved gases, including H_2S and CO_2 . The main water characteristics are: Anaerobic conditions in which temperatures range from 47-85 °C, pHs from 6.1-6.4, total dissolved solids (TDS) from 6-35 g/L (ionic strength, 0.1-0.6 M) much of which is Cl^- , $[H_2S/HS^-]$ from 5-100 mg/L, $[SO_4^{2-}]$ from 300-1200 mg/L, $[CO_2/HCO_3^-]$ from 250-600 mg/L. The concentrations of TDS, $[H_2S/HS^-]$ and $[CO_2/HCO_3^-]$ vary from place to place. H_2S/HS^- fluctuates versus time and exploitation flowrate. These characteristics classify them among the foremost corrosive natural waters for carbon steel.

Since 1989, the doublets are treated with various petrosourced organic corrosion inhibitors to prevent corrosion-scaling. Currently, there is no more untreated fluids to use them for testing the effectiveness of new inhibitors, whereas there is a great need to improve the geothermal exploitations.

Thanks to physicochemical analyses (from 15 wells from the Val de Marne, south-est of Paris) and modeling by PhreeqC®, a **standardized reconstituted geothermal water** (SRGW) has been realized and approved (tested in stability and composition as a function of time) to be used commonly as corrosive medium for the inhibitors selection. The mechanisms and corrosion kinetics of CSXC38, when immersed at this RGW without inhibitor, acquired electrochemically. The electrochemical behavior of CSXC38, when immersed in RGW treated by a defined concentration of an inhibitor enables the comparison without inhibitor, and then the inhibition efficacy. Several concentrations of the same inhibitor are performed. During the last 5 years, BRGM tested over 30 individual molecules and qualified quite 15 new petrosourced and 5 new biosourced corrosion inhibitors, some of them are now the most commonly used.