

# A critical zone observatory dedicated to suspended sediment transport: The meso-scale Galabre catchment (southern French Alps)

Cédric Legout, Guilhem Freche, Romain Biron, Michel Esteves, Oldrich Navratil, Guillaume Nord, Magdalena Uber, Thomas Grangeon, Nico Hachgenei, Brice Boudevillain, et al.

## ▶ To cite this version:

Cédric Legout, Guilhem Freche, Romain Biron, Michel Esteves, Oldrich Navratil, et al.. A critical zone observatory dedicated to suspended sediment transport: The meso-scale Galabre catchment (southern French Alps). Hydrological Processes, 2021, 35 (3), 10.1002/hyp.14084. hal-03747343

## HAL Id: hal-03747343 https://brgm.hal.science/hal-03747343v1

Submitted on 5 Dec 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

- A critical zone observatory dedicated to suspended sediment transport: the
- 2 meso-scale Galabre catchment (southern French Alps)

3

- 4 Legout C.<sup>1</sup>, Freche G.<sup>1</sup>, Biron R.<sup>2</sup>, Esteves M.<sup>2</sup>, Navratil O.<sup>3</sup>, Nord G.<sup>1</sup>, Uber M.<sup>1</sup>,
- 5 Grangeon T.<sup>4</sup>, Hachgenei N.<sup>1</sup>, Boudevillain B.<sup>1</sup>, Voiron C.<sup>2</sup>, Spadini L<sup>1</sup>.
- <sup>1</sup>Univ. Grenoble Alpes, CNRS, IRD, Grenoble INP, IGE, 38000 Grenoble, France
- <sup>2</sup>Univ. Grenoble Alpes, IRD, CNRS, Grenoble INP, IGE, 38000 Grenoble, France
- 8 <sup>3</sup>Univ. Lumière Lyon 2, Laboratoire Environnement Ville Société, 69500 Bron, France
- 9 <sup>4</sup>Bur Rech Geol & Minieres BRGM, Orleans, France

10

## 11 Keywords

- 12 Hydrology, meteorology, soil erosion, sediment transport, sediment fingerprinting,
- 13 hydrochemistry, critical zone, observatory.

## 14 Summary Paragraph

- 15 The 20 km² Galabre catchment belongs to the French network of critical zone observatories. It
- is representative of the sedimentary geology and meteorological forcing found in Mediterranean
- and mountainous areas. Due to the presence of highly erodible and sloping badlands of various
- 18 lithologies, the site was instrumented in 2007 to understand the dynamics of suspended
- 19 sediments (SS) in such areas. Two meteorological stations including measurements of air
- 20 temperature, wind speed and direction, air moisture, rainfall intensity, raindrop size and velocity
- 21 distribution are installed both in the upper and lower part of the catchment. At the catchment
- outlet, a gauging station records the water level, temperature and the turbidity (10 min. time-
- step). Water and sediment samples are collected automatically to estimate SS concentration-
- 24 turbidity relationships, providing SS fluxes quantifications with known uncertainties. The

sediment samples are further characterized by measuring their particle size distributions (PSD) and by applying a low-cost sediment fingerprinting approach using spectrocolorimetric tracers. Thus, the contributions of badlands on different lithologies to total SS flux are quantified at a high temporal resolution providing the opportunity to better analyze the links between meteorological forcing variability and watershed hydrosedimentary response. The set of measurements was extended to the dissolved phase in 2017. Both the river electrical conductivity and its major ion concentrations are measured each week and every three hours during storm events. This allows progress in understanding both the origin of the water during the events and the partitioning between particulate and dissolved fluxes in the critical zone.

## **Site Descriptions and Measurements**

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

The 20 Galabre catchment  $km^2$ belongs to the Draix-Bléone Observatory (https://oredraixbleone.inrae.fr/en/) which is also part of the research infrastructure OZCAR (Gaillardet et al., 2018). It is located in the southern French pre-Alps (Figure 1a) in the Bléone catchment (Figure 1b). The Bléone river is a tributary of the Durance river which delivers 18% of the total sediment fluxes released by the Rhône river to the Mediterranean Sea (Sadaoui et al., 2016). The elevations of the Galabre catchment range from 735 to 1909 m a.s.l. (above sea level) with mean slopes of 54%, 19% and 6% for hillslopes, intermittent rivers and the main river, respectively. The geology is composed of sedimentary rocks overlain by shallow soils (depth < 50 cm). The different geology types include limestones (34 %), marls (30 %), gypsum (9 %), molasses (9%) and quaternary deposits (18%) (Esteves et al., 2019). Unvegetated badlands covering 9% of the total area are distributed throughout the catchment on all types of geologies (Figure 1c). Grasslands cover 40% of the total area while forests cover more than half of the catchment (34% deciduous and 17% coniferous). The climate is both mountainous

and Mediterranean, characterized by freezing periods in winter and both high temperatures and high rainfall intensities in summer.

Meteorology

Two meteorological stations are installed at la Robine sur Galabre (since 2014) and at Ainac (since 2019) with similar sensors and configurations (Table 1). From 2008 to 2019 Ainac was equipped with an autonomous tipping bucket raingauge (Rainew 111). The common set of measurements at both stations are air temperature and moisture (Campbell Sc. CS215 sensors), wind speed and direction measured with a 2D ultrasonic anemometer (WindSonic4), precipitation measured with a tipping bucket raingauge (Precis Mecanique 3039) and drop size distributions (DSD) measured with an optical disdrometer (OTT Parsivel2). All sensors are supplied by a combination of battery and photovoltaic panel and controlled by a data logger (Campbell CR800) triggering measurement cycles every 15 min. (1 min. for DSD). Data are transmitted each day to a remote ftp server by a 2G/3G modem (Sierra Fastrack FXT009) through the LoggerNet software (Campbell Sc.).

Hydrology

The hydrological station was installed at la Robine sur Galabre in 2007 under a bridge. The river Galabre flows on limestone slabs at this location ensuring a high stability of the cross section without sedimentation or bed scouring. The configuration of this station is similar to that of the meteorological stations (i.e. data logger, energy supply and remote data transfer) with measurements performed every 10 minutes. Water temperature is measured with a Decagon ES-2 sensor. Water level is measured with a 24-GHz radar (Paratronic Cruzoe). Thirty-five discharge measurements were performed, either using a current flow meter or dilution methods to build a stage-discharge rating curve. As these manual measurements ranged

from 0.017 m<sup>3</sup> s<sup>-1</sup> to 0.948 m<sup>3</sup> s<sup>-1</sup>, an extrapolation was performed for higher water levels with a 1-D hydraulic model (HEC-RAS software; Esteves et al., 2019).

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

#### Particulate matter

The hydrological station also includes a turbidimeter (WTW Visolid 700-IQ) connected to a transmitter (IQ182) performing low concentration measurements by 90° diffusion and high concentrations by backscattering. When turbidity thresholds of 5 and 20 g L-1 SiO<sub>2</sub> are exceeded, the data logger triggers sample collection by an automatic sequential water sampler (Teledyne ISCO 3700) every 3 and 1 hour, respectively. The 500 ml water and sediment samples are processed in the laboratory to measure the suspended sediment concentration (SSC), particle size distribution (PSD) and spectral reflectance. Most SSC measurements are obtained by weighing the sample after drying for 24 h at 105°C. When SSC are visually assessed to be small (< 2 g L<sup>-1</sup>) measurements are performed by filtration through pre-weighed 0,45µm fibreglass filters and then weighed after drying. Continuous time series of SSC are obtained with turbidity-SSC relations either general (whole period) or specific to a given flood event. Navratil et al. (2011) assessed the uncertainties at the storm event scale to be, on average 20% and 30% for SSC and suspended sediment yield (SSY), respectively. PSD were measured on samples collected during five events using a laser diffraction sizer (Malvern Mastersizer 2000). The protocol detailed in Grangeon et al. (2012) provides, for each measured sample, eleven PSD measurements, the first one being the effective PSD, while the others provide the disaggregation dynamics of suspended particles and an absolute PSD. An aggregation degree was deduced from these measurements. The dried sediment samples were also measured with a portable spectrocolorimeter (Konica Minolta 2600d). Similar measurements were also carried out on source soil samples collected in badland areas of different geological nature. From the diffuse reflectance spectra, a low-cost sediment fingerprinting approach was developed (Legout et al., 2013). It allows to quantify with a maximum uncertainty of 20% the contribution of primary geological sources molasse, marl and limestone to each SS sample.

## Dissolved matter

Data characterizing the dissolved phase are available since 2017. Measurements are performed in samples collected automatically by the sequential sampler at a weekly frequency and a time step of a few hours during runoff events. Electrical conductivity is measured with a portable sensor (WTW 340i) regularly calibrated with commercial standards. Major ion concentrations (F-, Cl-, NO<sub>2</sub>-, Br-, NO<sub>3</sub>-, SO<sub>4</sub><sup>2</sup>-, Na+, NH<sub>4</sub>+, K+, Ca<sup>2+</sup>, Mg<sup>2+</sup>) are measured by ionic chromatography (Metrohm modular systems 732-733).

## Results and interest of the data set

The Galabre catchment is characterised by high SSC with 50% of the total SSY transported at SSC exceeding 13g L<sup>-1</sup>. It is highly intermittent with 50% of the total SSY transported in less than 0.1% of time and with less than 5% of the water volume. SS transport occurs mainly during two periods associated to two distinct rainfall regimes (Esteves et al., 2019). In early winter (November and December) widespread rainfall events associated to low rainfall intensities and large durations (>5 h) lead to a high hydrological connectivity within the catchment generating high liquid discharges (e.g. max. 34 m³ s<sup>-1</sup> on 24/12/09). Even though the SSC are usually low during these events (max. 16 g L<sup>-1</sup> on 24/12/09), SS fluxes remain high. In summer (June to September), convective storms are usually brief (1-2 h) over limited areas (few square km) leading to high SSC (e.g. max. 360 g L<sup>-1</sup> on 9/9/12) with low flow discharge (max. 0.3 m³ s<sup>-1</sup> on 9/9/12) due to a low hydrological connectivity. While the median effective diameters of SS are small (10μm), they are aggregated at various levels and exhibit either a stability or variability at the event scale (Grangeon et al., 2012). The sediment fingerprinting also revealed

a stability of the geological source contribution for some events while others exhibit high temporal variations (Legout et al., 2013).

The overall data set allows to address process-based understanding of the transfer of water and matter in the critical zone, particularly the links between sediment export from meso-scale watershed and meteorological forcing. It was already used in studies on sediment budgets at larger scales in the Bléone catchment in order to assess the spatial variations of erosion intensity (Evrard et al., 2011) or the drivers of the temporal variability of SS fluxes (Navratil et al., 2012). It also allows to test conceptual or physically based models investigating assumptions such as the respective contribution of badlands and the riverbed to SSY (Park et al., 2019, Misset et al., 2019) or the role of the catchment configuration on SS connectivity (Uber et al., 2020).

## Data availability

The data set summarised in Table 1 can be accessed through the OSUG data center at https://doi.osug.fr/public/DRAIXBLEONE\_GAL/index.html. A brief description and the data policy is provided for the overall data set (https://doi.org/10.17178/DRAIXBLEONE\_GAL.all) and for each sub data set. Alternatively, some data sets can be visualized directly on the BDOH database (https://bdoh.irstea.fr/DRAIX/nos-donnees?site=Galabre). BDOH also enables the interpolation of time steps for export in multiple formats after creating an account.

## **Acknowledgements**

The data acquired in the Galabre catchment is funded by the Institut National des Sciences de l'Univers (INSU/CNRS) and the Observatoire des Sciences de l'Univers de Grenoble (OSUG / Université Grenoble Alpes). The authors are grateful to Laurent Bourgès and OSUG for the publication of the DOI of datasets.

## References

145

- 146 Esteves M., Legout C., Navratil O., Evrard O. 2019. Medium term high frequency observation of
- 147 discharges and suspended sediment in a Mediterranean mountainous catchment. Journal of Hydrology
- 148 568: 562-574.
- Evrard O., Navratil O., Ayrault S., Ahmadi M., Némery J., Legout C., Lefèvre I., Poirel A., Bonté P., Esteves
- 150 M. 2011. Combining suspended sediment monitoring and fingerprinting to determine the spatial origin
- of fine sediment in a mountainous river catchment. Earth Surface Processes and Landforms 36(8):
- 152 1072-1089.
- 153 Gaillardet, J., Braud, I., Hankard, F., and co-authors: OZCAR: the French network of Critical Zone
- 154 Observatories. Vadose journal, 17(1),2018, doi: 10.2136/vzj2018.04.0067
- 155 Grangeon T., Legout C., Esteves M., Gratiot N., Navratil O. 2012. Variability of suspended particles size
- during highly concentrated flood events in a small mountainous catchment. Journal of Soils and
- 157 Sediments 12(10): 1549-1558.
- Legout C., Poulenard J., Nemery J., Navratil O., Grangeon T., Evrard O., Esteves M. 2013. Quantifying
- 159 suspended sediment sources during floods in headwater catchments by spectrocolorimetry. Journal of
- 160 Soils and Sediments 8: 1478-1492.
- 161 Misset C., Recking A., Legout C., Poirel A., Cazihlac M., Esteves M., Bertrand M. 2019. An attempt to
- Link suspended load hysteresis patterns and sediment sources configuration in alpine catchments.
- 163 Journal of Hydrology 576: 72-84.
- Navratil O., Esteves M., Legout C., Gratiot N., Némery J., Willmore S., Grangeon T. 2011. Global
- uncertainty analysis of suspended sediment monitoring using turbidimeter in a small mountainous
- river catchment. Journal of Hydrology 398: 246-259.
- Navratil O., Evrard O., Esteves M., Legout C., Ayrault S., Némery J., Mate-Marin A., Ahmadi M., Lefèvre
- 168 I., Poirel A., Bonté P. 2012. Temporal variability of suspended sediment sources in an alpine catchment

169	combining river/rainfall monitoring and sediment fingerprinting. Earth Surface Processes and
170	Landforms 37(8): 828-846.
171	Park J., Batalla R.J., Birgand F., Esteves M., Gentile F., Harrington J.R., Navratil O., Lopez-Tarazon J.A.,
172	Vericat D. 2019. Influences of catchment and river channel characteristics on the magnitude and
173	dynamics of storage and re-suspension of fine sediments in river beds. Water 11 (5): 878.
174	Sadaoui M., Ludwig W., Bourrin F., Raimbault P. 2016. Controls, budgets and variability of riverine
175	sediment fluxes to the Gulf of Lions (NW Mediterranean Sea). Journal of Hydrology 540: 1002:1015.
176	Uber M., Nord G. Legout C., Cea L. How do modeling choices impact the representation of structural
177	connectivity and the dynamics of suspended sediment fluxes in distributed soil erosion models? Earth
178	Surface Dynamics Discussion, https://doi.org/10.5194/esurf-2020-64, in review, 2020.