



**HAL**  
open science

# Modeling variable-density flow in saturated-unsaturated porous media: An advanced numerical model

Anis Younes, Behshad Koohbor, Benjamin Belfort, Philippe Ackerer, Joanna Doummar, Marwan Fahs

## ► To cite this version:

Anis Younes, Behshad Koohbor, Benjamin Belfort, Philippe Ackerer, Joanna Doummar, et al.. Modeling variable-density flow in saturated-unsaturated porous media: An advanced numerical model. *Advances in Water Resources*, 2022, 159, pp.104077. 10.1016/j.advwatres.2021.104077 . hal-04389944

**HAL Id: hal-04389944**

**<https://brgm.hal.science/hal-04389944>**

Submitted on 12 Jan 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34

**Modeling variable-density flow in saturated-unsaturated porous media: An advanced numerical model**

Anis Younes,<sup>1</sup> Behshad Koohbor,<sup>2</sup> Benjamin Belfort,<sup>1</sup> Philippe Ackerer,<sup>1</sup> Joanna Doummar,<sup>3</sup>  
Marwan Fahs<sup>1\*</sup>

<sup>1</sup> Institut Terre et Environnement de Strasbourg, Université de Strasbourg, CNRS, ENGEES, UMR 7063  
<sup>2</sup> BRGM (French Geological Survey), Orléans, France  
<sup>3</sup> Department of Geology, American University of Beirut, Beirut, Lebanon

*Submitted to Advances in Water Resources*

Contact author: Marwan Fahs  
E-mail: [fahs@unistra.fr](mailto:fahs@unistra.fr)

35        **Abstract**

36    Modeling variable-density flow in unconfined aquifers is a challenging task because of the  
37    nonlinear coupling between variably saturated flow and contaminant transport. This results in  
38    a highly nonlinear system since the strongly nonlinear Richards flow equation is, in addition,  
39    coupled to the advection-dispersion transport equation by viscosity and density variation. The  
40    solution of such a nonlinear system is often subject to convergence issues and can be very  
41    expansive in terms of computational time, especially for large-scale problems. Conventional  
42    numerical algorithms based on the sequential approach and the classical finite difference or  
43    finite element methods with the first-order backward Euler time integration scheme are  
44    generally inefficient and/or do not provide satisfactory results. In this work, we develop a new  
45    efficient and accurate 2D numerical model for the transport of dense contaminants in  
46    unsaturated porous media that allows for the simulation of large-scale problems. This research  
47    describes a new model that combines advanced spatial discretization methods (mixed hybrid  
48    finite element method, discontinuous Galerkin finite element method, and multipoint flux  
49    approximation method) with higher-order time integration techniques via the method of lines  
50    (MOL). The latter allows one to adapt the time step's size and the order of the time  
51    integration to improve the computational efficiency while maintaining accuracy. The  
52    robustness and accuracy of the new model are shown by comparison against a widely used  
53    commercial code based on the standard finite element method. The applicability of the  
54    developed model to a large-scale problem is then investigated by simulating saltwater  
55    intrusion under a climate change projection and long-term pumping regimes for the Akkar  
56    coastal aquifer in Lebanon using a simplified 2D conceptual model.

57    **Key words:** unsaturated flow, variable-density flow, mixed finite element method,  
58    discontinuous finite element method, multi-Point flux approximation, method of lines, field  
59    simulation.

## 60 **1. Introduction**

61 Many saturated-unsaturated aquifer systems are subject to the pollution of soils and  
62 groundwater resources by dense contaminants such as leachates derived from waste disposal  
63 sites, agricultural activity, or sanitary landfills. Contamination by saltwater is a major  
64 environmental issue that occurs, for instance, with the leakage of brine beneath the salt lakes,  
65 flooding of coastal areas by seawater, saltwater intrusion in coastal aquifers due to over-  
66 pumping, tidal effects or sea-level rise. For such situations, fluid flow and solute transport  
67 equations are coupled by the fluid density.

68 Several studies have focused on variable-density flow in saturated porous media [1-4] since  
69 the effect of density variations on the flow behavior in the saturated zone is much more  
70 significant than in the unsaturated zone. Indeed, in the unsaturated zone, the density variation  
71 in the liquid phase is much less important than the density variation between the liquid and  
72 the air phase (about three orders of magnitude). Simmons *et al.* [5] investigated the migration  
73 of a dense contaminant plume through the unsaturated zone using laboratory experiments.  
74 They showed that the unsaturated zone and position of the water table must be considered in  
75 contamination studies in order to predict the migration pathways, rates and the ultimate fate of  
76 dense contaminant plumes [5]. Ostrom *et al.* [6] and Dane *et al.* [7] investigated saturated  
77 variable-density flow with a narrow unsaturated zone in their physical models. They showed  
78 that the development of plume instabilities depends on the density difference between the  
79 plume and groundwater, the horizontal Darcy velocity, the contaminant leakage rates, the  
80 source dimensions, the hydrodynamic dispersion and the permeability of the porous media.  
81 Ouyang and Zheng [8] numerically showed that density-driven transport is significant for  
82 dissolved chemicals through unsaturated sandy soils. Using numerical simulations, Boufadel  
83 *et al.* [9] showed that concentration-dependent viscosity effects below dry salt lakes are

84 significant under fully saturated conditions, but have minor effects under unsaturated flow  
85 conditions.

86 Considering both saturated and unsaturated zones for coupled flow and transport processes  
87 can improve the representativeness of simulations when investigating evaporation and salt  
88 accumulation effects on riparian freshwater lenses [10] or when investigating the effect of  
89 water table salinization [11-14] or the effect of the slope of the seaward boundary on saltwater  
90 intrusion [15-17].

91 Including the unsaturated zone when modeling variable-density flow problems requires the  
92 solution of a coupled flow-transport nonlinear system. In such a system, the flow is ruled by  
93 the Richards' equation (RE), which uses nonlinear constitutive relationships between  
94 hydraulic conductivity, water content, and pressure head [18, 19]. Because of these  
95 nonlinearities, providing an accurate solution of RE is challenging due to convergence issues  
96 and high time consumption, particularly in the presence of sharp wetting fronts, as when  
97 simulating infiltration into initially dry soils [20]. These difficulties are increased in the case  
98 of a dense contaminant because of additional nonlinearities induced by density variations  
99 which require coupling between the RE and the advection-dispersion transport equation.

100 Because of nonlinearities and the absence of analytical solutions, numerical models are  
101 valuable tools for solving these complex problems and for understanding and predicting the  
102 propagation of contaminations in the aquifers. However, most of the existing numerical  
103 models do not provide satisfactory results when applied to unsaturated variable-density flow  
104 problems, essentially because:

- 105 • Classical spatial discretization methods such as finite element (FE) or finite difference  
106 (FD) methods may not provide an accurate velocity field, especially in the case of  
107 highly heterogeneous and/or anisotropic domains [21, 22].

- 108 • When applied to the transport equation, the classical methods provide results with  
109 significant unphysical oscillations for advection-dominated transport. If combined  
110 with first-order upstream techniques, they suffer from excessive numerical dispersion  
111 [23].
- 112 • Temporal discretization is often based on the first-order backward Euler scheme,  
113 which does not allow large time steps and, as a consequence, induces excessive  
114 computational time.
- 115 • Coupling between flow and transport equations is usually performed via a sequential  
116 approach with an empirical time-stepping technique without any control over the  
117 temporal truncation error, which may lead to inaccurate results [24].

118 To overcome these difficulties, in this work, we combine advanced spatial and temporal  
119 approximation methods. The flow equation is solved using the mixed hybrid finite element  
120 (MHFE) method [25]. This method simultaneously approximates both pressure and fluxes  
121 with the same order of convergence. The MHFE method is (i) locally conservative, (ii) well  
122 adapted for general unstructured meshes, and (iii) can easily handle full permeability tensors.  
123 The unknowns with the hybrid formulation are the traces of the pressure at edges/faces [26].  
124 The lumped form of the MHFE method proposed in [27] is employed in this work to avoid  
125 spurious oscillations encountered with transient simulations in the case of sharp wetting fronts  
126 [28].

127 For the transport equation, the discontinuous Galerkin (DG) method is used to discretize the  
128 advection equation and combined with the multi-point flux approximation (MPFA) method  
129 for the discretization of the dispersion equation [29]. The DG method is strictly conservative  
130 at the element level. It yields accurate results for problems involving sharp fronts [30]. DG is  
131 used with an implicit time discretization that avoids (i) time-step limitation caused by the

132 Courant–Friedrichs–Lewy (CFL) condition of explicit schemes and (ii) the use of a slope-  
133 limiting procedure to ensure the stability of the results [29]. A discontinuous linear  
134 approximation is used for the concentration at each element of the mesh. Often, the DG  
135 degrees of freedom (DOFs) correspond to the discontinuous concentration at the nodes inside  
136 each element (see, for instance, [31, 32]). The DOFs used here are the mean concentration and  
137 the horizontal and vertical components of the concentration gradient at each element [29].  
138 This choice allows one to imitate the upwind finite volume (FV) method when only the first  
139 equation corresponding to the mean concentration value is kept. Further, this choice of DOFs  
140 allows one to combine the DG method with MPFA for the approximation of dispersion  
141 without any operator splitting [29]. The classical methods, like FD or FV, based on two-point  
142 flux approximation (TPFA) to compute the flux between two adjacent elements, may not  
143 converge unless the grid is K-orthogonal [33]. The MPFA method calculates the flux at an  
144 element boundary using multiple surrounding elements; therefore, it is well adapted for  
145 general grids and full dispersion tensors [34].

146 The spatial discretization (MHFE\_DG\_MPFA) based upon the combination of MHFE, DG,  
147 and MPFA methods was shown to be robust and accurate for modeling variable-density flow  
148 in saturated porous media [35] and is extended in this work for unsaturated flow.

149 Higher-order time integration methods are used via the method of lines (MOL) to allow large  
150 time steps and improve the efficiency of the model. The flow and transport equations are  
151 solved simultaneously in a single step, which avoids slow convergence encountered with the  
152 sequential approach. The MOL allows one to adapt the time step's length and the order of the  
153 temporal discretization (up to 5 using the Backward Difference Formulas) in order to reduce  
154 the computational time while maintaining accuracy. The MOL is effective for the solution of  
155 the RE in the unsaturated zone [36] as well as for variable-density flow in saturated porous  
156 media [37]. In this work, the MOL is used for the first time for dense contaminant transport in

157 unsaturated porous media. Variable-order and variable-step size time integration are  
 158 performed using the DASPK [38] time solver.

## 159 **2. Governing Equations**

160 Dense contaminant transport in unsaturated porous media is governed by the Darcy-  
 161 Buckingham's law, the mass conservation of the fluid and the advection-dispersion transport  
 162 equation. Assuming the Boussinesq approximation is valid, the flow in the unsaturated zone  
 163 can be written in terms of equivalent freshwater head, as follows:

$$164 \quad \frac{\partial \theta}{\partial t} = \left( c(h) + S_s \frac{\theta(h)}{\theta_s} \right) \frac{\partial H}{\partial t} = -\nabla \cdot \mathbf{q} + q_s \quad (1)$$

$$165 \quad \mathbf{q} = -k_r \mathbf{K} \left( \nabla H + \frac{\rho - \rho_0}{\rho_0} \nabla z \right) \quad (2)$$

166 where  $c(h) = \partial \theta / \partial h$  is the specific moisture capacity [ $L^{-1}$ ],  $S_s$  the specific mass storativity  
 167 related to head changes [ $L^{-1}$ ],  $\theta$  the current water content [ $L^3 L^{-3}$ ],  $\theta_s$  the saturated water  
 168 content [ $L^3 L^{-3}$ ],  $H = h + z$  the equivalent freshwater head [ $L$ ],  $h = \frac{P}{\rho_0 g}$  the pressure head,  $P$   
 169 the pressure [ $Pa$ ],  $z$  the upward vertical coordinate [ $L$ ],  $t$  the time [ $T$ ],  $\mathbf{q}$  the Darcy's velocity  
 170 [ $LT^{-1}$ ],  $q_s$  the sink term [ $T^{-1}$ ],  $k_r$  the relative conductivity [-],  $\mathbf{K} = \frac{\rho_0 g}{\mu} \mathbf{k}$  the hydraulic  
 171 conductivity tensor [ $LT^{-1}$ ],  $\rho_0$  the density of the displaced fluid [ $ML^{-3}$ ],  $g$  the gravity  
 172 acceleration [ $LT^{-2}$ ],  $\mu$  the fluid dynamic viscosity [ $ML^{-1}T^{-1}$ ],  $\mathbf{k}$  the permeability tensor  
 173 dependent only on the porous medium [ $L^2$ ], and  $\rho$  the fluid density [ $ML^{-3}$ ].

174 The solute transport in the unsaturated zone is ruled by the advection-dispersion equation:

175 
$$\frac{\partial(\theta C)}{\partial t} + \nabla \cdot (\mathbf{q}C) - \nabla \cdot (\mathbf{D}\nabla C) = q_s C \quad (3)$$

176 where  $C$  [-] is the scaled concentration and  $\mathbf{D}$  the dispersion tensor given by:

177 
$$\mathbf{D} = D_m \mathbf{I} + (\alpha_L - \alpha_T) \mathbf{q} \otimes \mathbf{q} / |\mathbf{q}| + \alpha_T |\mathbf{q}| \mathbf{I} \quad (4)$$

178 with  $\alpha_L$  and  $\alpha_T$  the longitudinal and transverse dispersivities [L],  $D_m$  the pore water  
179 diffusion coefficient [ $L^2T^{-1}$ ], and  $\mathbf{I}$  the unit tensor.

180 We use the standard van Genuchten [39] model to define the relation between water content  
181 and pressure head:

182 
$$S_e = \frac{\theta(h) - \theta_r}{\theta_s - \theta_r} = \begin{cases} \frac{1}{\left(1 + (\alpha|h|)^n\right)^m} & h < 0 \\ 1 & h \geq 0 \end{cases} \quad (5)$$

183 where  $\alpha$  [ $L^{-1}$ ] and  $n$  [-] are the van Genuchten parameters,  $m = 1 - 1/n$ ,  $S_e$  [-] the effective  
184 saturation, and  $\theta_r$  the residual water content [ $L^3L^{-3}$ ].

185 The conductivity-saturation relationship is analytically derived from the Mualem [40] model,  
186 as proposed by van Genuchten [39]:

187 
$$k_r = S_e^{1/2} \left[ 1 - \left( 1 - S_e^{1/m} \right)^m \right]^2. \quad (6)$$

188 Darcy velocity  $\mathbf{q}$  in equation (2) depends on both the pressure head  $h$  and the concentration  
189  $C$ .

190 The flow and transport equations are coupled by the state equations. In the case of salt  
191 contamination, we can use the polynomial approximations given in [1]:

192 
$$\rho = \rho_0 + (\rho_1 - \rho_0)C, \text{ and } \mu = \mu_0(1.0 + 0.4819C - 0.2774C^2 + 0.7814C^3) \quad (7)$$

193 where  $\rho_0$  and  $\rho_1$  are densities of freshwater and saltwater and  $\mu_0$  the freshwater viscosity.  
 194 Different state equations may be used for density or viscosity [1].

195 **3. The numerical model**

196 The system of nonlinear equations (1)–(7), valid in 3D domains, is solved hereafter for 2D  
 197 vertical domains using adapted advanced numerical methods that allow an accurate estimation  
 198 of the velocity and concentration distributions for heterogeneous domains and unstructured  
 199 meshes. The main stages to form the final system to be solved are summarized hereafter for a  
 200 general triangular mesh.

201 *3.1 The lumped MHFE method for modeling fluid flow*

202 With the classical standard FE method, the head is approximated linearly inside each element  
 203 using standard chapeau functions, and hence, the velocity is constant at the element level.  
 204 With the MHFE method, we assume a linear approximation for the velocity  $\mathbf{q}$  inside each  
 205 triangle  $E$  using the linear Raviart-Thomas basis functions:

206 
$$\mathbf{q} = \sum_{j=1}^3 Q_j^E \mathbf{w}_j^E \quad (8)$$

207 where  $Q_j^E$  is the flux across the edge  $j$  of  $E$  and  $\mathbf{w}_j^E$  is the Raviart-Thomas basis function  
 208 [41].

209 The mass lumping procedure is used to avoid over- and undershoots observed for transient  
 210 simulations with small time steps [27, 28]. The basic idea of this procedure is to consider

211 steady-state flow (the mean head at the element  $E$  is  $H_E = (TH_1^E + TH_2^E + TH_3^E)/3$ ), and then  
 212 the transient component is directly added to the expression of the flux [35]:

$$213 \quad Q_i^E = \sum_j N_{ij}^E \left( TH_j^E + \frac{\rho_E - \rho_0}{\rho_0} z_j^E \right) - \frac{|E|}{3} r_E \frac{dTH_i^E}{dt} + \frac{Q_S^E}{3} \quad (9)$$

214 where  $TH_i^E$  (resp.  $z_i^E$ ) is the mean head (resp. mean elevation) of the edge  $i$  of  $E$  with  
 215  $TH_i = Th_i + z_i$ ,  $Th_i$  is the mean pressure head,  $j$  is an edge of  $E$ ,  $N$  is a local matrix of

216 coefficients  $N_{ij}^E = -k_r^E \frac{\det(\mathbf{K}_E)}{|E|} \mathbf{r}_i^T \cdot \mathbf{K}_E^{-1} \cdot \mathbf{r}_j$  where  $\mathbf{r}_i$  is the edge vector face to the vertex  $i$  of

217 the element  $E$  (see Younes *et al.* [42] for more details),  $|E|$  is the area of  $E$ ,

218  $r_E = c(h_E) + S_S \theta(h_E)/\theta_S$  is the accumulation term in Richards' equation,  $h_E$  is the mean

219 pressure head at  $E$ , and  $Q_S^E = \int_E q_S$  is the sink term on  $E$ .

220 The final flow system is formed by imposing continuity of heads ( $TH_i^E = TH_i^{E'}$ ) and fluxes

221 ( $Q_i^E + Q_i^{E'} = 0$ ) between the adjacent elements  $E$  and  $E'$  having a common edge  $i$ :

$$222 \quad \sum_j N_{ij}^E \left( TH_j^E + \frac{\rho_E - \rho_0}{\rho_0} z_j^E \right) + \sum_j N_{ij}^{E'} \left( TH_j^{E'} + \frac{\rho_{E'} - \rho_0}{\rho_0} z_j^{E'} \right) - \left( \frac{|E|}{3} r_E + \frac{|E'|}{3} r_{E'} \right) \frac{dTH_i^E}{dt} + \frac{Q_S^E}{3} + \frac{Q_S^{E'}}{3} = 0$$

223 (10)

224 The indices  $i$  and  $j$  are global, and the system is solved for the mean heads at edges  $TH_i$ .

225 In the case of a Dirichlet condition with a prescribed head  $H_{imp}$  at the boundary edge  $i$ ,

226 equation (10) is replaced by  $TH_i = H_{imp}$ . If the boundary edge  $i$  has a prescribed flux  $Q_{imp}$

227 (Neumann boundary condition), equation (10) is replaced by  $Q_i^E + Q_{imp} = 0$ .

228 Note that the system of equations (10) is highly nonlinear since (i) the local matrix  $N$  and the  
 229 accumulation term  $r$  depend on the pressure head and (ii) the hydraulic conductivity and the  
 230 buoyancy term depend on the concentration.

### 231 3.2 The DG-MPFA method for modeling solute transport

232 Using the mass conservation of the fluid, given by equation (1), the transport equation (3)  
 233 simplifies to:

$$234 \quad \theta \frac{\partial C}{\partial t} + \mathbf{q} \nabla C + \nabla \cdot \mathbf{q}_D = 0. \quad (11)$$

235 With  $\mathbf{q}_D = -\mathbf{D} \nabla C$ , the dispersive flux, assumed to have a constant divergence over the  
 236 element  $E$ :

$$237 \quad \nabla \cdot \mathbf{q}_D = \frac{1}{|E|} \sum_i Q d_i^E \quad (12)$$

238 where  $Q d_i^E$  is the dispersive flux across the edge  $i$  of  $E$ .

239 The concentration inside the element  $E$  is approximated with linear discontinuous functions:

$$240 \quad C^E = \sum_{i=1}^3 C_{E,i} \phi_{E,i} \quad (13)$$

241 with  $\phi_{E,i}$  being the interpolation function and  $i$  a local index that refers to the  $i^{\text{th}}$  DOF  $C_{E,i}$  of  
 242 the concentration inside the element  $E$ .

243 In the literature, the DOFs are often chosen (see, for instance, [43]) to be the concentration at  
 244 the nodes and  $\phi_{E,i}$ , the classical chapeau functions. In this work, the DOFs are the mean

245 concentration  $C_{E,1}$  and the components of the concentration gradient  $C_{E,2}$  and  $C_{E,3}$ , with the  
 246 corresponding interpolation functions:

$$247 \quad \phi_{E,1} = 1, \quad \phi_{E,2} = (x - x_E), \quad \phi_{E,3} = (z - z_E),$$

248 where  $x$  and  $z$  are horizontal and vertical coordinates, and  $x_E$  and  $z_E$  are the coordinates of  
 249 the center of the element  $E$ . Thus, the polynomial approximation of the concentration inside  
 250 the element  $E$  is  $C^E = C_{E,1} + C_{E,2}(x - x_E) + C_{E,3}(z - z_E)$ .

251 The variational formulation of Eq (11) using the test function  $\phi_{E,i}$  is:

$$252 \quad \int_E \theta \frac{\partial C}{\partial t} \phi_{E,i} - \int_E C \nabla \cdot (\mathbf{q} \phi_{E,i}) + \int_E \nabla \cdot (\mathbf{q} C \phi_{E,i}) + \int_E \phi_{E,i} \nabla \cdot \mathbf{q}_D = 0. \quad (14)$$

253 Using Green's formula and Eq (12) and Eq (13), we obtain:

$$254 \quad \sum_j \frac{dC_{E,j}}{dt} \theta_E \int_E \phi_{E,j} \phi_{E,i} - \sum_j \int_E C_{E,j} \phi_{E,j} \nabla \cdot (\mathbf{q} \phi_{E,i}) + \sum_j \int_j C_j^* \phi_{E,i} \mathbf{q} \cdot \boldsymbol{\eta}_j^E + \sum_j Q d_j^E \int_E \phi_{E,i} = 0 \quad (15)$$

255 where  $C_j^*$  is the upstream concentration at the edge  $j$ ,  $\boldsymbol{\eta}_j^E$  is the unit outward normal vector  
 256 to the edge  $j$  of  $E$ , and  $\mathbf{q}$  is the velocity obtained by substituting equation (9) into equation  
 257 (8).

258 Equation (15) is written for the three test functions  $\phi_{E,i}$  ( $i=1,2,3$ ) for each element  $E$ . The  
 259 index  $j$  ( $j=1,2,3$ ) refers to the  $j^{\text{th}}$  DOF of the concentration in the element  $E$  in the two  
 260 first terms of Eq (15) and to the  $j^{\text{th}}$  edge of  $E$  for the last two terms in equation (15).

261 The upstream concentration  $C_j^*$  at the edge  $j$  can be written as follows:

262 
$$C_j^* = \tau_j^E C_j^E + (1 - \tau_j^E) C_j^{E'} \quad (16)$$

263 with  $\tau_j^E = 1$  for an outward flux ( $\mathbf{q} \cdot \boldsymbol{\eta}_j^E \geq 0$ ), else  $\tau_j^E = 0$ .

264 Thus,  $C_j^*$  corresponds to  $C_j^E$ , the concentration at the edge  $j$  calculated using the polynomial  
 265 approximation of the concentration at the element  $E$ , or  $C_j^{E'}$ , the concentration at  $j$   
 266 calculated using the polynomial approximation of the concentration at the element  $E'$ , sharing  
 267 the edge  $j$  with  $E$ .

268 Equation (15) yields three equations for each element  $E$  having 3 adjacent elements  
 269 ( $E1, E2, E3$ ):


270 
$$[A] \begin{pmatrix} \frac{dC_{E,1}}{dt} \\ \frac{dC_{E,2}}{dt} \\ \frac{dC_{E,3}}{dt} \end{pmatrix} = [B] \begin{bmatrix} C_{E,1} \\ C_{E,2} \\ C_{E,3} \end{bmatrix} - [M^0] \begin{bmatrix} C_{E,1} \\ C_{E,2} \\ C_{E,3} \end{bmatrix} - \sum_{\ell=1}^3 [M^\ell] \begin{bmatrix} C_{E\ell,1} \\ C_{E\ell,2} \\ C_{E\ell,3} \end{bmatrix} - \begin{bmatrix} \sum_j Qd_j^E \\ 0 \\ 0 \end{bmatrix} \quad (17)$$

271 with:

272 
$$\begin{aligned} A_{i,j} &= \theta_E \int_E \phi_{E,j} \phi_{E,i} & B_{i,j} &= \int_E \phi_{E,j} \nabla \cdot (\mathbf{q} \phi_{E,i}) \\ M_{i,j}^0 &= \sum_{\ell} \tau_{\ell}^E \mathbf{q} \cdot \boldsymbol{\eta}_{\ell}^E \int_{\ell} \phi_{E,i} \phi_{E,j} & M_{i,j}^{\ell} &= (1 - \tau_{\ell}^E) \mathbf{q} \cdot \boldsymbol{\eta}_{\ell}^E \int_{\ell} \phi_{E,i} \phi_{E\ell,j} \end{aligned}$$

273 To avoid operator splitting between advection and dispersion, the dispersive flux  $Qd_j^E$  in  
 274 equation (17) is approximated using the MPFA method. The latter has similar properties to  
 275 the MFE method since both are locally conservative and can handle unstructured meshes and  
 276 anisotropic and heterogeneous domains. The two methods can be equivalent for some specific  
 277 situations [34, 44]. However, contrary to the MHFE method, which uses the concentration at

278 the edges as DOFs, MPFA uses the mean concentration at each element as DOFs. Hence, the  
 279 discrete approximation of  $Qd_j^E$  can be directly added to the system of equations (17), which  
 280 avoids the necessary operator splitting if the MHFE method is used for dispersion, as in [30].



281

282 **Figure 1.** A triangular element divided into three subcells, with linear concentration  
 283 approximation on each subcell.

284 To calculate  $Qd_j^E$  with the MPFA method, we assume that the concentration inside the sub-  
 285 cell  $(O, F_1, G, F_2)$  formed by the node  $O$ , the center  $G$ , and the mid-edges  $F_1$  and  $F_2$  (gray  
 286 area in the Figure 1) is linear. Hence, it can be approximated using  $C_{E,1}$ ,  $\lambda_1$  and  $\lambda_2$  the  
 287 concentrations at respectively  $G$  and the two continuity points  $f_1$  and  $f_2$  located at

288 
$$\frac{Of_1}{OF_1} = \frac{Of_2}{OF_2} = \frac{2}{3}.$$

289 Therefore,  $(O, f_1, G, f_2)$  is a parallelogram, and the half-edge fluxes

290 
$$\left( Qd_o^1 = \int_o^{F_1} -D\nabla C \text{ and } Qd_o^2 = \int_o^{F_2} -D\nabla C \right) \text{ are}$$

291 
$$\begin{pmatrix} Qd_o^1 \\ Qd_o^2 \end{pmatrix} = \frac{3}{|E|} \begin{pmatrix} -\overline{OF_1}^\perp \cdot \mathbf{D}_E \cdot \overline{OF_1}^\perp & \overline{OF_1}^\perp \cdot \mathbf{D}_E \cdot \overline{OF_2}^\perp \\ \overline{OF_1}^\perp \cdot \mathbf{D}_E \cdot \overline{OF_2}^\perp & -\overline{OF_2}^\perp \cdot \mathbf{D}_E \cdot \overline{OF_2}^\perp \end{pmatrix} \begin{pmatrix} \lambda_1 - C_{E,1} \\ \lambda_2 - C_{E,1} \end{pmatrix} \quad (18)$$

292 where  $\mathbf{D}_E$  is the dispersion tensor of the element  $E$ , given by equation (4) and using the  
 293 velocity at the center of  $E$  from equations (8) and (9).

294 Equation (18) is written for all elements sharing the vertex  $O$ . Then, imposing continuity of  
 295 half-edge fluxes and continuity of the concentration at the continuity points gives a local  
 296 system, which we invert to obtain explicitly the concentration at each continuity point as a  
 297 function of the concentration at all elements sharing the node  $O$ . The latter is then replaced in  
 298 equation (18), and the summation of all half-edge fluxes is then substituted into equation (17)  
 299 (see [29] for more details). Therefore, the first line of the system (17) contains the  
 300 contribution of all elements sharing at least one node of the element  $E$ . The second and third  
 301 equations of (17) contain the contribution of adjacent elements sharing an edge with  $E$ . Note  
 302 that, because of the judicious choice of DOFs, the DG\_MPFA scheme reduces to an upwind  
 303 FV\_MPFA scheme by removing the second and third equations of (17) for all mesh elements.

304 The final vector of residuals for the global flow-transport nonlinear system is formed by the  
 305 system of equations (10), written for the unknown pressure head  $TH_i$  at the edges, followed  
 306 by the system of equations (17), written for the three unknown DOFs of the concentration at  
 307 each element.

### 308 *3.3 The temporal discretization*

309 The coupled nonlinear flow equation (10) and transport equation (17) are written in a single  
 310 implicit system of ordinary differential equations (ODEs) or differential algebraic equations  
 311 (DAEs) of the general form:

$$312 \quad F(t, \mathbf{y}, \mathbf{y}') = 0 \quad (19)$$

313 where  $\mathbf{y} = \left[ (TH_i)_{i=1, \dots, nb\_edges}, (C_{E,1}, C_{E,2}, C_{E,3})_{E=1, \dots, nb\_elements} \right]$  is the vector of unknowns formed

314 by (i) the head traces at all the edges of the mesh (except Dirichlet boundary edges) and (ii)  
 315 the three DOFs for the concentration at each element of the mesh. This vector reduces to  
 316  $\mathbf{y} = \left[ (TH_i)_{i=1, \dots, nb\_edges}, (C_{E,l})_{E=1, \dots, nb\_elements} \right]$  with only one DOF per element for the  
 317 concentration in the case of FV (instead of DG) formulation.

318 The system (19) is solved in time using higher-order methods, which are known to be more  
 319 efficient than lowest-order methods. Indeed, higher-order methods allow larger time steps and  
 320 less effort in the nonlinear solver compared with the lowest-order methods [45]. Furthermore,  
 321 higher-order methods are often combined with an efficient automatic time-stepping scheme,  
 322 which improves the computational efficiency. The time-step size management is optimized to  
 323 maintain a given temporal discretization error [36, 45-47].

324 Among the integration methods, the Backward Difference Formula (BDF) has good stability  
 325 properties and is well adapted for time integration of stiff problems [48]. The Fixed Leading  
 326 Coefficient Backward Difference Formula (FLCBDF) is used in this work via the DASPK  
 327 solver. The basic idea of the  $k^{\text{th}}$ -order FLCBDF method is to convert the system  
 328  $F(t_n, \mathbf{y}_n, \mathbf{y}'_n) = 0$  at a given time  $t_n = t_{n-1} + \underline{h}$  with solution history  $\mathbf{y}_{n-1}, \dots, \mathbf{y}_{n-k}$  to the system  
 329  $F(t_n, \mathbf{y}_n, \hat{\mathbf{a}}\mathbf{y}_n + \hat{\mathbf{b}}) = 0$  where  $\hat{\mathbf{a}}$  and  $\hat{\mathbf{b}}$  depend on the step size  $\underline{h}$ , the order  $k$ , and the solution  
 330 history (see [49] for more details).

331 The main advantages of the FLCBDF method are: (i) it avoids the unstable behavior of the  
 332 interpolated fixed-step methods and (ii) the Newton iteration matrix can be reused for more  
 333 steps than in a fully variable-step approach [38, 50].

334 The Jacobian matrix is evaluated numerically using finite difference approximation. The same  
 335 Jacobian matrix is used for several time steps to improve efficiency. Furthermore, to reduce  
 336 drastically the computational time required for the calculation of the Jacobian, sparsity and

337 structure of  $J$  are provided and the variables are perturbed by group using the column  
338 grouping technique (see [51, 52]).

339 The order (up to the fifth-order) of BDF, as well as the time step's size, are optimized to  
340 reduce the computational effort while maintaining a small temporal truncation error. The  
341 latter is estimated using a predictor-corrector scheme. Both absolute and relative convergence  
342 criteria are fixed to  $10^{-5}$  in this work.

343 In this work, we use the DASPK time solver with the preconditioned Krylov iterative method  
344 to solve the linear systems arising at each time step.

#### 345 **4. Numerical experiments**

346 Three test cases are investigated to show the efficiency and accuracy of the developed  
347 numerical model. The first test case is inspired by the laboratory experiment performed by  
348 Vauclin *et al.* [53]. It deals with the infiltration, under constant flux, of a dense contaminant  
349 into an unsaturated-saturated porous medium. This test, which is relatively simple from a  
350 computational point of view, is used to validate the developed code against a standard finite  
351 element solution obtained using COMSOL Multiphysics®. The second test case, inspired by  
352 the work of Forsyth and Kropinski [54], deals with the infiltration of a dense contaminant in a  
353 heterogeneous initially dry soil. The simulated moving sharp front induces high nonlinearity,  
354 which makes this computational test cases very challenging. It is used to highlight the  
355 efficiency of our newly developed model and to assess the advantages of combining high-  
356 performance numerical methods compared with classical ones implemented in COMSOL.  
357 The last test case is investigated to show the applicability of the new model to large-scale  
358 problems. In this test case, the developed numerical tool is used to simulate a simplified  
359 conceptual 2D model of saltwater intrusion under climate change for the Akkar coastal  
360 aquifer in Lebanon.

361 4.1 Infiltration of a dense contaminant in an unsaturated-saturated porous medium

362 Vauclin *et al.* [53] performed laboratory experiments to investigate the transient position of  
363 the water table under artificial recharge. The problem is extended here by including the  
364 infiltration from the surface of a dense contaminant and used for the validation of the new  
365 model by comparison with COMSOL results. The domain is a rectangular sandbox of 600 cm  
366  $\times$  200 cm, with the water table located at 65 cm from the bottom. The initial conditions  
367 correspond to hydrostatic pressure distribution with a domain free from pollutants. Infiltration  
368 of a contaminant under a constant flux of 86.4 cm/day is then applied over 200 cm in the  
369 center of the soil surface. A Dirichlet boundary condition with a head of 65 cm is fixed below  
370 the water table. A no-flow boundary is prescribed for the bottom and top surface, except for  
371 the infiltration zone. Owing to the symmetry of this problem, only the right-hand side of the  
372 domain is modeled with a no-flow boundary imposed along the axis of symmetry. The  
373 material properties are given in Table 1.

374

375

376

377

378

379

380 **Table 1.** Simulation parameters for the first test case inspired from Vauclin *et al.* [53].

Parameters	
$\theta_r$	0.01

$\theta_s$	0.3
$\alpha(cm^{-1})$	0.033
$n$	4.1
$K(cm.s^{-1})$	$10^{-2}$
$S_s(cm^{-1})$	$10^{-10}$
$\alpha_L(cm)$	1
$\alpha_T(cm)$	0.1
$D_m(m^2/s)$	$10^{-9}$
$\rho_0(kg/m^3)$	1000
$\rho_1(kg/m^3)$	1000 or 1100
$\mu(kgm^{-1}s^{-1})$	0.001

---

381

382 The simulation is performed for 80 hours using a triangular mesh formed by 4273 triangular  
383 elements. Two configurations are investigated: in the first one, the injected contaminant is a  
384 tracer ( $\rho_1 = 1000 kg/m^3$ ), whereas in the second, the contaminant has a higher density  
385 ( $\rho_1 = 1100 kg/m^3$ ).

386 The evolution of the contaminant plume during the time for both situations is shown in Figure  
387 2. Before reaching the water table (initially at  $z = 65$  cm), the tracer and dense contaminant  
388 plumes are almost the same (see results at  $t = 15$  h). Indeed, density variation seems to have  
389 no effect during the transport through the unsaturated zone. The main reasons for this  
390 similarity are that (i) a fixed flux is used at the surface and hence the same quantity of  
391 contaminant is intruded in the system for both situations and (ii) the density variation in the  
392 liquid phase (10%) is much less important than the density variation between the liquid and  
393 air phase, which is about three orders of magnitude. This last reason is no longer valid once  
394 the plume reaches the water table. As a consequence, due to density effects, the dense  
395 contaminant moves downward in the saturated domain, creating a recirculation zone (vortex)  
396 near the water table interface (see results of Figure 2, at  $t = 30$  h), whereas the tracer

397 contaminant remains near the water table. The velocity distribution in the unsaturated zone is  
398 quite similar for the tracer and dense contaminant situations, whereas strong differences can  
399 be observed in the saturated zone. For the tracer contamination, the velocity is not affected by  
400 the evolution of the contaminant and remains mainly horizontal. However, in the case of the  
401 dense contaminant, strong vertical velocities appear due to density effects, which bring the  
402 contaminant down to the bottom. As a consequence, the results in terms of velocity field and  
403 contaminant distribution at  $t = 80$  h for the dense and tracer situations are completely  
404 different. The tracer moves mainly horizontally at the upper part of the saturated zone with a  
405 maximum displacement near the water table, whereas the dense contaminant moves toward  
406 the substratum and then horizontally in the lower part of the domain. The vortex remains near  
407 the water table interface (see results of Figure 2 at  $t = 80$  h).

408 The validity of the new model is investigated by comparing the obtained results against those  
409 of the popular COMSOL model. The same spatial discretization was used to allow for a  
410 comparison between COMSOL and our newly developed model, and the solution was also  
411 checked on a fine mesh since no analytical solution is available. The results of the two models  
412 are almost similar, which demonstrates the validity of the developed model (Figure 3). Notice  
413 that the non-dimensional mass injected from the upper boundary during the simulation is  
414 0.288. With the new numerical model, the total mass in the domain at 80h is 0.28815, whereas  
415 it is 0.2820 with COMSOL. Hence, the mass balance error with COMSOL is around 0.021,  
416 whereas it is around  $5 \times 10^{-4}$  with the new model. Therefore, the very small difference  
417 observed in Figure 3 between the isocontour levels of the new model and COMSOL is  
418 probably due to the loss of mass observed with COMSOL.

419 Both COMSOL and the new model were used with the MOL and a variable high-order (up to  
420 5) time integration BDF method. The evolution of the time step's length with the new model  
421 during the simulation of the tracer and the dense contaminant infiltration situations are

422 depicted in Figure 4. The tracer simulation required 51s of CPU time, for a total number of  
423 1128 time steps. The time step starts at  $10^{-4}$  s and increases to 1655 s in almost a monotonic  
424 way (see Figure 4a). Only 37 Jacobian evaluations are required during the 1128 time steps.  
425 The simulation of the dense contaminant required more CPU time (70 s) and needed more  
426 time steps (1751). In this case, smaller time steps are used (the maximum is 389 s), and the  
427 time step size is no longer monotonic (Figure 4b), probably because of the more complex  
428 occurring physics. Note that the evolution of the time step's size remains quite similar before  
429 the wetting front reaches the saturated zone. The same Jacobian is maintained for several time  
430 steps since the number of evaluations of the Jacobian remains small (only 40 evaluations),  
431 which shows the efficiency of the new model.


432 As a comparison, the simulation of the dense contaminant with COMSOL requires 1452 time  
433 steps. The evolutions of the time step's length with both models are similar. However, the  
434 new model was around 10 times more efficient than COMSOL. Indeed, the new model spent  
435 only 70 seconds of CPU time, whereas COMSOL required 720 seconds for the whole  
436 simulation. In fact, COMSOL was very slow in the early stages of simulation, probably due to  
437 the significant oscillating pressure and concentration values observed in the neighborhood of  
438 the infiltration front. These unphysical oscillations affect the convergence of the nonlinear  
439 solver and increase the number of nonlinear iterations per time step.

440

441

442


443




444

445 **Figure 2.** velocity field and contaminant distributions for the infiltration of a tracer and a  
 446 dense contaminant in an unsaturated-saturated system.


447



448  
 449 **Figure 3.** Concentration distribution at  $t = 80\text{h}$  for the dense contaminant infiltration: Results  
 450 of the new model (contours) versus COMSOL results (dashed-lines)



451



452  
 453 **Figure 4.** Time step evolution for the tracer (a) and dense (b) contaminant infiltration  
 454 simulated with the new model.

455 4.2 Infiltration of a dense contaminant in a heterogeneous initially dry soil

456 Simulating infiltration into dry soils is known to be a challenging task. Indeed, for very dry  
457 conditions, the head gradient becomes extremely large at the wetting front, which can lead to  
458 large computational times and unphysical oscillations [20]. To investigate the efficiency of  
459 the developed model for such situations, we simulate the infiltration problem given in [36].  
460 The problem is inspired from Huang *et al.* [55] and involves infiltration under a constant head  
461 boundary condition into a heterogeneous dry soil. The domain has a rectangular shape of 125  
462 cm width and 230 cm depth and contains two horizontal layers. The surface layer of 40 cm  
463 thickness is formed by a clayey soil. The subsurface layer is a sandy soil of 190 cm thickness.  
464 The properties of the two soil layers are depicted in Table 2. A Dirichlet boundary condition  
465 is prescribed in the strip  $0 \leq x \leq 20\text{cm}$  at the surface with a fixed pressure head of -10 cm. A  
466 fixed pressure head of  $-10^4$  cm is maintained at the bottom of the domain. The other sides are  
467 impervious. A constant initial pressure head of  $-10^4$  cm is considered for the entire domain,  
468 which corresponds to an initial water content of  $0.059 \text{ cm}^3.\text{cm}^{-3}$  and  $0.045 \text{ cm}^3.\text{cm}^{-3}$ ,  
469 respectively, in the upper and lower layer. The infiltrated contaminant has a density of  
470  $1025\text{kg}.\text{m}^{-3}$ , which corresponds to seawater density. A triangular mesh of 3505 elements is  
471 used for the spatial discretization, and the final simulation time is 7 days.

472

473

474

475


476

477  
478

**Table 2.** Simulation parameters for the problem of contaminant infiltration in a heterogeneous initial dry soil.

Parameters	Upper Layer	Lower Layer
$\theta_r$	0.0001	0.045
$\theta_s$	0.40	0.43
$\alpha(cm^{-1})$	0.0174	0.145
$n$	1.37	2.68
$K(\times 10^{-4} cm.s^{-1})$	3.5	82.5
$S_s(\times 10^{-10} cm^{-1})$	1	1
$\alpha_L(cm)$	0.5	0.5
$\alpha_T(cm)$	0.1	0.1
$D_m(m^2/s)$	$10^{-9}$	$10^{-9}$
$\rho_0(kg/m^3)$	1000	1000
$\rho_1(kg/m^3)$	1025	1025
$\mu(kgm^{-1}s^{-1})$	0.001	0.001

479 The obtained pressure and concentration distributions are shown in Figure 5. In this figure,  
480 the pressure shows a sharp front, reflecting a very high gradient caused by the dry initial  
481 conditions (-100 m).



482  
483  
484  
485  
486  
487

**Figure 5.** (a) Pressure distribution (in m) with COMSOL, (b) pressure and (c) concentration distributions with the new model at  $t = 7$  days for the problem of contaminant infiltration in a heterogeneous initial dry soil. Dashed lines represent results of upwind first order FV instead of DG for advection.

488 The sharp pressure front cannot be accurately simulated with COMSOL. Indeed, the  
489 simulation of this test case with COMSOL using the same mesh failed to converge because of  
490 unphysical oscillations generated near the wetting interface. Convergence problems have been  
491 also encountered when changing the initial (and bottom) conditions from -100 m to -1 m. The  
492 only way to obtain a convergent solution with COMSOL was to use a finer mesh of about  
493 14,000 elements and an initial pressure head of -1 m instead of -100 m. And, even for such a  
494 situation, the results of COMSOL are inaccurate since the obtained pressure head is between -  
495 1.4 m and -0.1 m instead of -1 m and -0.1 m. Besides, the solution contains strong unphysical  
496 oscillations near the wetting interface (Figure 5a). These unphysical oscillations are avoided  
497 with the new code, thanks to the used advanced numerical methods and, especially, the mass  
498 lumping procedure, which avoids unphysical oscillations in the case of transient simulations  
499 with sharp wetting fronts [27, 28].

500 Figure 5c shows the final concentration distribution at  $t = 7$  days. The results of a simplified  
501 version of the numerical code using the upwind first-order FV scheme instead of DG are also  
502 depicted (dashed lines) in Figure 5c. This figure shows that a large numerical diffusion is  
503 generated using the upwind first-order FV method. To quantify the difference between the  
504 two methods, the spread of the concentration  $L_S = X_{0.9} - X_{0.1}$ , corresponding to the distance  
505 between the 10% and 90% isochlors at the left vertical side of the domain, is measured for the  
506 FV and DG simulations. The spread with FV is  $L_S^{FV} = 0.4$ , whereas with DG, it is  
507  $L_S^{DG} = 0.24$ . Hence, due to numerical diffusion, the spread with the FV method is around  
508 170% that of DG. This shows clearly that DG is well-adapted for advective-dominated  
509 transport and generates limited numerical diffusion compared with the upwind first-order FV  
510 method.

511 It is worth noting that, in the first test case, the contaminant distribution in the unsaturated

512 region was not affected by the density of the contaminant, since the infiltration occurred under  
 513 a constant flux boundary condition. For the current test case, the concentration distribution is  
 514 sensitive to the density of the contaminant because of the Dirichlet boundary condition used at  
 515 the surface infiltration boundary (results are not shown in the paper). The pollutant infiltration  
 516 is slightly more pronounced with the dense contaminant than with the tracer contaminant. The  
 517 total mass in the system at  $t = 7$  days is 0.64 kg with the tracer, whereas it is 0.66 kg if the  
 518 contaminant has a density of  $1025 \text{ kg.m}^{-3}$ . This total mass can increase up to 0.76 kg in the  
 519 case of a contaminant with a density of  $1200 \text{ kg.m}^{-3}$  (brine contamination).

520 Finally, to highlight the benefit of the higher-order time integration for the investigated  
 521 challenging infiltration problem, we compare the efficiency of the model when used with a  
 522 first-order and with a variable high-order (up to 5) time integration with the BDF method.

523 **Table 3.** Performance statistics for the first-order and variable order methods implemented in  
 524 the advanced developed model for the simulation of the second test case.

<b>Time integration method</b>	<b>CPU</b>	<b>Nb time steps</b>	<b>Nb Jacobian</b>	<b>Max time step</b>	<b>Mean time step</b>
First-order	896	28871	115	45	21
Variable-order (up to 5)	128	4322	138	378	140

525  
 526 The results of Table 3 show that the high-order method requires more Jacobian evaluations,  
 527 but allows much larger time steps and needs fewer calculations compared with the classical  
 528 first-order method. The variable high-order method is around 7 times more efficient than the  
 529 first-order method for the investigated problem.

### 530 *4.3 Large-scale simulation of SWI under climate change*

531 The developed numerical tool is used to simulate a large-scale contamination problem with  
 532 large spatial and temporal ranges that occurs in the Akkar unconfined coastal aquifer, located

533 in the north of Lebanon (Figure 6a). The plain is cultivated with market gardening and cereals  
534 crops and the aquifer underwent a significant increase in pumping water, both for irrigation  
535 and domestic consumption, notably because of the massive arrival of Syrian refugees in the  
536 region. As a consequence, some pumping wells suffer from salinization caused by the  
537 overexploitation of the aquifer.

538 Because of the lack of data (infiltration rates, piezometric heads, etc) and of precise  
539 knowledge of initial and boundary conditions, a full 3D simulation of the above-described  
540 problem has not been considered. A representative 2D vertical cross-section is designed to  
541 investigate saltwater intrusion under climate change projection and long-term pumping  
542 regimes.

543

544

545


546

547

548

549

550



551 **Figure 6.** (a) Location of the Akkar aquifer, (b) conceptual representation of the aquifer with  
 552 a lognormal permeability field and the boundary conditions (c) the recharge data until 2019  
 553 and projections under climate change between 2020 and 2099 and (d) pumping rates in  
 554 production wells.

555 The shore-perpendicular section has an extension of 2 km offshore and 6 km onshore [56].  
556 The depth of the Akkar basin varies between 100 m and 170 m from the surface and is formed  
557 by fluvial deposits. In the conceptual model (Figure 6b), the permeability field was generated  
558 assuming a lognormal distribution with a variance of  $1.0 \text{ m}^4$  and a geometric average  
559 conductivity of  $0.945 \cdot 10^{-11} \text{ m}^2$ . An exponential correlation function was used with horizontal  
560 and vertical correlation lengths of 1000 m and 10 m, respectively. The bottom is formed by  
561 clays and marls and is considered impermeable. The left vertical side corresponds to the sea  
562 boundary, which has a prescribed concentration of  $C = 35 \text{ g.l}^{-1}$  and a vertical hydrostatic  
563 pressure distribution. The recharge, depicted in Figure 6c, corresponds to observed data for  
564 the period between 1962 and 2020 and a projection for the period 2020–2099, obtained from  
565 the IPSL\_CM5 Global Climate Model (GCM) [57]. A weak regional flow is assumed at the  
566 right land boundary. Although radial upconing around wells have necessarily 3D  
567 configurations, two wells are assumed to represent the different pumping activities in the  
568 Akkar aquifer [58]. The wells are located at, respectively, 1500 m and 3000 m from the  
569 shoreline at, respectively, a depth of 45 m and 30 m. The rates for the two pumping wells  
570 (Figure 6d) are assumed to represent the observed rates for the period 1962–2020 and  
571 expected rates (with increasing water demand) for 2020–2099. Note that pumping was  
572 stopped for Well 1 (the closest to the sea) in 2020 because of salinization. The pumping rate  
573 of Well 1 was transferred to Well 2.

574

575

576

577

578

579 **Table 4.** Properties of the soil and the water for the simulation of the simplified conceptual  
 580 Akkar aquifer.


Parameter	Value
Freshwater density $\rho_0 (kg.m^{-3})$	1,000
Seawater density $\rho_1 (kg.m^{-3})$	1,025
Gravity $g(m.s^{-2})$	9.81
Viscosity $\mu(kg.m^{-1}.s^{-1})$	$10^{-3}$
Anisotropy ratio $r_k (= k_z/k_x)$	0.1
Porosity $\varepsilon$	0.39
Storage coefficient $S_s(m^{-1})$	$5 \times 10^{-4}$
Molecular diffusion $D_m(m^2.s^{-1})$	$1.0 \times 10^{-9}$
$\alpha(cm^{-1})$	0.01
$n$	1.75
$\theta_s$	0.39
$\theta_r$	0.1
$\alpha_L(m)$	5
$\alpha_T(m)$	0.5
Right boundary condition: Regional flow/ unit width $q_d(m^2.s^{-1})$	$6 \times 10^{-7}$

581


582 The domain is discretized with approximately 75K triangular elements with an almost equal  
 583 area of 15 m<sup>2</sup>. The simulation is, at first, performed for a long time with the yearly average  
 584 recharge of pre-1962, without pumping to mimic the natural equilibrium conditions (Figure  
 585 7a). The value of recharge for this period is taken uniformly and equal to 90 mm.y<sup>-1</sup>. Next,  
 586 two periods are simulated: (i) the 1962–2020 period, which leads to the current situation of  
 587 the coastal aquifer (Figure 7b), and (ii) the 2020–2099 period, which corresponds to the future  
 588 response of the aquifer to the impact of a climate change projection and estimated pumping  
 589 regime (Figure 7c).

590 The problem is solved for 333,031 DOFs (unknowns) on a computer with a single Intel i7-  
 591 7700 processor 3.6 GHz and 16 Go of RAM (i.e. Random Access Memory). The whole  
 592 simulation (138 years) required around 9h of CPU time.


593



594



595




596

597 **Figure 7.** Spatial salinity distribution in the aquifer and water table position: (a) at 1962 (state  
598 of equilibrium), (b) currently at 2020 and (c) predictions for 2099.  
599

600 Figure 7a shows that, without any pumping, the natural equilibrium situation of 1962 shows a  
601 moderate saltwater intrusion. The concentration profile shows a small dispersion. The aquifer  
602 is only contaminated near the bottom, for a distance of around 400 m from the shoreline.  
603 Because of pumping, the concentration distribution at 2020 shows a more significant saltwater  
604 intrusion. In Figure 7b, Well 1, located 1500 m from the shoreline, is reached by salt  
605 contamination, which is in agreement with the field observations. The breakthrough curves of  
606 salt concentration at the two wells are depicted in Figure 8. In this figure, a small inflection is  
607 observed in 2020 when pumping is stopped at Well 1. Then, the concentration continues to  
608 increase because of the advancement of the salt front caused by the pumping in Well 2. The  
609 final concentration in Well 1 is very high and reaches  $30 \text{ g.l}^{-1}$ . Well 2, located 3000 m from

610 the shoreline, starts to be salinized at around 2060. Then, the concentration continues to  
611 increase significantly, with a high rate of salinization, which makes the well unusable in 2070  
612 and onward.



613

614 **Figure 8.** Dimensionless concentration (concentration/seawater concentration) at the two  
615 pumping wells.

616

617 Figure 7b shows that the water table slightly falls in 2020 due to pumping. The major part of

618 the aquifer is contaminated by salt in 2100 (Figure 7c) because of (i) the reduced recharge

619 caused by climate change and (ii) the increase of the pumping rate of Well 2 due to the

620 expected increase of water demand. The progress of saltwater intrusion inside the aquifer is


621 relatively fast, as can be observed in Figure 9, which depicts the evolution of  $L_{toe}$  (i.e. the

622 maximum horizontal distance between the shoreline and the 50% salt concentration contour

623 line). The evolution of  $L_{toe}$  is almost linear until 2070. The saltwater intrusion is significant

624 and fast. From Figure 9, the salt front invades the domain, with an almost constant velocity of

625  $25 \text{ m.y}^{-1}$ .



626

627 **Figure 9.** Evolution of  $L_{toe}$  (the maximum horizontal distance between the shoreline and the  
 628 50% salt concentration contour).

629

630 Finally, note that the predicted state in 2100 (Figure 7c) shows that a significant water table  
 631 falls more than 20 m, which warrants the use of that saturated-unsaturated model to  
 632 investigate problems of density-driven flow in unconfined coastal aquifers.

### 633 5. Conclusion

634 Unsaturated–saturated aquifer systems can be subject to pollution by dense contaminants such  
 635 as SWI in coastal unconfined aquifers. Modeling such problems requires the solution of a  
 636 highly nonlinear system combining the nonlinear Richards’ equation with the advection-  
 637 dispersion transport equation. The solution of such a nonlinear system can be hampered by  
 638 convergence issues and excessive computational time, especially for regional-scale problems.  
 639 A new model has been developed in this work based on advanced spatial discretization  
 640 methods (lumped MHFE, implicit DG and MPFA methods) and higher-order time integration  
 641 techniques via the method of lines.

642 The efficiency and accuracy of the new model have been investigated for three test cases. The  
 643 first test case deals with the infiltration of a contaminant in an unsaturated-saturated

644 rectangular sandbox. This test case served as a benchmark to validate the numerical model.  
645 The results of simulations are similar to those obtained with COMSOL. Tracer and dense  
646 contaminants yielded similar plumes in the unsaturated zone. However, when the water table  
647 is reached, the dense contaminant moves downward, creating a recirculation zone, whereas  
648 the tracer moves horizontally along the water table. The test case shows that the new model is  
649 highly efficient since it uses large time steps and maintains the same Jacobian for several  
650 calculations.

651 The second test case deals with the challenging problem of infiltration into a heterogeneous  
652 and initially very dry soil. For this problem, COMSOL failed to reproduce the sharp pressure  
653 front and generated strong unphysical oscillations. The new model gives accurate results, and  
654 the higher-order integration method is around 7 times more efficient than the classical first-  
655 order method.

656 Finally, the developed model has been used to simulate a simplified 2D conceptual model of  
657 SWI in the Akkar unconfined aquifer, under climate change and long-term pumping regimes.  
658 The purpose of this last test case was to show the applicability of the newly developed model  
659 in simulating large-scale regional problems under dynamic conditions. The results show that  
660 SWI was moderate in the case of natural equilibrium (in 1962). Then, because of the pumping  
661 undergone in the past decades, a significant SWI occurred and salinization reached the  
662 pumping well at 1500 m. Simulations until 2100 show that the reduced recharge caused by  
663 climate change and the increase in pumping due to the evolution of water demand induce  
664 significant salinization of the aquifer, with a salt front advancing inland at an average speed of  
665  $25 \text{ m.y}^{-1}$  and an important water table fall. Note that these preliminary results must be taken  
666 with caution since the simulations were performed on a simplified 2D conceptual model  
667 without any calibration because of the lack of data.

668 This study points out that the newly developed numerical model is an interesting tool to assess  
669 environmental issues. Efficient and robust numerical models are useful for applications at  
670 large scales, involving repetitive simulations, as in model calibration, sensitivity/uncertainty  
671 analysis, and scenario-based studies.

672

### 673 **Acknowledgments**

674 The authors wish to thank the Investissements d'Avenir and ADEME for supporting this work  
675 as part of the GEOTREF research project.

676 Marwan Fahs would like to acknowledge the support from the National School of Water and  
677 Environmental Engineering of Strasbourg through the research project PORO6100.

678

- 680
- 681 [1] Diersch, H.J., Kolditz, O., 2002. Variable-density flow and transport in porous media:  
682 approaches and challenges. *Advances in Water Resources* 25, 899-944.
- 683 [2] Simmons, C.T., 2005. Variable-density groundwater flow: From current challenges to  
684 future possibilities. *Hydrogeology Journal* 13, 116-119.
- 685 [3] Graf, T., Simmons, C.T., Boufadel, M.C., Neuweiler, I., 2010. Movement of dense  
686 plumes in variably saturated porous media: numerical model and results. *Proceedings of*  
687 *the XVIII International Conference on Water Resources (CMWR)*, Barcelona, Spain,  
688 June 2010. Abstract 23.
- 689 [4] Werner, A.D., Bakker, M., Post, V.E.A., Vandenbohede, A., Lu, C., Ataie-Ashtiani, B.,  
690 et al., 2013. Seawater intrusion processes, investigation and management: Recent  
691 advances and future challenges. *Advances in Water Resources*, 51, 3–26.
- 692 [5] Simmons, C.T., Pierini, M.L., Hutson, J.L., 2002. Laboratory investigation of variable  
693 density flow and solute transport in unsaturated-saturated porous media. *Transport in*  
694 *Porous Media*, 47, 215-244.
- 695 [6] Oostrom, M., Hayworth, J. S., Dane, J. H. and Guven, O., 1992. Behaviour of dense  
696 aqueous phase leachate plumes in homogeneous porous media. *Water Resources*  
697 *Research* 28(8), 2123–2134.
- 698 [7] Dane, F.H., Guven, O., Oostrom, M., Hayworth, J. S. and Leijnse, A., 1994. Dense  
699 aqueous phase contaminant plume behaviour in porous media near the groundwater  
700 table. *IAHS Publ.* 222,333–340.
- 701 [8] Ouyang, Y., Zheng, C., 1999. Density-driven transport of dissolved chemicals through  
702 unsaturated soil, *Soil Science* 164(6), 376–390.
- 703 [9] Boufadel, M.C., Suidan, M.T. and Venosa, A.D., 1999. Numerical modeling of water  
704 flow below dry salt lakes: effect of capillarity and viscosity. *Journal of Hydrology* 221,  
705 55–74.
- 706 [10] America, I., Zhang, C., Werner, A. D., & van der Zee Sjoerd E. A. T. M. (2020).  
707 Evaporation and salt accumulation effects on riparian freshwater lenses. *Water*  
708 *Resources Research*, 56, e2019WR026380. <https://doi.org/10.1029/2019WR026380>
- 709 [11] Werner, A.D., Lockington, D.A., 2004. The potential for soil salinization above aquifers  
710 impacted by seawater intrusion, in *Proceedings of 13th International Soil Conservation*  
711 *Organisation Conference: Conserving Soil and Water for Society: Sharing Solutions*,  
712 edited by S. R. Raine et al., 6 pp., ASSSI/IECA, Brisbane.
- 713 [12] Werner, A.D., Lockington, D.A., 2006. Tidal impacts on riparian salinities near  
714 estuaries. *Journal of Hydrology* 328, 511–522.
- 715 [13] Ibrahim, M.K., Miyazaki, T., Nishimura, T., Imoto, H., 2014. Contribution of shallow  
716 groundwater rapid fluctuation to soil salinization under arid and semiarid climate.  
717 *Arabian Journal of Geosciences* 7, 3901–3911.
- 718 [14] Badaruddin, S., Werner, A.D., Morgan, L.K., 2015. Water table salinization due to  
719 seawater intrusion. *Water Resources Research* 51, 8397–8408.
- 720 [15] Qu, W., Li, H., Wan, L., Wang, X., Jiang, X., 2014. Numerical simulations of steady-  
721 state salinity distribution and submarine groundwater discharges in homogeneous  
722 anisotropic coastal aquifers, *Advances in Water Resources*. 74, 318-328.
- 723 [16] Zhou, P., Li, G., Lu, Y., Li, M., 2014. Numerical modeling of the effects of beach slope  
724 on water-table fluctuation in the unconfined aquifer of Donghai Island, China.  
725 *Hydrogeology Journal* 22, 383–96.
- 726 [17] Ataie-Ashtiani, B., Volker, R.E., Lockington D.A., 2001. Tidal effects on groundwater  
727 dynamics in unconfined aquifers. *Hydrological Processes* 15, 655–69.

- 728 [18] Farthing, M.W., Ogden, F.L., 2017. Numerical Solution of Richards' Equation: A  
729 Review of Advances and Challenges. *Soil Science Society of America Journal* 81, 1257.
- 730 [19] Szymkiewicz, A., 2013. *Modelling Water Flow in Unsaturated Porous Media*,  
731 *GeoPlanet: Earth and Planetary Sciences*. Springer Berlin Heidelberg, Berlin,  
732 Heidelberg.
- 733 [20] Zha, Y., Yang, J., Yin, L., Zhang, Y., Zeng, W., Shi, L., 2017. A modified Picard  
734 iteration scheme for overcoming numerical difficulties of simulating infiltration into dry  
735 soil. *Journal of Hydrology* 551, 56–69.
- 736 [21] Durlofsky, L., 1994. Accuracy of mixed and control volume finite element  
737 approximations to darcy velocity and related quantities. *Water Resources Research*  
738 30(4), 965–974.
- 739 [22] Schneider, M., Glaser, D., Flemisch, B., Helmig, R., 2018. Comparison of finite-volume  
740 schemes for diffusion problems. *Oil & Gas Science and Technology - Rev. IFP*  
741 *Energies nouvelles* 73, 82.
- 742 [23] Konz, M., Ackerer, P., Younes, A., Huggenberger, P., Zechner, E., 2009. 2D Stable  
743 Layered Laboratory-scale Experiments for Testing Density-coupled Flow Models.  
744 *Water Resources research* 45, W02404.
- 745 [24] Younes, A., Ackerer, P., 2010. Empirical vs. time stepping with embedded error control  
746 for density-driven flow in porous media. *Water Resources research* 46(8).
- 747 [25] Chavent, G., Roberts, J.-E., 1991. A unified physical presentation of mixed, mixed-  
748 hybrid finite element method and standard finite difference approximations for the  
749 determination of velocities in water flow problems. *Advances in Water Resources*  
750 14(6), 329– 348.
- 751 [26] Younes, A., Ackerer, P., Delay, F., 2010. Mixed finite element for solving 2D diffusion-  
752 type equations. *Reviews of Geophysics*, 48(1).
- 753 [27] Younes, A., Ackerer, P., Lehmann, F., 2006. A new mass lumping scheme for the  
754 mixed hybrid finite element method. *International Journal for Numerical Methods in*  
755 *Engineering* 67(1), 89-107.
- 756 [28] Belfort, B., Ramasomanan, F., Younes, A., Lehmann, F., 2009. An efficient Lumped  
757 Mixed Hybrid Finite Element Formulation for variably saturated groundwater flow.  
758 *Vadose Zone Journal*. 8, 352-362.
- 759 [29] Younes, A., Ackerer, P., 2008. Solving the Advection-Dispersion Equation with  
760 Discontinuous Galerkin and Multipoint Flux Approximation methods on unstructured  
761 meshes. *International Journal for Numerical Methods in Fluids* 58(6), 687-708.
- 762 [30] Siegel, P, Mosé, R, Ackerer, P, Jaffré, J., 1997. Solution of the advection-diffusion  
763 equation using a combination of discontinuous and mixed finite elements. *International*  
764 *Journal for Numerical Methods in Fluids* 24, 595-613.
- 765 [31] Ackerer, P., Younes, A., Mosé, R., 1999. Modelling variable density flow and solute  
766 transport in porous medium: 1. Numerical model and verification. *Transport in Porous*  
767 *Media* 35, 345-373.
- 768 [32] Hoteit, H., Firoozabadi, A., 2005. Multicomponent fluid flow by discontinuous Galerkin  
769 and mixed methods in unfractured and fractured media. *Water Resources Research*.  
770 41(11).
- 771 [33] Aavatsmark, I., Barkve, T., Bøe, O., & Mannseth, T., 1998. Discretization on  
772 unstructured grids for inhomogeneous, anisotropic media. Part I: Derivation of the  
773 methods. *SIAM Journal on Scientific Computing* 19(5), 1700-1716.
- 774 [34] Younes, A., Fontaine, V., 2008. Hybrid and Multi Point Formulations of the Lowest  
775 Order Mixed Methods for Darcy's Flow on Triangles. *International Journal for*  
776 *Numerical Methods in Fluids* 58(9), 1041-1062.

- 777 [35] Ackerer, P., Younes, A., 2008. Efficient approximations for the simulation of density  
778 driven flow in porous media. *Advances in Water Resources* 31(1), 15-27.
- 779 [36] Fahs, M., Younes, A., Lehmann, F., 2009. An easy and efficient combination of the  
780 Mixed Finite Element Method and the Method of Lines for the resolution of Richards'  
781 Equation. *Environmental Modelling & Software* 24(9), 1122-1126.
- 782 [37] Younes, A., Fahs, M., Ahmed, S., 2009. Solving density driven flow problems with  
783 efficient spatial discretizations and higher-order time integration methods. *Advances in*  
784 *Water Resources* 32(3), 340-352.
- 785 [38] Van Keken, P.E., Yuen, D.A., Petzold, L.R., 1995. DASPK: A new high order and  
786 adaptive time-integration technique with applications to mantle convection with  
787 strongly temperature-and pressure-dependent rheology. *Geophysical & Astrophysical*  
788 *Fluid Dynamics* 80(1-2), 57-74.
- 789 [39] van Genuchten, M.Th., 1980. A Closed-form Equation for Predicting the Hydraulic  
790 Conductivity of Unsaturated Soils. *Soil Science Society of America Journal* 44(5), 892-  
791 898.
- 792 [40] Mualem, Y., 1976. A new model for predicting the hydraulic conductivity of  
793 unsaturated porous media. *Water Resources Research* 12, 513-522.
- 794 [41] Raviart, P.A., Thomas, J.M., 1977. A mixed finite element method for second order  
795 elliptic problems, in *Mathematical Aspects of Finite Element Method*. Lecture Notes in  
796 *Mathematics* 606, 292-315.
- 797 [42] Younes, A., Ackerer, P., Chavent, G., 2004. From mixed finite elements to finite  
798 volumes for elliptic PDE in 2 and 3 dimensions. *International Journal for Numerical*  
799 *Methods in Engineering*, 59, 365-388.
- 800 [43] Moortgat, J., Firoozabadi, A., 2016. Mixed-hybrid and vertex-discontinuous-Galerkin  
801 finite element modeling of multiphase compositional flow on 3D unstructured grids.  
802 *Journal of Computational Physics* 315, 476-500.
- 803 [44] Vohralík, M., 2006. Equivalence between lowest-order mixed finite element and multi-  
804 point finite volume methods on simplicial meshes. *Mathematical Modelling and*  
805 *Numerical Analysis* 40 (2), 367-391.
- 806 [45] Farthing, M.W., Kees, C.E., Miller, C.T., 2002. Mixed finite element methods and  
807 higher-order temporal approximations. *Advances in Water Resources* 25, 85-101.
- 808 [46] Tocci, M.D., Kelly, C.T., Miller, C.T., 1997. Accurate and economical solution of the  
809 pressure-head form of Richards' equation by the method of lines. *Advances in Water*  
810 *Resources* 20, 1-14.
- 811 [47] Kavetski, D., Binning, P., Sloan, S.W., 2001. Adaptive backward Euler time stepping  
812 with truncation error control for numerical modelling of unsaturated fluid flow.  
813 *International Journal for Numerical Methods in Engineering* 53,1301-1322.
- 814 [48] Kees, C.E., Miller, C.T., 2002. Higher order time integration methods for two-phase  
815 flow. *Advances in Water Resources* 25(2), 159-177.
- 816 [49] Brenan KE, Campbell SL, Petzold LR., 1996. *The numerical solution of initial value*  
817 *problems in differential-algebraic equations*. Philadelphia, PA: Society for Industrial  
818 and Applied Mathematics.
- 819 [50] Hindmarsh, A.C., Petzold, L.R., 1995. Algorithms and software for ordinary differential  
820 equations and differential-algebraic equations, Part II: Higher-order methods and  
821 software packages *Computers in Physics* 9(2), 148-155.
- 822 [51] Curtis, A.R., Powell, M.J.D., Reid, J.K., 1974. On the Estimation of Sparse Jacobian  
823 Matrices. *Journal of the Institute of Mathematical Applications* 13, 117-119.
- 824 [52] Hindmarsh, A.C., 1982. Large ordinary differential equation systems and software.  
825 *IEEE Control System Magazine* 2, 24-30.

- 826 [53] Vauclin, M., Khanji, D., Vachaud, G., 1979. Experimental and numerical study of a  
827 transient, two-dimensional unsaturated-saturated water table recharge problem. *Water*  
828 *Resources Research* 15, 1089–1101.
- 829 [54] Forsyth, P.A., Kropinski, M.C., 1997. Monotonicity considerations for saturated-  
830 unsaturated subsurface flow. *SIAM Journal on Scientific Computing* 18, 1328-1354.
- 831 [55] Huang, K., Mohanty, B.P., van Genuchten, M.T., 1996. A new convergence criterion  
832 for the modified Picard iteration method to solve the variably saturated flow equation.  
833 *Journal of Hydrology* 178(1-4), 69-91.
- 834 [56] United Nations Development Program. Assessment of Groundwater Resources of  
835 Lebanon. Ministry of Energy and Water, Beirut, Lebanon.2014.
- 836 [57] Van Vuuren, D., Edmonds, J., Kainuma, M., Riahi, K., Thomson, A., Hibbard, K.,  
837 2011. The representative concentration pathways: an overview. *Climatic Change* 109, 5-  
838 31.
- 839 [58] FAO., 1970. *Projet de Développement Hydro-Agricole: Etude Hydrogeologique De La*  
840 *Plaine D'Akkar. République Libanaise, Ministère des Ressources Hydrauliques et*  
841 *Électriques, Beyrouth, Liban.*
- 842
- 843
- 844