

Experimental and numerical characterization of toluene transport and bioremediation processes using spectral induced polarization

Urie Luli Zohoré, Isis Froment, Aya Nianzou, Pauline Kessouri, Jacques Deparis, Marc Crampon, Roger Guérin, Damien Jougnot

▶ To cite this version:

Urie Luli Zohoré, Isis Froment, Aya Nianzou, Pauline Kessouri, Jacques Deparis, et al.. Experimental and numerical characterization of toluene transport and bioremediation processes using spectral induced polarization. 7th International IP workshop, May 2024, Lund, Sweden. hal-04509223

HAL Id: hal-04509223 https://brgm.hal.science/hal-04509223v1

Submitted on 18 Mar 2024 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Experimental and numerical characterization of toluene transport and bioremediation processes using spectral induced polarization

Urie Luli Zohoré^{1,2}, Isis Froment², Aya Nianzou², Pauline Kessouri², Jacques Deparis², Marc Crampon², Roger Guérin¹, Damien Jougnot¹

¹ Sorbonne Université, CNRS, EPHE, UMR 7619 METIS, 75005 Paris, France, zohore.urie@gmail.com

² BRGM, Service Géologique National, 45060 Orléans, France, zohore.urie@gmail.com

Workshop session: "Characterization of contaminated subsurface and monitoring of dynamic processes"

Is the first and presenting author a student? Yes

Polluted soils are often the result of more or less recent anthropogenic activities, and constitute major societal issues. A recent study (Froger et al., 2021) estimates that 30% of the surface area of France has polycyclic aromatic hydrocarbon (PAH) concentrations in soils above 100 μ g.kg⁻¹. Once in the underground surface, these pollutants pose a risk to groundwater and drinking water supplies. Biodegradation in many regards can be an environmental-friendly remediation technique. This technique involves the decomposition of organic pollutants by micro-organisms. Many studies have highlighted the sensitivity of spectral induced polarization (SIP) to bacterial growth, biodegradation and bacterial activities such as mineral and biofilm production (e.g. Davis et al., 2006; Atekwana and Slater, 2009; Abdel Aal et al., 2010; Kessouri et al., 2019). All these studies focused on describing the influence of biodegradation on SIP without providing a method for quantification. To date, very little work has been done to quantitatively study the SIP response of bacteria in porous media. This work, part of the ANR project IMAGE, aims to develop: (i) petrophysical relationships at a column scale, linking complex conductivity to toluene biodegradation processes and (ii) a process-based inversion scheme coupled with a stochastic approach.

The experimental part uses two columns: one inoculated with *Rhodococcus wratislaviensis* which biodegrades toluene, and an abiotic control column. In fact, the columns form part of a more complete setup (see Figure 1).




Figure 1: Experimental set-up of the open-loop circulation system.

This includes feeding bottles containing the growth media and toluene, a pressurised oxygen supply at 0.5 bar for oxygenation of the solutions, a multiparameter analyser (pH, Eh, dissolved oxygen and electrical conductivity of the fluid), and a peristaltic pump that allows the fluid to circulate at a constant flow rate through the system. Two configurations of fluid circulation were set up in this system. The first one is a closed-loop circulation: the fluid leaving the column flows back into the feed. The purpose of closed-loop circulation is to allow bacterial colonisation of the solid matrix (sand) in the column. The second configuration is an open-loop circulation: the fluid leaving the column (outflow fluid) does not return to the feed and is renewed regularly. This configuration comes close to natural conditions of biodegradation in groundwater. Moreover, in this configuration toluene concentration is monitored in the outflow fluid. Finally, at the end of the experiment, sand samples are collected at different heights in the column for DNA analysis.

It is worth mentioning that this experimental phase is in progress after a first attempt with technical difficulties. The first trial showed a DNA distribution higher at the bottom (194.4 ng/g) compared to the top (11.9 ng/g) of the inoculated column. This distribution is consistent with the expected distribution of toluene in the column. Indeed, bacteria tend to grow close to the point of entry of toluene in the column. The results also show a DNA concentration of 56.6 ng/g at the bottom of the abiotic column, thus revealing a contamination in the abiotic column. In the second trial, we have solved the issues previously encountered.

The second aspect of this work is devoted to forward modelling and inversion. The approach that we develop in this study aims to satisfy two criteria (i) to include in its expression the biogeochemical processes involved in biodegradation and (ii) to provide a more complete exploration of the solution space. In an effort to satisfy these two criteria, we are implementing a stochastic inversion approach. This approach is based on a Markov chain Monte Carlo algorithm. This method will allow the determination a quantitative relationship between complex resistivity and biodegradation parameters such as pollutant quantity, porosity and bacterial concentration.

References

- Abdel Aal G.Z., Atekwana E.A., Rossbach S., Werkema D.D., 2010 Sensitivity of geoelectrical measurements to the presence of bacteria in porous media. Geophysical Research Letters. 115(G3).
- Atekwana E.A., Slater L.D., 2009 Biogeophysics: A new frontier in Earth science research. Reviews of Geophysics, 47, RG4004.
- Davis C.A., Atekwana E., Atekwana, E., Slater, L.D., Rossbach S., Mormile M.R., 2006 Microbial growth and biofilm formation in geologic media is detected with complex conductivity measurements: microbial growth and geophysics. Geophysical Research Letters, 33, L18403.
- Froger C., Saby N., Jolivet C.C., Boulonne L., Caria G., Freulon X., de Fouquet C., Roussel H., Marot F., Bispo A., 2021 Spatial variations, origins, and risk assessments of polycyclic aromatic hydrocarbons in French soils. Soil, 7, 161–178.
- Kessouri, P., Furman, A., Huisman, J. A., Martin, T., Mellage, A., Ntarlagiannis, D., ... & Placencia-Gomez, E. (2019). Induced polarization applied to biogeophysics: recent advances and future prospects. Near Surface Geophysics, 17(6-Recent Developments in Induced Polarization), 595-621.